INCH-POUND
A-A-33C
24 March 2020
SUPERSEDING
A-A-33B
28 July 2009

COMMERCIAL ITEM DESCRIPTION

SCALE REMOVING COMPOUND (LIQUID)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE. This commercial item description (CID) covers a liquid form scale removing compound, hereafter referred to as "compound", intended for removing scale deposits from environmental surfaces, commercial dishwashing machines, and boiler coilers. This compound can be used in laboratories, food handling and processing areas, veterinary areas, and dairy plants.

2. SALIENT CHARACTERISTICS.

2.1 Materials. Unless otherwise specified herein, materials shall be in accordance with the manufacturer's material specifications. The compound shall be a uniform liquid, free of sediments and suspended particles, and shall contain a corrosion inhibiting agent and a wetting agent.

2.1.1 Phosphoric acid (as P_2O_5). The compound shall have a phosphoric acid content of not less than 30.0% and not more than 40.0% when determined in accordance with ASTM D820 Electrometric Titration Method.

2.1.2 Hydrogen-ion concentration (pH). The compound shall have a pH of not more than 2.0 when determined in accordance with ASTM E70.

2.1.3 Citric acid. The compound shall have a citric acid content of more than 6% when determined in accordance with ASTM D4608.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data that may improve this document should be sent to DLA Aviation, VEB, 8000 Jefferson Davis Highway, Richmond, VA 23297-5616 or e-mailed to STDZNMGT@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST database at https://assist.dla.mil

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:57Z
Check the source to verify that this is the current version before use.

2.1.4 Hydrochloric acid (HCl). The compound shall contain not more than 10% HCl when determined in accordance with the manufacturer's standard practice.

2.1.5 Excluded ingredients. The compound shall not contain sulfuric acid or organic solvents.

2.2 Surface tension. The compound shall have a surface tension not greater than 8.08 x 10^{-3} poundals per inch (44.0 dynes per centimeter) when measured in accordance with ASTM D1331 using a sample at 77°F (25°C) in a 1% aqueous solution.

2.3 Corrosive effects on steel. The compound, in a 1% distilled aqueous solution, shall have a corrosive effect on steel of not more than 0.15% loss of mass on 2 inch by 2 inch by 0.053 inch thick (51mm X 51mm X 0.89mm thick) coupons of UNS G10200 hot rolled steel after a 24 hour period of immersion in the compound.

2.4 Nonvolatile matter. The compound shall have a nonvolatile matter content of not less than 30.0% when determined in accordance with ASTM D2834 using a 2 to 3 gram sample weight, 100 mm diameter glass Petri dishes, and a forced draft oven set at 221 ± 4°F (105 ± 2°C) for 16 hours.

2.5 Foaming. The compound shall exhibit no foam at temperatures above 100°F (38°C).

2.6 Identification and markings. Identification and markings shall be permanent and legible and shall include, as a minimum, the manufacturer's identification code (CAGE) and labeling with instructions for use.

3. REGULATORY REQUIREMENTS.

3.1 Safety data sheet (SDS). Manufacturers shall prepare and submit a SDS in accordance with FED-STD-313, "Material Safety Data, Transportation Data and Disposal Data for Hazardous Materials Furnished to Government Activities", and meeting the requirements of 29 Code of Federal Regulations (CFR) § 1910.1200, "Occupational Safety and Health Standards: Hazard Communication".

3.2 Marking, packaging, and labeling. The product shall be labeled, packed and marked in accordance with 49 CFR parts 100 to 185.

3.3 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4. PRODUCT CONFORMANCE PROVISIONS.

4.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:57Z
Check the source to verify that this is the current version before use.

commercial market. Any certificate of analysis (COA) offered with the product to the commercial market shall be provided with each lot or batch of product. The lot or batch number and the date of inspection/analysis from the offer shall be on each COA. A full COA proving the salient characteristics of the product meets government requirements shall be provided upon request.

4.2 Market acceptability. The compound shall have been sold previously to the Government or to the commercial market in order to qualify for acceptability under this CID

5. PACKAGING. Preservation, packaging, and marking shall be as specified in the contract or order (see 6.2).

6. NOTES.

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Source of documents.

6.1.1 Electronic copies of CFR documents can be obtained from https://gov.ecfr.io/cgi-bin/ECFR.

6.1.2 Electronic copies of ASTM documents may be obtained from https://www.astm.org/.

6.1.3 Copies of FED-STD-313 can be obtained from https://quicksearch.dla.mil.

6.2 Ordering data. Acquisition documents must specify the following:

a. Title, number, and date of this CID.
b. The specific issue of individual documents referenced, if required.
c. Packing requirements.

6.3 Cross-reference data. Scale removing compound conforming to this CID is interchangeable/substitutable with scale removing compound conforming to P-S-120B, type II, dated April 8, 1977 (cancelled October 17, 1997 with supersession by this document).

6.4 National stock number (NSN). NSN 6850-00-949-1397 corresponds to this CID. This may not be the only NSN associated with this document.

6.5 Key Words.

Boiler coiler
Dishwashing machine

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:57Z
Check the source to verify that this is the current version before use.

Phosphoric acid

6.6 Changes from previous issues. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

MILITARY INTERESTS:

Custodian:
DLA – GS

CIVIL AGENCY COORDINATING ACTIVITY:
GSA-FAS

Preparing Activity:
DLA – GS3

(Project 6850-2020-002)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:57Z
Check the source to verify that this is the current version before use.