A-A-5A
April 4, 1984
SUPERSEDING
A-A-5
September 18, 1979

COMMERCIAL ITEM DESCRIPTION

DISHWASHING COMPOUND, HAND

(BUILT DETERGENT; FLAKE, GRANULAR OR BEAD)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification P-D-410, Type I, Class 2.

Salient characteristics.

The product shall be a uniform, free-flowing, lump-free drum dried flake, drum dried granular, or spray-dried bead built detergent intended for use in hand dishwashing.

The product shall conform to the requirements listed below:

Characteristic	Requirement	Test Method
Moisture	4.0 percent, maximum	ASTM D 820, # 5-6
Synthetic detergent	15.0 percent, minimum	ASTM D 820, # 46
Condensed Phosphates as phosphorus pentoxide	11.5 percent, minimum	ASTM D 820, # 21-28
Total Alkalinity as sodium oxide	12.0 percent, maximum	ASTM D 820, # 16-17 except calculate to sodium oxide
Silicates as silicon dioxide	6.0 percent, maximum	ASTM D 800, # 18-21
pH of 1.0 percent solution	7.5 - 9.5	ASTM E 70
Bulk Density	0.25 - 0.60 g/ml	ASTM D 2854
Particle size:		
Retained on No. 16 sieve	10.0 percent maximum	ASTM D 502
Retained on No. 170 sieve	90.0 percent minimum	ASTM D 502

The issues of the referenced test methods in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Rinsing properties. The product shall be free-rinsing when tested as follows: Prepare synthetic hard water by dissolving 0.404 g calcium chloride dihydrate and 0.136 g magnesium chloride hexahydrate per liter of final solution at 25 degrees C. Place 0.5 g of the hand dishwashing compound and 98 ml synthetic hard water into a clean and spotless 250 ml Erlenmeyer flask at room temperature.

Stopper the flask and shake vigorously for 1 minute. Pour out the solution. Rinse the flask with three 75 ml portions of synthetic hard water. Invert the flask and allow to dry. Rinse another clean and spotless 250 ml Erlenmeyer flask with three 75 ml portions of synthetic hard water. Invert this flask and allow to dry. Examine both flasks for any residue not rinsed from the interior. There shall be no more residue in the flask into which the dishwashing compound was placed than in the flask which was rinsed with hard water alone.

The containers shall be labeled with directions for use of the hand dishwashing compound. The containers shall be labeled in accordance with the Federal Hazardous Substances Act Regulations (Code of Federal Regulations Title 16, Part 1500).

Preservation, packaging, packing, labeling and marking. Preservation, packaging, packing, labeling and marking shall be as specified in the contract or order.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:56Z
Check the source to verify that this is the current version before use.

NOTES:

ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

Users of this commercial item description shall state in the contract the size containers of hand dishwashing compound required.

Requirements for hand dishwashing compound conforming to P-D-410, Type I, Class 1 have been deleted from this CID due to lack of procurement requirements.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:56Z
Check the source to verify that this is the current version before use.