[METRIC]
A-A-5B
April 2, 1998
Superseding
A-A-5A
April 4, 1984

COMMERCIAL ITEM DESCRIPTION

DISHWASHING COMPOUND, HAND
(BUILD DETERGENT; FLAKE, GRANULAR OR BEAD)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. Scope. This commercial item description covers a built detergent for dishwashing by hand.

2 Salient Characteristics:

2.1 The product shall be a uniform, free-flowing, lump-free drum dried flake, drum dried granular, or spray-dried bead built detergent for use in hand dishwashing.

2.2 The product shall conform to the following requirements:

Characteristic	Requirement	Test Method
Moisture	4.0 percent, max.	ASTM D 820, #5-6
Synthetic detergent	15.0 percent, min.	ASTM D 820, #46
Condensed Phosphates as phosphorus pentoxide	11.5 percent, min.	ASTM D 820, #21-28
Total alkalinity as sodium oxide	12.0 percent, max.	ASTM D 820, #16-17 (except calculate to sodium oxide)
Silicates as silicon dioxide	6.0 percent, max.	ASTM D 800, 18-21
pH of 1.0 percent solution	7.5 - 9.5	ASTM E 70
Bulk density	0.25 - 0.60 g/ml	ASTM D 2854
Particle size:		
Retained on No. 16 sieve	10.0 percent, max.	ASTM D 502
Retained on No. 170 sieve	90.0 percent, max	ASTM D 502

Beneficial comments, recommendations, additions, deletions, clarification, etc., and any data which may improve this document, should be sent to: GSA, Paints and Chemicals Center, 400 15th Street, S.W., Auburn, WA 98001.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-24T02:56Z
Check the source to verify that this is the current version before use.

Rinsing properties. The product shall be free-rinsing when tested as follows: Prepare synthetic hard water by dissolving 0.404 g calcium chloride dihydrate and 0.136 g magnesium chloride hexahydrate per liter of final solution at 25^0C. Place 0.5 g of the hand dishwashing compound and 98 ml synthetic hard water into a clean and spotless 250 ml Erlenmeyer flask at room temperature.

Stopper the flask and shake vigorously for 1 minute. Pour out the solution. Rinse the flask with three 75 ml portions of synthetic hard water. Invert the flask and allow to dry. Rinse another clean and spotless 250 ml Erlenmeyer flask with three 75 ml portions of synthetic hard water. Invert this flask and allow to dry. Examine both flasks for any residue not rinsed from the interior. There shall be no more residue n the flask into which the dishwashing compound was placed than in the flask which was rinsed with hard water alone.

3. Product Conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

4. Notes.

4.1 The contractor may use his normal quality assurance procedures for manufacture of this product; however, should a disagreement arise between the Government and its customer or between the Government and the manufacturer concerning compliance to the salient characteristics of this commercial item description, the test methods and tests stated in this commercial item description will be used to determine compliance of the product.

4.2 ASTM standards are available from the American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

PREPARING ACTIVITY:
GSA - FSS

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 202610-24T02:56Z
Check the source to verify that this is the current version before use.