# MILITARY SPECIFICATION

## FUZE, MTSQ, M776
## LOADING, ASSEMBLING AND PACKING

This Specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements and quality assurance provisions for the loading, assembling and packing of the M776 Mechanical Time Super Quick (MTSQ) Fuze.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

MIL-A-48078 - Ammunition, Standards Quality Assurance Provisions, General Specification for

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1390
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-105 | - Sampling Procedures and Tables for Inspection by Attributes |
| MIL-STD-331 | - Fuze and Fuze Components, Environmental and Performance Test for |
| MIL-STD-414 | - Sampling Procedures and Tables for Inspection by Variables for Percent Defectives |

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT DRAWINGS

| | |
|---|---|
| 12361000 | - Fuze, MTSQ, M776 |

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specification sheets or MS standards) the text of this specification shall take precedence. Nothing in this specification, however shall supersede applicable laws and regulation unless specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Fuze assembly. The M776 MTSQ fuze assembly shall comply with all requirements specified in drawing (dwg.) 12361000 and with all requirements specified in applicable specifications.



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:53Z
Check the source to verify that this is the current version before use.

3.3 Transportation vibration. The fuze assembly shall comply with the requirements of MIL-STD-331A, Test 123, and of 3.8.1, 3.8.3 and 3.8.5.

3.4 Jolt and jumble. The fuze assembly shall comply with the requirements of MIL-STD-331A, Test 101.3, Procedure 2 and Test 102.2.

3.5 Drop test, 1.5 meter. The fuze assembly shall comply with the requirements of MIL-STD-331A, Test 111.1.

3.6 Waterproofness. The fuze assembly shall comply with the requirements of MIL-STD-331A, Test 108, except that the duration of immersion shall be five (5) minutes minimum and the pressure shall be three (3) psig min.

3.7 Torque. The fuze assembly timer setting section shall not move when a torque of 30 kpcm min. is applied. The timer setting section shall move when a torque of 55 kpcm max. is applied.

3.8 Ballistic performance (proving ground).

3.8.1 Premature burst. There shall be no premature burst or metal parts failure in the mortar tube or in the first 100 meters of flight.

3.8.2 Arming safety. The fuze shall not function on impact against a 25mm min. plywood screen positioned at a distance of 40 meters +/- 1 meter.

3.8.3 Fuze functioning time (70°F). The fuze, when set in the time mode, shall cause the projectile to function within the upper (UL) and lower (LL) time limits and shall not exceed the maximum allowable percent defective as specified below.

| Set Time (sec) | Function Time Limits (sec) | |
|---|---|---|
| 19.0 | LL = 18.00 | UL = 20.00 |
| 26.0 | LL = 25.00 | UL = 27.00 |

| Sample Size (see 6.4) | Maximum Allowable Percent Defect |
|---|---|
| 30 | 2.83 |
| 20 | 2.95 |
| 10 | 3.26 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

3.8.4 Extreme temperature fuze functioning time. The fuze, when set in the time mode, and conditioned at -50°F or 145°F, shall cause the projectile to function within the upper (UL) and lower (LL) time limits and shall not exceed the maximum allowable percent defective requirement as specified below.

| Set Time (sec) | Function Time Limits (sec) | |
|---|---|---|
| 26.0 | LL = 24.50 | UL = 27.50 |

| Sample Size (see 6.4) | Maximum Allowable Percent Defect |
|---|---|
| 30 | 2.83 |
| 10 | 3.26 |

3.8.5 Fuze failure. When a fuze is set to function in the air and functions on impact or does not function at all, it shall be considered a dud.

3.9 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspections in accordance specified herein. (see 4.3 and 6).

3.10 Workmanship. All parts and assemblies shall be fabricated in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, rust and other foreign matter. The cleaning methods shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coating shall be uniform and continuous except for a few light scratches not exposing any base material. All required markings shall be neat and sharply defined.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual nor does it commit the Government to acceptance of any defective material.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item.

a. First Article Inspection (see 4.3)

b. Quality Conformance Inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

| Part Description | Drawings | Quantity |
|---|---|---|
| Fuze, MTSQ, M776 | 12361000 | 200 |

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3. Rejection. See MIL-A-48078.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

**CLASSIFICATION OF DEFECTS & TESTS**

MIL-F-70713 (AR)

| PARAGRAPH | TITLE: Fuze, MTSQ, M776 | | SHEET 1 OF 1 | | DRAWING NUMBER: 12361000 |
|---|---|---|---|---|---|
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| | Fuze, MTSQ, M776 (Dwg. 12361000) | | | | |
| | Examination for Defects | 200 | | 3.2 | 4.4.2.1 |
| | Transportation Vibration Test Samples Premature During MIL-STD-331A, Test no. 19, Procedure 2 | 20(a) | | 3.3 | 4.5.1 |
| | Jolt and Jumble Test | 18(a) | | 3.4 | 4.5.2 |
| | 1.5 Meter Drop Test | 10(a) | | 3.5 | 4.5.3 |
| | Waterproofness Test | 10(a) | | 3.6 | 4.5.4 |
| | Torque Test | 10(a) | | 3.7 | Gage |
| | Transportation Vibration Test Samples Premature During Ballistic Test | 20(a) | | 3.3 | 4.5.1 |
| | Transportation Vibration Fuze Failures | 20(b) | | 3.3 | 4.5.1 |
| | Premature Burst | 120(c) | | 3.8.1 | 4.5.5.2 |
| | Function in Arming Safety | 12(a) | | 3.8.2 | 4.4.5.1 |
| | Estimated Lot Percent Defective | 140(c) | | 3.8.3 | 4.4.5.2 |
| | | | | 3.8.4 | 4.4.5.2 |
| | Fuze Failures | 120(d) | | 3.8.5 | 4.4.5.2 |

NOTES: (a) One (1) or more defectives shall cause the first article to be rejected.
(b) Two (2) or more fuze failures shall cause the first article to be rejected.
(c) One (1) or more groups exceeding the lot percent defectives shall cause the first article to be rejected.
(d) Three (3) or more fuze failures shall cause the first article to be rejected.

AMSMC Form 1570a, 1 Apr 85 Replaces DRDAR-QA Form 160a, 1 Jun 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lot shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot of fuzes shall contain:

a. Fuze components from one lot interfix number from one manufacturer.

b. Expelling charges of one lot interfix number from one manufacturer.

4.4.2. Examination. See MIL-A-48078. Unless otherwise specified in the classification of Defects and Test Tables, sampling plans shall be in accordance with MIL-STD-105, Inspection Level II.



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:53Z
Check the source to verify that this is the currentversion before use.

## CLASSIFICATION OF DEFECTS & TESTS



| PARAGRAPH | TITLE | SHEET | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Fuze, MTSQ, M776 (Prior to Assembly of Base Plug and After Assembly of Clamp Screw | 1 OF 1 | 12361000 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | | | | | |
| 1 | Rotor not engaged to set back pins | | 100% | 3.2 | Visual |
| 2 | Safety arbor not engaged to rotor slot | | 100% | 3.2 | Visual |
| Major | | | | | |
| 101 | Safety cotter less than 23.5mm | | 0.40% | 3.2 | Gage |
| 102 | Detonator missing or improperly assembled | | 0.40% | 3.2 | Visual |
| 103 | External thread (1.5"-12 UNF-1A) | | 0.40% | 3.2 | Gage |
| 104 | Fuze intrusion length | | 0.40% | 3.2 | Gage |
| 105 | Fuze setting torque | | 0.40% | 3.7 | Gage |
| Minor | | | | | |
| 201 | Fuze improperly marked | | 0.65% | 3.2 | Visual |
| 202 | Evidence of poor workmanship | | 0.65% | 3.10 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

## QUALITY CONFORMANCE INSPECTION

## CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70713 (AR)

| PARAGRAPH | TITLE | | SHEET 1 OF 1 | | DRAWING NUMBER |
|---|---|---|---|---|---|
| 4.4.2.2 | Fuze, MTSQ, M776, Destructive Lot Acceptance Testing | | | | 12361000 |
| | | | | | NEXT HIGHER ASSEMBLY |
| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
| Critical | | | | | |
| 1 | Transportation vibration test samples premature during MIL-STD-331A, test no. 19, procedure 2 and premature burst during firing | 10(a) | | 3.3 | 4.5.1 |
| 2 | Premature burst in ballistic test | 60(a) | | 3.8.1 | 4.5.5.2 |
| 3 | Function in arming safety test | 12(a) | | 3.8.2 | 4.5.5.1 |
| 4 | Jult and jumble test | 9(a) | | 3.4 | 4.5.2 |
| 5 | 1.5 meter drop test | 10(a) | | 3.5 | 4.5.3 |
| Major | | | | | |
| 101 | Waterproofness test | 5 | | 3.6 | 4.5.4 |
| 102 | Transportation vibration fuze failures | 10(b) | | 3.3 | 4.5.1 |
| 103 | Estimated lot percent defectives | 70(c) | | 3.8.3 | 4.5.5.2 |
| 104 | Fuze failures | 60(d) | | 3.8.5 | 4.5.5.2 |

NOTES:
(a) One (1) or more defectives shall cause the lot to be rejected.
(b) Two (2) or more fuze failures shall cause the lot to be rejected.
(c) One (1) or more groups exceeding the estimated lot percent defectives shall cause the lot to be rejected.
(d) Two (2) or more fuze failures shall cause the lot to be rejected.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

## QUALITY CONFORMANCE INSPECTION

### CLASSIFICATION OF DEFECTS & TESTS

| PARAGRAPH | TITLE | SHEET 1 OF 1 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.3 | Pack, Complete (Before and After Sealing) | | 42.700-004.0 |
| | | | NEXT HIGHER ASSEMBLY |

| CATEGORY | EXAMINATION OR TEST | NO. OF SAMPLE UNITS | AQL OR 100% | REQUIREMENT PARAGRAPH | PARAGRAPH REFERENCE /INSPECTION METHOD |
|---|---|---|---|---|---|
| Critical | None defined | | | | |
| Major | | | | | |
| 101 | Incorrect number of fuzes | | 0.40% | 5.1 | Visual |
| 102 | Upper and lower halves improperly coupled | | 0.40% | 5.1 | Visual |
| 103 | Spacer missing | | 0.40% | 5.1 | Visual |
| 104 | Liner missing | | 0.40% | 5.1 | Visual |
| 105 | Wood box improperly sealed | | 0.40% | 5.1 | Visual |
| Minor | | | | | |
| 201 | Marking missing or unidentifiable | | 0.65% | 5.1 | Visual |
| 202 | Evidence of poor workmanship | | 0.65% | 3.10 | Visual |

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See section 6 of MIL-A-48078 and 6 of this specifications.

4.5 Methods of inspection.

4.5.1 Transportation vibration. The test shall be performed on complete fuze assemblies (dwg. 12361000) set "S". The test shall be conducted in accordance with the procedures outlined in MIL-STD-331A, Test 123. The sampled fuzes shall then be fired as detailed in 4.5.5.2. If any fuze becomes unsafe or inoperable following the test, then the fuze shall be classed defective. In addition, the fuzes shall meet the requirement of 3.8.3.

4.5.2 Jolt and jumble. The test shall be performed on complete fuze assemblies (dwg. 12361000) set "S". The jolt test shall be conducted in accordance with the procedures outlined in MIL-STD-331A, Test 101.3, Procedure I. Following the completion of the jolt test, the fuzes shall be subjected to the jumble test in accordance with the procedures of MIL-STD-331A, Test 102.2.

4.5.3 Drop test, 1.5 meter. The complete fuze assemblies without the pull wires, set "S", shall be assembled to inert loaded projectiles as specified in the contract and be subjected to the 1.5 meter drop test. The test shall be conducted in accordance with the procedures outlined in MIL-STD-331A, Test 111.1, Procedure 1. After this test, the fuzes shall be disassembled to determine the fuzes have been armed or become unsafe in anyway. If so, the condition shall be classed defective.

4.5.4 Waterproofness. The complete fuze assemblies shall be subjected to the waterproofness test. The waterproofness test shall be tested in accordance with the procedures outlined in MIL-STD-331A, Test 108, except as provided in 3.6. After the test, the fuzes shall be disassembled and examined under ultra-violet light. Any assembly that has evidence of any water entry shall be classed defective.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

4.5.5 Ballistic test.

4.5.5.1 Arming safety. The fuzes shall be assembled to inert filled 60mm cartridges. The fuze shall be set "S", fired at charge 1 at zero (0) degree elevation, against a one inch plywood screen set at 40 +/- 1 meters from the muzzle. If any fuze functions upon impacting the screen, the fuze shall be classed as a defective. The fuze may function behind the screen.

4.5.5.2 Fuze functioning time. The sampled fuzes shall be assembled to 60mm, M721 cartridges and fired from an M224 mortar at elevations between 800 mils and 1511 mils for air burst functioning. All fuze settings shall be photographed using an instant, self processing camera. Three independent infrared sensing chronograph systems or equivalent shall be used to measure time of burst. The three recorded time values for each round shall be rounded to the nearest .01 second. At least two time values are necessary to calculate the estimate of lot percent defectives. The estimate of lot percent defective shall be calculated using methods prescribed in MIL-STD-414, Example B3.

5. PACKAGING

5.1 Packing, packaging, marking. Packaging, packing and marking shall be in accordance with 42.700-004.0 and requirements in the contract or purchase order.

6. NOTES

6.1 Intended use. The M776 MTSQ fuze is intended for use on 60mm mortar ammunition.

6.2 Ordering data. See MIL-A-48078 (PA).

6.3 Submission of design for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required, to Commander, AMCCOM, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Requirement List DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Performance test summary (proving ground ballistic).

6.4.1 First article inspection test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

6.4.1.1 Arming safety.

| Cartridge | Charge | QE (mils) | Set | Quantity |
|---|---|---|---|---|
| Inert 60MM | 1 | 0 | "S" | 12 |

6.4.1.2 Fuze time functioning at 70° F.

| Cartridge | Charge | QE (mils) | Set Time | Quantity |
|---|---|---|---|---|
| M721 | 1 | 1511 | 19.0 sec | 20 (a) |
| M721 | 1 | 1511 | 19.0 sec | 30 |
| M721 | 4 | 800 | 26.0 sec | 30 |

(a) Transportation vibration samples

NOTE: The fuzes shall be conditioned at 70° F for a minimum of four (4) hours.

6.4.1.3 Extreme temperatures fuze time functioning.

| Cartridge | Charge | QE (mils) | Set Time | Quantity |
|---|---|---|---|---|
| M721 | 4 | 800 | 26.0 sec | 30 (b) |

(b) Thirty fuzes each shall be conditioned at -50° F and 145° F for a minimum of four (4) hours.

6.4.2 Quality Confromance test.

6.4.2.1 Arming safety.

| Cartridge | Charge | QE (mils) | Set | Quantity |
|---|---|---|---|---|
| Inert 60mm | 1 | 0 | "S" | 12 |

6.4.2.2 Fuze time functioning at 70° F

| Cartridge | Charge | QE (mils) | Set Time | Quantity |
|---|---|---|---|---|
| M721 | 1 | 1511 | 19.0 sec | 10 (a) |
| M721 | 1 | 1511 | 19.0 sec | 20 |
| M721 | 4 | 800 | 26.0 sec | 20 |

(a) Transportation vibration samples.

NOTE: The fuzes shall be conditioned at 70° F for a minimum of four (4) hours.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

6.4.2.3 Extreme temperatures fuze time functioning.

| Cartridge | Charge | QE (mils) | Set Time | Quantity |
|---|---|---|---|---|
| M721 | 4 | 800 | 26.0 sec | 10 (b) |

(b) Ten (10) fuzes each shall be conditioned at -50° F and 145° F for a minimum of four (4) hours.

6.5 Required number of data points. The number of reading(s) to be used for the estimated percent defective shall be no less than eight (8) for a sample group of ten (10), seventeen (17) for a thirty (30). The number of readings used as a basis shall exclude duds, off times and lost times. If there are insufficinet rounds in any group, it is the Governments option to require additional rounds to be fired under the conditions of the group, until sufficient in accordance with the above.

6.6 Subject term (keyword) listing.

Cartridge, illuminating, M721
Fuze, mechanical time super quick, M776
Testing arming safety

Custodian:
Army-AR

Preparing activity:
Army-AR
(Project 1390-A578)



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:53Z
Check the source to verify that this is the currentversion before use.

**INSTRUCTIONS:** In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

*NOTE:* This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

*(Fold along this line)*

*(Fold along this line)*

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:53Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

*(See Instructions – Reverse Side)*

| 1. DOCUMENT NUMBER | 2. DOCUMENT TITLE |
|---|---|
| MIL-F-70713 | FUZE, MTSQ, M776 LOADING, ASSEMBLING AND PACKING |

| 3a. NAME OF SUBMITTING ORGANIZATION | 4. TYPE OF ORGANIZATION *(Mark one)* |
|---|---|
| | ☐ VENDOR<br>☐ USER<br>☐ MANUFACTURER<br>☐ OTHER *(Specify)*: _____ |
| b. ADDRESS *(Street, City, State, ZIP Code)* | |

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

| 7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional | b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional |
|---|---|
| c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional | 8. DATE OF SUBMISSION *(YYMMDD)* |

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 20260410-23T03:53Z
Check the source to verify that this is the current version before use.