A-A-219A
June 1, 1988
SUPERSEDING
A-A-219
April 21, 1981

COMMERCIAL ITEM DESCRIPTION

# HINGE, BUTT
# (CABINET)

The General Services Administration, has authorized the use of this commercial item description in preference to Federal Specification FF-H-116, in part.

This commercial item description covers commercial and industrial quality full mortise hinges, edge mounted on cabinets with flush doors.

Salient characteristics:

The cabinet hinges shall be in accordance with ANSI/BHMA Standard A156.9 identifying number B81352 (wrought steel, grade 2) or B81353 (wrought steel, grade 3) as specified.

Hinge size: Hinge size shall be as specified in the contract or purchase order and shall be defined in terms of length of joint, minimum open width, and minimum thickness if applicable. Table I shows those sizes most often required for Government use.

TABLE I

| Length of Joint (nominal) | Minimum thickness | Minimum width open |
|---|---|---|
| 1 (25.4) | Ø.Ø45 (1.14) | 1-3/16 (3Ø.16) |
| 1-1/2 (38.1) | Ø.Ø45 (1.14) | 1-3/8 (34.93) |

1/ Dimensions shown in table I are inches, with approximate millimeter equivalents shown in parenthesis.

Dimensional tolerances: The dimensional tolerance for length of joint shall be ± 1/16 inch (1.6 mm). Tolerance limits specified are absolute limits as defined in ASTM Recommended Practice E29, for Indicating Which Places of Figures Are to Be Considered Significant in Specified Limiting Values.

Finish. The surface of the hinge shall be electroplated zinc coated in accordance with finish code 6Ø3 or bright brass plated, clear coated in accordance with finish code 632 of ANSI/BHMA A156.18 as specified.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026Ø-26T08:05Z
Check the source to verify that this is the current version before use.

Pins. The hinge pin shall be fast with spun or riveted ends. The pin material shall be brass or steel.

Hardware. All fasteners required for attachment shall be included with the hinges. Fasteners furnished shall be of the size appropriate for hinge furnished.

Workmanship. The hinges furnished shall be free from imperfections which may impair durability or serviceability.

Quality Assurance Provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Sampling.

Lot. All hinges of the same size, and finish presented for acceptance at one time shall be considered a lot for purposes of inspection.

Sampling for quality conformance examination. A random sample of hinges shall be selected from each lot in accordance with Military Standard MIL-STD-105 `Sampling Procedures And Tables For Inspection By Attributes'.

Visual and dimensional inspection. Samples shall be selected in accordance with MIL-STD-105, special inspection level S-3, AQL 2.5 expressed in terms of percent defective. The sample hinges shall be visually and dimensionally examined to verify compliance with this specification.

Testing for performance set and finish. Samples shall be selected in accordance with ANSI/BHMA A156.9. The sample hinges shall be tested in accordance with ANSI/BHMA A156.9.



Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:05Z
Check the source to verify that this is the current version before use.

Certification of performance and finish test requirements. When specified in the contract or purchase order, a certificate of conformance may be furnished in lieu of actual testing on a lot by lot basis providing that:

(1) Objective evidence dated not more than one (1) year prior to the date of the start of the contract as described in the solicitation or date of the purchase order as applicable shall be available.
(2) Tests specified in the industry standards referenced herein have been performed by an independent test facility acceptable to the Government.
(3) That the product being offered is the same type, material and finish and has been manufactured using the same material, processes and manufacturing techniques as the product tested.
(4) By furnishing a certificate of conformance in lieu of performing tests the supplier agrees to perform or have performed as applicable additional tests at the request of the Government when deemed necessary.

Examination for preparation for delivery A random sample of unit, intermediate and shipping containers (as applicable) shall be selected from each lot and examined for conformance with the preservation, packaging, packing, labeling and marking required in the contract or order. Samples shall be selected in accordance with MIL-STD-105, Inspection level II, AQL 6.5 expressed in terms of defects per hundred unit.

Preservation, packaging, packing, labeling, and marking (Civil Agencies). The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Packaging (DOD). The packaging shall be in accordance with ASTM Standard D3951 'Commercial Packaging, Practice for'.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products are allowed under this commercial item description unless otherwise specified.



Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the current version before use.

Notes:
Ordering activities should specify number B81352 (grade 2) or B81353 (grade 3), size, finish and if certification is acceptable in lieu of testing on a lot by lot basis.

The COMMERCIAL ITEM CERTIFICATION CLAUSE is not required when this commercial item description is used for procurement.

ANSI/BHMA standards are available from the Builders Hardware Manufacturers Association, Inc., 60 East 42nd Street, New York, NY 10165.

Copies of Military Standard 105 are available from the Naval Publications and Forms Center, 5801 Tabor Ave., Philadelphia, PA 19120.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 1910З.

The standards referenced in this document shall be the issues in effect on the date of the invitation for bids or request for quotation and shall be used to determine compliance with these requirements. In the event that there is a conflict between this document and a standard referenced herein, this document shall take precedence.

MILITARY INTERESTS:

Military Coordinating Activity:

Army - AR

Custodians:

Army - AR
Air Force - 99

Review Activitits:

Army - AR
Navy - MC
DLA - IS

User Activities:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

VA - VOC

PREPARING ACTIVITY:

GSA - FSS



Source: https://assist.dla.mil -- Downloaded: 202610-26T08:05Z
Check the source to verify that this is the current version before use.