[METRIC]

A-A-561A
January 19, 1994
SUPERSEDING
A-A-561
July 1, 1981

COMMERCIAL ITEM DESCRIPTION

RACKS, RUBBER STAMP

The General Services Administration has authorized the use of this commercial item description

1. SCOPE: This commercial item description covers racks for holding rubber stamps. The rubber stamp racks shall be of the following types and sizes, as specified.

Type I - Wheel rack

Size 1 Six stamps (1 wheel)
Size 2 Fourteen stamps (2 wheels)
Size 3 Twenty-four stamps (3 wheels)

Type II - Strip rack

2. SALIENT CHARACTERISTICS:

A. Construction.

Type I rack. The type I rack shall consist of a base, wheel(s), extension stud(s), and a locking device. The base, extension studs, and locking device shall be provided with appropriate threads.

Base. The base shall be circular, hexagonal, or octagonal in shape and not less than 13.34 cm (5-1/4)" in diameter. Hexagonal and octagonal bases shall be measured across the flats to determine measurement. The rack shall be stable during normal usage.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document, should be sent to: General Services Administration, Federal Supply Service, 26 Federal Plaza, New York N.Y. 10278 ATTN: Engineering Branch (2FYEE).

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

Wheels. The wheels shall be designed to revolve easily and smoothly when the locking device and extension studs are securely tightened. Spring tension clips shall be permanently attached to the wheels. The clips shall be designed for holding rubber stamp handles with a holding area diameter of 12.7 ± 3.18 mm (1/2 ± 1/8 ") . The rack shall have the number of wheels indicated for the respective capacities.

Extension studs. The extension studs shall have a minimum cross sectional diameter of 9.53 mm (3/8") and shall be of sufficient length to provide a minimum distance of 7.30 cm (2-7/8") between wheels, and between the bottom wheel and the base.

Locking device. The locking device shall be designed to hold the top wheel in place, and shall lock tight against the shoulder of the stud when tightened.

Type II rack. The type II rack shall be designed for fastening to a flat vertical surface with screws. Two appropriate wood screws shall be furnished. The rack shall consist of 9 tension clips permanently attached to a flat metal strip which shall have a hole at each end. The strip shall be 30.48 ± 2.54 cm (12 ± 1 ") in length, not less than 11.11 mm (7/16") in width, and not less than 2.38 mm (3/32") thick. The clips shall be designed for holding rubber stamp handles with a holding area diameter of 12.7 ± 3.18 mm (1/2 ± 1/8 ").

Finish and color. The spring tension clips shall be bright nickel or chrome plated. Stainless steel, if used, shall have a No.4 general purpose polished finish. Unless made of corrosion resistance material, the other parts of the rack shall be bright nickel or chrome plated, or shall have a gray baked enamel finish. The enamel finish shall level out to produce a uniform surface and color without runs, grit, areas of thin film, chips, flaking, and cracks.

Identification marking. Each rack shall be marked with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

Materials. The base, wheel(s), and stud(s) of the type I rack, and the flat strip of the type II rack shall be metal suitable for finishing as required. The locking device for the type I rack may be fabricated of metal or plastic. Spring tension clips for type I and II racks shall be full hard cold-rolled steel not less than 0.64 mm (0.025") in thickness and shall retain its shape and spring tension after being formed. Alternatively, at the option of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

supplier, spring tension clips may be fabricated from 400 series (AISI) quarter hard stainless steel not less than 0.51 mm (0.020") in thickness. The width of the steel for spring tension clips shall be 9.53 ± 1.59 mm (3/8 ± 1/16 ").

B. Workmanship. All parts shall be free from burrs, slivers, and sharp edges. The racks shall be free from defects and imperfections which affect appearance or impair serviceability.

3. QUALITY ASSURANCE:

A. Responsibility for Inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this Commercial Item Description, where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

B. Contractor Certification. The contractor shall certify and maintain substantiating evidance that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices.

C. Sampling. Samples shall be selected for inspection in accordance with MIL-STD-105. A lot shall consist of a number of sample units manufactured by the same process from the same components at the same time. Random samples shall be drawn from each lot for the end item inspection. The sample unit shall be one rack. The inspection level for construction and workmanship shall be S-4 and the AQL shall be 4.0 percent defective.

4. REGULATORY REQUIREMENTS: The offeror/contractor is encouraged to use recovered materials in accordance Paragraph 23.403 of the Federal Acquisition Regulation.

5. PACKAGING, PACKING, MARKING AND PALLETIZATION: Shall be as specified in the contract or purchase order.

6. REFERENCED DOCUMENTS: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this commercial item description.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

A. Federal Regulations:

Federal Acquisition Regulation. Paragraph 23.403

Copies of the U.S. Code may be obtained through the Congressional Sales Office, U.S. Government Printing Office, Washington D.C. 20402.

B. Military Standard

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

Available from: Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, or as directed by the contracting officer.

7. NOTES: Purchasers shall specify the following in the contract or purchase order.

A. Ordering Data.

(1). Title, number, and date of this Commercial Item Description
(2). Type and size of wheel racks required.
(3). Unit of issue and quantity
(4). Packaging, packing, marking and palletization requirements.

B. Item Identifiers/Reference Part Number System (for cataloging use only)

A-A-561 1 b — This example describes a wheel rack with two wheels for fourteen stamps

- b: a - Size 1 Six stamps (1 wheel); b - Size 2 Fourteen stamps (2 wheels); c - Size 3 Twenty-four stamps (3 wheels)
- 1: 1 - Type I - Wheel rack; 2 - Type II - Strip rack

MILITARY INTERESTS:

DoD has no registered interest in revisions and amendments to this commercial item description until further notice.

PREPARING ACTIVITY:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.