A-A-50163
April 20, 1988

COMMERCIAL ITEM DESCRIPTION

CRUETS, COMMUNION

The General Services Administration has authorized the use of this commercial item description in preference to Item 2 of MIL-F-43381.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The glass cruets shall be fabricated of either a lime or a lead flint glass and may be either handmade or machine made. The cruets shall have a minimum of 4 ounce capacity and shall measure approximately 4 inches from the base to the top of the cruet without the stopper. The stopper shall be all glass and measure approximately 2 inches in height. The cruets shall include an all glass handle which is consistent with standard commercial practice. All glass surfaces and edges shall be free from defects. The design of the cruets may be specified by the procuring activity. The cruets shall be procured in pairs.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3. PACKAGING

3.1 Packaging. Each pair of cruets, with stoppers, shall be wrapped in flexible cellular plastic film (bubble pack) or at least two thicknesses of tissue paper. Each pair of wrapped cruets shall be placed in a snug-fitting fiberboard box. Cushioning shall be applied, as necessary, to immobilize the cruets and fill voids in the box.

FSC 9925

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

3.2 Packing. Forty-eight cruets (twenty-four pair), packaged as specified, shall be packed in a snug-fitting shipping container conforming to style RSC, type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids and of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

3.3 Palletization. When specified (see 4.2), cruets shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded by means K and L, or O or P, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contract or purchase order, unit packs, shipping containers and unitized pallet loads shall be marked in accordance with MIL-STD-129.

4. NOTES

4.1 Intended use. The cruets described in this document are intended for Chapel use by Army, Navy, and Air Force Chaplains under noncombat conditions.

4.2 Ordering data.

a. Title, number, and date of this document.
b. When palletization is required (see 3.3).

MILITARY INTERESTS:

Custodians

Army - GL
Navy - PE
Air Force - 28

Review activities

Armed Forces Chaplians Board
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 9925-1007

☆U.S. GOVERNMENT PRINTING OFFICE: 1988 — 505-033/91769

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.