A-A-50165
April 21, 1988

COMMERCIAL ITEM DESCRIPTION

BATTING, COTTON, NONABSORBENT, UNBLEACHED

The General Services Administration has authorized the use of this commercial item description in preference to CCC-B-606.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers nonabsorbent, unbleached cotton batting of one type in the following grades (see 5.2):

Grade A - 50-percent, 3/4-inch fibers
Grade B - 50-percent, 1/2-inch fibers

2. SALIENT CHARACTERISTICS

2.1 General. The batting shall be made from unbleached, nonabsorbent cotton, natural color, which is cleaned and garnetted to produce continuous unbroken sheets of uniform thickness in the weights and dimensions specified in 2.3. The Grade A batting shall have a minimum of 50 percent new cotton fibers having a 3/4 inch minimum staple length. The Grade B batting shall have a minimum of 50 percent new or reworked cotton having a 1/2 inch minimum staple length.

2.2 Physical requirements.

2.2.1 Ash. The cotton ash residue shall not exceed two percent when tested in accordance with Fed. Std. 191A, Method 2611.

FSC 8320

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

2.2.2 Absorbency. The cotton shall be nonabsorbent such that the cotton batting will not submerge in water within 15 minutes when tested as specified in 3.2.

2.3 Put-up. The batting shall be furnished with a separator strip running its length which shall be rolled together tightly and evenly according to the batting sizes and weights outlined below:

Size	Width (inches)	Batting weight (oz/linear yard)	Nominal length (yd)
1	12	5.3	3
2	27	12.0	20

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of the description and conforms to the producer's own drawings, specifications, standards and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic, the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3.2 Method for testing absorbency. The test specimen shall be 10 grams of cotton batting folded into a 4 inch square. The specimen shall be held parallel and close to the surface of distilled water at 77° ± 4°F, dropped lightly upon the water, and the time required for the specimen to completely submerge shall be recorded to the whole second. Five determinations shall be made and the results averaged.

4. PACKAGING

4.1 Packaging. Batting, put-up as specified in 2.3, shall be wrapped in minimum 30 pound basis weight kraft paper.

4.2 Packing. Twelve rolls, packaged as specified in 4.1, shall be compressed into a bale, strapped and placed in a snug-fitting plastic bag conforming to A-A-1668. The plastic bag shall have a nominal thickness of 0.005 inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.

DSM DO NOT constitute or imply authorization ... requirements on current contracts. Comments submitted on this

4.3 Palletization. When specified (see 5.2), batting, packed as specified in 4.2, shall be palletized in accordance with load type II of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 89 for size 1 and 83 for size 2, in accordance with the appendix of MIL-STD-147.

4.4 Marking. In addition to any marking required by the contract or purchase order, unit packs, bales and palletized unit loads shall be marked in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The nonabsorbent, cotton batting covered in this commercial item description is to be used for wadding.

5.2 Ordering data.

a. Title, number and date of this document.
b. Grade of batting required (see 1.1).
c. When palletization is required (see 4.3).

5.3 Sources of documents.

5.3.1 Source of government documents. Copies of military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

MILITARY INTERESTS:

Custodian:

Army - GL

Review activities:

Army - MD
DLA - CT
DS

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 8320-0091

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:39Z
Check the source to verify that this is the current version before use.