A-A-50168
June 3, 1988

COMMERCIAL ITEM DESCRIPTION

CABINETS, FOOD WARMING, ELECTRICALLY HEATED, DRAWER TYPE

The General Services Administration has authorized the use of this commercial item description in preference to MIL-C-43609.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers food warming cabinets of the following types, as specified (see 5.2).

Type I - For countertop use (2 drawers)
Type II - Floor model, caster mounted (3 drawers)

1.2 Part identification number. The part identification number shall consist of the commercial item description number and the type number as follows:

AA50168 - 1
- AA50168: CID number
- 1: Type

2. SALIENT CHARACTERISTICS

2.1 Design and construction.

2.1.1 Body. The entire outside of the cabinet, except for the outer bottom, shall be fabricated from stainless steel. The outer bottom may be stainless steel, aluminized steel, galvanized steel or any steel coated to resist corrosion. All components and assemblies of the cabinet shall be free from dirt, burrs, slivers, die and tool marks, dents and cracks. Exposed surfaces shall be free from sharp edges and corners. Welds shall be continuous, smooth and free of cracks, burn holes, undercuts, fissures or incomplete fusion. All scale shall be removed from the finish weld area. Threaded fasteners, where used, shall not be broken, cracked or stripped, and shall be drawn tightly. Rivets, where used, shall fill the hole completely and heads shall be in full contact with the surface of the member and concentric with the hole.

2.1.2 Drawers. Cabinets shall have 2 or 3 drawers, depending on the type specified (see 1.1), fabricated from 300 series stainless steel. Drawers shall be designed to slide in and out with minimum effort and shall be provided with stops to prevent them from accidently being pulled all the way out. The drawers shall fit flush and tight with cabinet exterior. Each drawer shall have the capacity for one 4-1/2 inches deep by 12 inches wide by 20 inches long food

FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

service or cafeteria type pan, and shall be capable of maintaining such foods as rolls warm and moist, and fried chicken crisp. Drawer temperature shall be thermostatically maintained to a tolerance of ± 10°F within the range of 150°F to 200°F. The heating elements shall be capable of raising the drawer temperature to 150°F at the minimum rate of 3°F per minute.

2.1.3 Type I cabinet. Type I cabinets shall not be greater than 29-1/2 inches wide by 22 inches deep by 23 inches high.

2.1.4 Type II cabinet. Type II cabinets shall not be greater than 30 inches wide by 21 inches deep, excluding bumpers, by 37 inches high. Type II cabinets shall have bumpers on all four sides as well as a bumpered handle welded or bolted to the right side of the unit. Type II cabinets shall be equipped with 5 inch diameter casters. The two casters on the left side shall be rigid and the two casters on the right shall be of the swivel type with locking brakes.

2.2 Codes and standards. The cabinets shall comply with the applicable requirements of UL Standard No. 197 and NSF Standard No. 4.

2.3 Electrical requirements. Unless otherwise specified (see 5.2), cabinets shall be rated for 120 volts, 60 hertz, 1 phase system. The cabinet shall have a 3 to 6 foot long power supply cord with a NEMA 5-15P plug attached to it.

2.4 Thermostat. The thermostat control shall have an integral "ON-OFF" switch. The "OFF" position and dial settings shall be clearly marked on the control.

2.5 Data name plate (Government unique requirement see 5.4). The cabinets shall be furnished with a data name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for: (a) Methods of applying; (b) Identification tags; (c) Information not required and (d) Optional marking information shall not apply. The data plate shall be made of minimum 20 gauge corrosion-resisting metal and attached to the cabinet by rivets, screws or welding in such a manner as to meet the applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Contract Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number (List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (when specified, see 5.2)

Each plate shall be placed so that it is readily visible to the operator during normal operating use and so as to not adversely affect the life and utility of the food warming cabinet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description and except for those government unique requirements specified, conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The contractor shall certify the product meets the "Government unique" requirements except when specific quality assurance provisions are specified for the Government unique requirements. In this case, the contractor shall provide data resulting from inspection conducted in accordance with the specified quality assurance. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each cabinet shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.3 Export packaging and packing.

4.3.1 Export packaging. Each cabinet shall be cleaned, preserved and cushioned to protect against corrosion, deterioration and physical damage during shipping and storage.

4.3.2 Export packing. Each cabinet shall be packed in a wood-cleated plywood box conforming to PPP-B-601, type domestic, style optional, or a wood-cleated fiberboard box conforming to PPP-B-591, class II, style optional. Each box shall be closed, strapped and skidded if the shipping weight exceeds 200 pounds, in accordance with PPP-B-601 or PPP-B-591, as applicable.

4.3.3 Palletization. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Marking (commercial and export). Marking of the shipping containers and unit loads shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The cabinets covered by this commercial item description are intended for use in kitchens and hospitals to keep food warm prior to serving.

5.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. Type of cabinet required (see 1.1).
c. When electrical requirements are other than specified (see 2.3).
d. Government approved manual number to be included on the data name plate when manuals are purchased under the contract (see 2.5).
e. Type of packaging and packing required (see 4.1).
f. When palletization of shipping containers is required (see 4.3.3).

5.3 Sources of documents.

5.3.1 Sources of nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging, is available from:

The American Society for Testing and Materials (ASTM)
1916 Race Street
Philadelphia, PA 19103

NSF Standard No. 4 - Cooking and Hot Food Storage Equipment, is available from:

National Sanitation Foundation (NSF)
3475 Plymouth Road
P.O. Box 1468
Ann Arbor, MI 48106

UL Standard No. 197 - Commercial Electric Cooking Appliances, is available from:

Underwriters Laboratories, Inc. (UL)
333 Pfingsten Road
Northbrook, IL 60062

Standard WD1 - General Purpose Wiring Devices, is available from:

National Electrical Manufacturers Association (NEMA)
155 East 44th Street
New York, NY 10017

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

5.3.2 Source of governmental documents. Copies of Military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

5.4 Government unique requirements. Whenever "(Government unique requirements)" is included in the title of a paragraph under "salient characteristics" it is meant that the requirement is something that is not normally offered to the commercial marketplace by the manufacturer.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review activities:

Army - MD, TS
Air Force - 84
DLA - GS

User activity:

Navy - MC

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0729

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.