A-A-50173
October 5, 1988

COMMERCIAL ITEM DESCRIPTION

CANDLE BURNER

The General Services Administration has authorized the use of this commercial item description in preference to item 1 of MIL-C-43467.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The candle burner shall be fabricated of commercial brass with a chromium plate finish. The candle burner shall be cylindrical in design, and be tapered at the top. The burner shall approximate 1-1/2 inches high and the base diameter will be 1-1/4 inches. The top opening of the burner should approximate 13/16 inch in order to accommodate a 15/16 inch diameter candle.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3. Packaging Requirements

3.1 Packaging. Each candle burner shall be completely wrapped in tissue paper with the ends tucked inside or enclosed in a clear polyethylene bag. Twelve candle burners shall then be placed into a snug-fitting top loading paperboard box equipped with separators.

3.2 Packing. One hundred and forty-four candle burners, packed as specified, shall be packed in a snug-fitting fiberboard shipping container conforming to style RSC, type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids, and of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

AMSC N/A FSC 9925

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

3.3 Palletization. When specified (see 4.2), candle burners, packaged as specified, shall be palletized on a 4-way entry pallet in accordance with load type 1a of MIL-STD-147. Each prepared load shall be bonded by means K and L or O or P, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contract or purchase order, unit packs, intermediate packs, shipping containers and unitized pallet loads shall be marked in accordance with MIL-STD-129.

4. NOTES

4.1 Intended use. The candle burner covered by this document is intended to be used with 15/16 inch diameter candles to prevent dripping of wax.

4.2 Ordering data.

a. Title, number, and date of this document.
b. When palletization is required (see 3.3).

4.3 Source of government documents. Copies of military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19120

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - PE
Air Force - 28

Review Activities:

Navy - PE
Air Force - 28
Armed Forces Chaplains Board

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing Activity:

Army - GL

PROJECT NO. 9925-1012

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the current version before use.