A-A-50176
October 7, 1988

COMMERCIAL ITEM DESCRIPTION

BOWL, BAPTISMAL

The General Services Administration has authorized the use of this commercial item description in preference to MIL-B-43401.

1. SALIENT CHARACTERISTICS

1.1 Design and construction. The baptismal bowl shall be fabricated of commercial brass with a chromium plate finish. The bowl should approximate 9-10 inches in diameter, with a 5-6 inch round base. The overall height shall be 5 inches ± 1 inch. Design of the bowl shall be the manufacturer's standard commercial model.

2. QUALITY ASSURANCE

2.1 Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

3. PACKAGING REQUIREMENTS

3.1 Packaging. Each baptismal bowl shall be completely enclosed in a clear polyethylene bag. Bags shall be closed by folding the end around and securing it with a piece of pressure sensitive tape. Each bowl shall then be inserted into a snug-fitting folding or set-up paperboard box.

3.2 Packing. Six baptismal bowls, packaged as specified, shall be packed in a snug-fitting RSC style corrugated fiberboard shipping container conforming to type CF, (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The shipping container shall be completely filled with no voids, and of a size that can be palletized in accordance with MIL-STD-147. Each shipping container shall be closed in accordance with the appendix of PPP-B-636.

AMSC N/A FSC 9925

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

3.3 Palletization. When specified (see 4.2), baptismal bowls, packed as specified, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded by means K and L or O or P, in accordance with MIL-STD-147.

3.4 Marking. In addition to any special markings required by the contract or purchase order, unit packs, shipping containers and unitized pallet loads shall be marked in accordance with MIL-STD-129.

4. NOTES

4.1 Intended use. The baptismal bowl covered by this document is intended for use during Baptismal Ceremonies.

4.2 Ordering data.

a. Title, number, and date of this document.
b. When palletization is required (see 3.3).

4.3 Source of government documents. Copies of military and Federal documents are available from:

Naval Publications and Forms Center
5801 Tabor Avenue
Philadelphia, PA 19102

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - PE
Air Force - 28

Review activities:

Navy - PE
Air Force - 28
Armed Forces Chaplains board

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

Army - GL

Project No. 9925-1015

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.