A-A-50181
October 20, 1988

COMMERCIAL ITEM DESCRIPTION

FRYERS, DEEP-FAT (GAS, HEAVY DUTY)

The General Services Administration has authorized the use of this commercial item description in preference to S-F-700.

1. Classification. This commercial item description covers commercial, heavy duty, floor mounted gas heated, deep-fat fryers of the following sizes:

Size 1 - 30 pounds minimum production capacity
Size 2 - 60 pounds minimum production capacity
Size 3 - 90 pounds minimum production capacity
Size 4 - 110 pounds minimum production capacity

2. Salient characteristics.

2.1 Design and construction. The fryers shall have an enclosed cabinet designed for floor use equipped with adjustable stainless steel legs. "The cabinet front, door and sides shall be stainless steel. The back and bottom shall be stainless steel, aluminized steel, galvanized steel or steel treated to resist corrossion." The cooking vessels shall be stainless steel and have a hand operated drain valve. A stainless steel or nickel plated steel fat draining vessel with carrying handle(s), having a minimum capacity of 35 percent of the cooking vessels capacity, shall be furnished with each fryer. Each fryer shall be equipped with one large and two half baskets, constructed of stainless steel or nickle plated steel and a stainless steel cooking vessel cover with a handle. The fryer shall be equipped with a thermostat, on-off switch, and signal lights indicating burner(s) on, up to selected temperature, and thermostat failure.

2.2 Gas consumptions and dimensions. The fryer dimension shall be within the dimensional limits specified in table I:

TABLE I. GAS CONSUMPTION AND DIMENSIONS

	Production capacity 1/ lbs/hr (minimum)	BTU/HR (minimum)	Dimensions inches (max) Height 2/	Width	Depth
Size 1	30	60,000	37-1/2	14-1/2	30
Size 2	60	90,000	37-1/2	20	38
Size 3	90	110,000	37-1/2	21-1/2	38
Size 4	110	125,000	37-1/2	21-1/2	38

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the current version before use.

1/ Production capacity of raw to done 1/2 inch by 1/2 inch french fries that can be processed in 1 hour.

2/ Height from floor to top of cooking vessel including legs.

2.3 Fuel system. The fuel system shall be designed to burn propane or liquid petroleum gas (LPG) and comply with the BTU for the fryer size as specified in table I. The fryer shall be equipped with a pressure regulator, automatic pilot with safety shut-off, and an automatic ignition system. An American Gas Association (AGA) approved quick disconnect (socket and plug) and a 5 foot long minimum flexible metal connector with a male pipe thread fitting on one end and a union with a female pipe fitting on the opposite end shall be provided. Fryers shall be supplied to burn natural gas. Orifices for LPG and instructions for conver-sion from natural gas to LPG and a pressure regulator shall be provided with each fryer.

2.4 Electrical requirements. Electrical controls shall operate on a nominal 120 volt, 60 hertz power source. The fryer shall be equipped with a 6 foot long minimum three wire power supply cord with a National Electrical Manufacturers Association (NEMA) 5-15P plug.

2.5 Thermostat. The fryer shall be equipped with an adjustable thermostat with a range of 200°/275°F to 375°/400°F, and a fixed overtemperature thermostat to shut off the entire gas system when the fat reaches a high limit of 430°F to 460°F.

2.6 Standard compliance. The fryer shall comply with American National Standards Institute (ANSI) Z83.13 and National Sanitation Foundation (NSF) No. 4.

2.7 Identification Plate. In addition to the marking requirements of ANSI Z83.13, the identification plate shall include the contract number and the national stock number, specification data, manufacturer's name, address, and telephone number, supplier's name, address, and telephone number, manufacturer's model number, and DGSC approved manual number.

3. Certification. The contractor shall certify that the product offered meets the salient characteristics of this description, conforms to the producers' own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. Packaging.

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified. (See 5.2.)

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the current version before use.

4.2 Commercial.

4.2.1 Commercial packaging and packing. Each fryer shall be cleaned, preserved, packaged, packed and unitized in accordance with ASTM D 3951.

4.3 Export.

4.3.1 Export packaging. Each fryer shall be disassembled to the extent determined by the contractor to protect parts susceptible to damage during shipment and storage and for reduction of cubage. Parts removed shall be packaged in a domestic fiberboard box constructed and closed in accordance with PPP-B-636. Parts not removed shall be secured in place with cushioning or pressure-sensitive tape. Doors and drawers shall be secured in a closed position with filament reinforced pressure-sensitive tape. The fryer and parts shall be cleaned, preserved, and cushioned to afford protection against corrosion, deterioration, and physical damage during shipment and storage.

4.3.2 Export packing. Each fryer shall be packed in a snug-fitting wood-cleated, plywood box, conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601 or mailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. When legs or casters are not disassembled, the fryer shall be blocked in a manner to provide approximately 1 inch clearance between the legs or casters and the bottom of the box. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 and PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit pack and shipping container shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The fryers are intended for use in kitchens or galleys for deep fat frying of food products.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Type and size of fryer required. (see 1).
c. Type of packaging and packing required (see 4.1).

5.3 Sources - for nongovernment association documents.

American Gas Association (AGA)
8501 E. Pleasant Valley Road
Cleveland, OH 44129

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the current version before use.

ANSI Z83.13 - American National Standards
Institute (ANSI)
1430 Broadway
New York, NY 10018

NSF No. 4 - National Sanitation Foundation (NSF)
3475 Plymouth Road
Ann Arbor, MI 48106

National Electrical Manufacturers Association (NEMA)
2101 L Street, NW
Washington, DC 20037

ASTM D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

MILITARY INTERESTS:

Custodians

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD, TS
Navy - MS, SA
DLA - GS

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
VA - OSS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0724

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:40Z
Check the source to verify that this is the current version before use.