A-A-50182
October 20, 1988

COMMERCIAL ITEM DESCRIPTION

URN, COFFEE, TWIN, AUTOMATIC (ELECTRIC, STEAM, AND GAS)

The General Services Administration has authorized the use of this commercial item description in preference to MIL-U-43263, for specific classifications of items listed in this document. (See supersession data for the specific items this document replaces.)

1. Classification. This commercial item description covers automatic twin coffee urns and shall be of the following styles, sizes, types and design (power requirements):

Style 1 - Under counter
- Size 3 - 3 gallon each compartment
  - Type I - Electric
    - Design A - 120/208 V, 60 Hz, 1/3 Ph.
  - Type II - Steam
    - Design B - 120 V, 60 Hz, 1 Ph.
- Size 6 - 6 gallon each compartment
  - Type I - Electric
    - Design A - 120/208 V, 60 Hz, 1 Ph.
  - Type II - Steam
    - Design B - 120 V, 60 Hz, 1 Ph.

Style 2 - Counter or stand mounted
- Size 3 - 3 gallon each compartment
  - Type I - Electric
    - Design A - 120/208 V, 60 Hz, 1/3 Ph.
    - Design C - 380 V, 50 Hz, 1 Ph.
  - Type II - Steam
    - Design B - 120 V, 60 Hz, 1 Ph.
    - Design D - 220 V, 50 Hz, 1 Ph.
  - Type III - Gas
    - Design B - 120 V, 60 Hz, 1 Ph.
- Size 4 - 4 gallon each compartment
  - Type I - Electric
    - Design A - 120/208 V, 60 Hz, 1/3 Ph.
    - Design C - 380 V, 50 Hz, 3 Ph.
  - Type II - Steam
    - Design B - 120 V, 60 Hz, 1 Ph.
    - Design D - 220 V, 50 Hz, 1 Ph.
  - Type III - Gas
    - Design B - 120 V, 60 Hz, 1 Ph.

AMSC N/A FSC 7310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

Size 6 - 6 gallons each compartment
Type I - Electric
Design A - 120/208V, 60Hz, 1/3Ph
Design C - 380V, 50Hz, 1Ph

Type II - Steam
Design B - 120V, 60Hz, 1Ph
Design D - 220V, 50Hz, 1Ph

Type III - Gas
Design B - 120V, 60Hz, 1Ph"

Energy efficient type I or type II urns may be obtained by specifying "Energy Efficient" after the style, size, type and design.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. All urns shall have two coffee compartments and one water heating compartment and shall automatically brew coffee by push button control. The following functions shall be performed automatically:

a. Heat water.
b. Spray measured amount of hot water over ground coffee.
c. Refill the water compartment.
d. Maintain brewed coffee temperature.
e. Deliver brewed coffee and hot water to faucets.
f. Agitate the coffee at the end of the brew cycle.

The water compartment shall be non-pressurized. Urns shall be provided with a special brewing device or adapter to automatically brew one half compartment capacity. The spray-over temperature of the water shall not be less than 195°F or more than 210°F. The spray head shall evenly distribute water over the ground coffee without overspraying or pocketing. The spray-over device and piping shall be capable of delivering the proper amount of water to brew urn grind, also referred to as drip or universal grind, in no more than 6 minutes, and regular grind in no more than 13 minutes. The solids in the brewed coffee shall be between 1.15 and 1.32 percent of the total weight of the brew in each compartment. The urn shall maintain brewed coffee at a temperature between 180°F and 190°F for a minimum of one hour. Initial heat-up time shall not exceed 50 minutes and recovery time between brews shall not exceed 15 minutes. Initial heat-up and recovery times are based on 160°F minimum incoming water for gas-heated urns above 3 gallon capacity, and 70°F minimum for all other urns. Types I and III urns shall be provided with low water protection which shuts off electric power or gas when the water level drops below a point considered to be detrimental to the unit. All urns shall have a sight glass for each of the coffee compartments and water compartments to indicate liquid level. All urns shall be supplied with permanent filters, leacher bags or paper filters as specified, capable of meeting the requirements of this commercial item

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

description and sufficient to make 500 batches of coffee per compartment. All coffee urns, including coffee and water compartments and covers, shall be fabricated from minimum 20 gauge 300 series stainless steel. All other exposed metal fittings and hardware shall be stainless steel or brass with chrome-nickel plating.

Style 1. Style 1 urns shall not be greater than 45 inches wide, 28 inches deep and 33-1/3 inches high. Urns shall be provided with one coffee faucet and one hot water faucet for dispensing from a countertop, and in addition, one coffee faucet per compartment and one hot water faucet at the urn body. Pumps shall be used to feed coffee and hot water to countertop faucets. The pump shall be capable of filling a 5 ounce cup in no more than 6 seconds. Coffee and hot water faucets at the urn body shall be gravity fed. Urns shall have a drip trough with removable anti-splash cover under the faucets at the urn body. The urns shall be mounted on four 3-inch minimum diameter casters with a total load rating equal to or greater than the loaded urn. Service connections shall be flexible. Plastic tubes shall be protected with flexible, braided stainless steel covering. The length of the dispensing lines shall be 8 feet.

Style 2. Style 2 urns shall not be greater than 43 inches wide, 22 inches deep and 40 inches high. Urns shall be provided with one coffee faucet per compartment and one hot water faucet. Coffee faucets shall be gravity fed, while the hot water faucet may be gravity fed or tap water fed. When specified, style 2 urns shall be supplied with a stand as described herein. Style 2 urns shall have four adjustable stainless steel legs.

Type I urns - Type I urns shall be heated by immersion type heating elements rated for the specified voltage, frequency and phase. The heating elements shall be removeable only for replacement or servicing.

Type II urns - Type II urns shall have a steam coil for operating on steam pressure of from 10 pounds per square inch gage (psig) to maximum of 25 psig. Urns shall be provided with a 5-foot minimum flexible steam supply hose with necessary connections and condensate return line(s).

Type III urns - Type III urns shall be designed to burn natural gas and liquefied petroleum gas (LPG). Pilot gas valves shall be of the fixed orifice type with interchangeable orifice hoods or bushings. Each burner valve shall be provided with two orifice hoods or bushings, one drilled for natural gas and the other drilled for LPG. Instructions shall be provided for converting from one type of gas to the other and vice versa. Natural gas hoods or bushings shall be unpainted brass, while LPG hoods or bushings shall be black. An automatic safety shut-off device shall interrupt flow of gas to burner and pilot when the source of ignition fails.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

2.2 Energy efficient. When energy efficient urns are specified, they shall comply with all of the requirements of this commercial item description. In addition, the coffee temperature in energy efficient urns shall not drop more than 30°F in 4 hours. This shall be determined in an ambient temperature of 70°F ± 5°F, 4 hours after the urn reaches a brewing temperature of 195°F to 210°F and heat to the unit is shut off.

2.3 Urn stand. The stand for style 2 urns shall be 48 inches wide by 36 inches deep by 34 inches high. The stand top shall be a minimum 18 gauge stainless steel skin and shall be constructed to form a rigid base for the loaded urn. The stand shall have a built-in drip trough, a bottom shelf and two doors along the 48 inch dimension, and shall be equipped with four adjustable stainless steel or chrome plated brass bullet-shaped legs.

2.4 Cleaning brush. A flexible brush suitable for cleaning faucets, pipes, shank connections and gage glasses shall be furnished with each urn.

2.5 Faucets. Faucets shall be anti-splash, self-closing with replaceable seat cups or washers and designed for temperatures up to 220°F. The clearance between the countertop and bottom of faucets on style 1 urns shall be between 5-1/2 inches and 8 inches. The clearance between bottom of compartment faucets and drip trough splash cover shall be between 5-1/8 inches and 9-3/8 inches for style 1 urns, and between 11 inches and 13-1/4 inches for style 2 urns.

2.6 Electrical requirement. Urns shall be designed to operate on the following power supplies as referenced in paragraph 1:

Design A - 120/208 V, 60 Hz, 3 Ph, 4 wire, convertible to 1 Ph, 3 wire.
Design B - 120 V, 60 Hz, 1 Ph.
Design C - 380 V, 50 Hz, 3 Ph.
Design D - 220 V, 50 Hz, 1 Ph.

The energy ratings for Type I urns shall be in the range of 12 kw to 15 kw. All urns shall be grounded and all urns except Design B urns and style 1, type I, design A urns shall be supplied for direct connection to the power supply. Design B urns shall have a power supply cord and a NEMA 5-15P plug attached to the cord. Style 1, type I, design A urns shall have a power supply cord and a NEMA 18-60P plug attached to the cord.

2.7 Standards compliance. Coffee urns shall comply with the applicable requirements of NSF Standard 4, UL Standard 197 and ANSI Z83.14. The stand shall comply with the applicable requirements of NSF Standards 2 and 4.

2.8 Identification plate. In addition to the marking requirements of ANSI Z83.14, the identification plate shall include the manufacturer's model and serial number, contract number, national stock number, specification data,

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

manufacturers name, address, telephone number, supplier's name, address, telephone number (if different than manufacturer's), and DGSC's approved manual number.

3. Certification. The contractor shall certify this product offered meets the salient characteristics of this description, conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same as the product offered for sale in the commercial marketplace, except for those additional requirements/characteristics specified herein. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial.

4.2.1 Commercial packaging and packing. Each urn shall be cleaned, preserved, packaged and packed in accordance with ASTM D 3951.

4.3 Export.

4.3.1 Export packaging. Each urn shall be disassembled to the extent determined by the supplier. Accessories and disassembled parts shall be packaged in a domestic fiberboard box constructed and closed in accordance with PPP-B-636 or be secured to the urn. The urn, accessories and parts shall be cleaned, preserved, cushioned, and immobilized to afford protection against corrosion, deterioration and physical damage during shipment and storage.

4.3.2 Export packing. Each complete urn shall be packed in a snug-fitting wood-cleated plywood box conforming to domestic type, style A or J, grade B, type 2 load of PPP-B-601, or nailed wood box conforming to class 1, style 2 or 4, grade B, type 2 load of PPP-B-621. The contents of each box shall be blocked and braced to prevent movement while the box is in transit. The casters or legs of the urn shall be blocked in a manner to provide approximately 1-inch clearance between the casters or legs and the bottom of the box. Each shipping container shall be closed and strapped in accordance with the appendix of PPP-B-601 or PPP-B-621, as applicable.

4.4 Marking (commercial and export). Marking of unit packs and shipping containers shall be in accordance with MIL-STD-129.

5. NOTES

5.1 Intended use. The coffee urns are intended for dispensing of coffee and hot water for tea in hospitals, cafeterias, galleys and dining facilities.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

5.2 Ordering data.

a. Title, number, and date of this document.
b. Style, size, and type (and class, if applicable) of coffee urn required (see 1.).
c. Type of packaging and packing required (see 4.1).
d. Electrical requirements (see 2.6).

5.3 Sources for nongovernment association documents.

NATIONAL SANITATION FOUNDATION (NSF)

Standard No. 2 - Food Service Equipment
Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment

(Application for copies should be addressed to the National Sanitation Foundation, NSF Building, Ann Arbor, MI 48105.)

UNDERWRITERS LABORATORIES, INC. (UL)

UL 197 - Commercial Electric Cooking Appliances

(Application for copies should be addressed to the Underwriters Laboratories, Inc., 333 Pfingston Road, Northbrook, IL 60062.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

Standard Z83-14 - American National Standards for Gas Counter Appliances

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018; or the American Gas Association Laboratories, 8501 East Pleasant Valley Road, Cleveland, OH 44131.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

5.4 Supersession data. The styles, types and designs of coffee urns covered by this commercial item description replace items covered by MIL-U-43263, as indicated below:

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.

CID A-A-50182

Style	Size	Type	Design
1	3	I	A
1	3	II	B
1	6	I	A
1	6	II	B
2	3	II	B
2	3	I	C
2	3	I	A
2	3	II	D
2	3	III	B
2	4	I	C
2	4	I	A
1	4	II	B
2	4	II	D
2	4	III	B

MIL-U-43263

Style	Size	Type	Class
1	1	I	1
1	1	II	1
1	2	I	1
1	2	II	1
3	1	II	-
3	1	I	-
3	1	I	-
3	1	II	-
3	1	III	-
3	4	I	-
3	4	I	-
3	4	II	-
3	4	II	-
3	4	III	-

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review activities:

Army - MD, TS
Navy - MS, MC
Air Force - 84
DLA - GS

User activity:

Navy - CG

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

Preparing activity:

Army - GL

Project No. 7310-0725

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:40Z
Check the source to verify that this is the current version before use.