A-A-50188
December 2, 1988

COMMERCIAL ITEM DESCRIPTION

COFFEE BOILER, METAL

The General Services Administration has authorized the use of this commercial item in preference to MIL-C-17536D.

1. CLASSIFICATION

1.1 Classification. This commercial item description covers one type of coffee boiler having a minimum capacity of 2 gallons.

2. SALIENT CHARACTERISTICS

2.1 Design and construction. The coffee boiler shall consist of a seamless body, spout, pouring handle, cover, bail with heat resistant grip, and bail ears. The boiler shall be not greater than 12 inches in height and 10 inches in width, shall have either straight or tapered sides, and shall have a minimum capacity of 2 gallons. The design of the spout shall preclude coffee grounds in the boiler from being poured. The spout shall be sanitarily joined to the body using non-toxic materials and shall form a water tight seal. The pouring handle shall be joined to the body such as to provide stability while pouring and shall be located diametrically opposite the spout, at the lower part of the body. The cover with strip handle shall be one piece and shall not slip off while the boiler is being emptied. The grip shall be able to roll about the bail without lateral movement. The bail ears shall be joined to the body and shall permit the bail to move freely and rest to either side of horizontal and so that the grip does not contact the coffee boiler.

2.2 Codes and standards. The coffee boiler shall comply with the requirements of National Sanitation Foundation Standard No. 4.

2.3 Body. The body shall be minimum 20-gage, drawn, type 304 stainless steel.

2.4 Spout. The spout shall be minimum 20-gage, type 304 stainless steel.

AMSC/NA FSC 7330

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

2.5 Pouring handle. The pouring handle shall be fabricated from a minimum 18-gage, type 304 stainless steel tubing with a nominal 1/2 diameter.

2.6 Cover. The cover shall be minimum 20-gage, type 304 stainless steel.

2.7 Bail and grip. The bail shall be formed from 1/4-inch, type 304 stainless steel rod. The grip shall be heat resistant material, nominally 1/2-inch diameter and 4 inches in length.

2.8 Bail ears. The bail ears shall be formed from 14-gage, type 304 stainless steel.

3. QUALITY ASSURANCE

3.1 Certification. The contractor shall certify that the product offered meets the salient characteristics and requirements of the description, and conforms to the producer's own drawings, specifications, standards, and quality assurance practices, and is the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall furnish data resulting from inspection conducted in accordance with the specific quality assurance provisions. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

4. PACKAGING

4.1 Packaging and packing. Packaging and packing shall be commercial or export as specified (see 5.2).

4.2 Commercial packaging and packing. Each coffee boiler shall be cleaned, preserved, packaged, packed, and unitized in accordance with ASTM D 3951.

4.3 Export packaging. Each coffee boiler shall be disassembled to the extent determined by the contractor to protect parts susceptible to damage during shipment and storage. Each boiler shall be packaged in a fiberboard box conforming to type CF or SF, class domestic, style optional of PPP-B-636.

4.3.1 Export packing. Six coffee boilers shall be packed in a snug-fitting fiberboard shipping container conforming to PPP-B-636, class weather-resistant, style optional, type CF or SF. Each box shall be closed, waterproofed and reinforced in accordance with PPP-B-636. When specified (see 5.2), shipping containers shall be palletized in accordance with MIL-STD-147.

4.4 Marking (commercial and export). Marking of unit packs, shipping containers and unit load shall be in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.

5. NOTES

5.1 Intended use. The coffee boiler covered is intended for carrying coffee from urns to points of service, and also for making coffee by boiling ground coffee in water.

5.2 Ordering data.

a. Title, number, and date of this document
b. Selection of applicable packaging and packing (see 4.1)
c. When palletization is required (see 4.3.1)

5.3 Sources for nongovernment association documents.

ASTM D 3951 - Standard Practice for Commercial Packaging - copies are available from: The American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

National Sanitation Foundation Standard No. 4 - Commercial Cooking and Hot Food Storage Equipment; copies are available from: The National Sanitation Foundation, 3475 Plymouth Road, P.O. Box 1468, Ann Harbor, MI 48106.

Military Interests:

Custodian

Army - GL
Navy - SA
Air Force - 84

Review Activity

Army - MD
Navy - MS

User Activity

Navy - CG

Preparing activity:

Army - GL

Project No. 7330-0586

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:40Z
Check the source to verify that this is the current version before use.