[METRIC]

A-A-558B
November 30, 1995
Superseding
A-A-558A
January 6, 1989

COMMERCIAL ITEM DESCRIPTION
MAPTACK

The General Services Administration has authorized the use of this Commercial Item Description, for all Federal agencies.

1. **SCOPE:** This Commercial Item Description covers maptacks.

2. **SALIENT CHARACTERISTICS:**

2.1 Material. The heads of the maptacks shall be spherical in shape and shall be made of metal, plastic or glass as specified. The pins of the maptacks shall be made of a heat-treated, polished, suitable steel.

2.2 Design and Construction. The dimensions of the heads and pins shall be in accordance with table listed paragraph 2.6. The pin shall extend from the underside of the head and shall be concentric with the axis of the head. The length of the pin shall have a tapered and sharp point. The pin shall not become loose, detached, or break off the head during normal usage.

2.3 Colors. The heads of the maptacks shall be a solid color specified in the contract or order. If assorted colors are specified, a random mix of a minimum of seven commercial colors will be allowed.

2.4 Finish. All exposed metal surfaces shall be protected against normal use corrosion by a suitable commercially accepted permanent finish.

2.5 Workmanship. All surfaces of the maptacks shall have a smooth finish and shall be free from slivers, rough, or sharp edges with the exception of the sharp point of the pin. Components shall not be broken, cracked or malformed. Maptacks shall be free of any other defects which may affect appearance or serviceability.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

2.6 Tables

Diameter of Heads ±0.397mm(±.015")	Length of Pins ±1. 588 mm(.063")	Diameter of Pins mm / inches
4.366(0.172")	9.525 mm(.375")	0.06096 to 1.016 mm (.024" to .040")
6.35(.25")	9.525 mm(.375")	" (.024" to .040")
6.35(.25")	15.875 mm(.625")	" (.024" to .040")
7.938(.312")	31.75 mm(1.25")	" (.024" to .040")
6.35(.25")	12.7 mm(0.50")	1.016 to 1.041 mm (.040" to .041")

3. **REGULATORY REQUIREMENTS**: The offeror / contractor is encouraged to use recovered materials in accordance with Paragraph 23.403 of the Federal Acquisition Regulation(FAR).

3.1 Certification: The contractor shall certify that if polystyrene is used in the manufacture of this item, it shall contain a minimum of 25 percent Postconsumer Recovered Materials in accordance with Title 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Material; Final rule. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4. **QUALITY ASSURANCE PROVISIONS**:

4.1. Contractor Certification. The contractor shall certify and maintain substantial evidence that the product offered meets the salient characteristics of this Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

4.2 Suppliers are encouraged to use quality control (QC) techniques that exhibits control over their processes (e.g. Statistical process Controls). These techniques shall ensure quality levels equal to, or greater than, those cited in the applicable technical document or herein. For those product characteristics which are controlled by such a method, requirements for end item inspection or test may be considered to have been met. End item inspection / testing may be used by the offeror, or the Government representative, as a means to determine the effectiveness of the inprocess quality controls. Inprocess controls shall not be substituted for end item performance testing, unless it can be demonstrated that there exists a direct correlation between the process and product performance, such that end item performance testing is obviated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

For those characteristics for which there are no such controls, or for end item performance test, lot by lot sampling for inspection / shall be required. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society of Quality Control (ASQC) ANSI/ASQC Z1.4 1993, Sampling Procedures and Tables for Inspection by Attributes.

For Visual and Dimensional inspections the level shall be S-3 with an Acceptable Quality Level (AQL) of 4.0 Percent Defective. The sample unit shall be one maptack. The supplier must provide objective evidence (test and inspection records) that the presented material meets the requirements of this Commercial Item Description.

5. Preservation, packing and marking shall be specified in the contract or Order.

6. **NOTES:**

6.1 REFERENCED DOCUMENTS: The issue of the referenced documents in effect on the date of the solicitation for offers or request for proposals shall be used to determine conformance with the requirements of this Commercial Item Description.

6.1.1 Federal Regulations:
Federal Acquisition Regulations. Paragraph 23.403
Title 40 code of Federal Regulations Protection of Environment, Part 247. Copies of the U.S. Code of Federal Regulations may be purchased with a VISA, Master Card or prepaid check through: Government Printing Office Washington, DC. Telephone (202)783-3238. When ordering, ask for Title 40, Parts 190-250, Stock Number: 869-013-146-0.

6.1.2 Application for copies of ANSI/ASQC Procedures should be addressed to:
ANSI/ASQC Z1.4-1993
American Society of Quality Control
P.O. Box 3005
611E Wisconsin Avenue
Milwaukee, WI. 53201-4606

6.2. Ordering Information. Purchasers shall specify the following in the contract or purchase order.
1. Title, number, and date of this commercial item description.
2. Arrangement for inspection and inspection facilities, if different than provisions under Quality Assurance.
3. Packaging and marking requirements.
4. Color of maptack.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

6.3 National Stock Number Listing:

7510-00-272-3086
7510-00-272-3087
7510-00-272-3088
7510-00-272-3089
7510-00-272-3090
7510-00-272-3091
7510-00-272-3096
7510-00-272-3099
7510-00-272-3100
7510-00-285-5844

MILITARY INTEREST:

NONE
DoD has no registered interest in revisions and amendments to this Commercial Item Description.

PREPARING ACTIVITY:

FSS-GSA

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.