METRIC

MIL-PRF-8565/3G
15 April 2026
SUPERSEDING
MIL-PRF-8565/3F (AS)
20 October 2021

PERFORMANCE SPECIFICATION SHEET

BATTERY, STORAGE, AIRCRAFT, MEDIUM RATE, NO MAINTENANCE, 24-VOLT, 15 AMPERE-HOUR

This specification is approved for use by all Departments and Agencies of the Department of Defense.

D8565/3-2 was inactivated for new design after 26 June 1987.
D8565/3-3 should be used in place of D8565/3-2 for new design.

The complete requirements for acquiring the storage battery described herein shall consist of this document and the latest issue of specification MIL-PRF-8565.





FIGURE 1. Battery P/N D8565/3-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.



NOTES:

1. All dimensions are millimeters.
2. Allow additional 4 mm width for cover plus 4 mm for mounting bracket across side of container.

FIGURE 1. Battery P/N D8565/3-2 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.





FIGURE 2. Battery P/N D8565/3-3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.



COORDINATES OF CURVES STRAIGHT LINE BETWEEN COORDINATES			
Current in Amps	Potential in Volts		Start Time in Seconds
	D8565/3-2	D8565/3-3	
280	14.0	16.5	0
175	16.5	18.0	2
130	18.0	19.0	4
100	18.9	20.0	8
80	19.1	20.5	12
60	20.0	21.0	50
40	20.5	21.5	60

FIGURE 3. Start cycle requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.




FIGURE 4. Random vibration test levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

1. The rated capacity of the battery shall be 15 ampere-hours (15.0 Ah/1 hr./21°C/18.0 V at end of life). 1C = 15.0 amperes.

2. The D8656/3-2 battery shall weight 26 kg max. The D8565/3-3 battery shall weight 21.5 kg max.

3. Mounting holes shall have a coating-free surface, 12.7 mm diameter both sides.

4. Aircraft installation. For installation in the aircraft, the battery shall be supported as shown on figure 3 of MIL-PRF-8565. Vibration isolation shall be provided, if necessary, to ensure that the vibration level does not exceed the requirements of the 2-year cycling test of 4.5.10, as modified herein. If vibration isolators are used, sufficient sway clearance between the battery and the mounting structure shall be provided. Battery life in the aircraft shall be 2 years.

5. Batteries manufactured in accordance with MIL-PRF-8565 and MIL-PRF-8565/3 shall be inspected and tested using the inspections and the order of inspections given in table II herein.

6. The battery shall conform to military specification MIL-PRF-8565, except as modified by the following:

3.5.5 Receptacles. Add: “The receptacle for the battery’s positive and negative connections shall be dimensionally equal to MIL-PRF-18148/3, Style 1.”

7. Add the following new paragraph:

3.5.1.1 Add: “An auxiliary receptacle MS27466T17B6P, shall be located as shown on figures 1 and 2.

a. Pin A shall be high side AC (input heater power) (see figure 5).

b. Pin B shall be AC ground (heater return) (see figure 5).

PIN A 115 VAC

PIN B AC GROUND




FIGURE 5. Electrical schematic for pin A and pin B.

8. The battery shall conform to military specification MIL-PRF-8565, except as modified by the following:

3.5.10.a Add “Heater current shall not exceed 6A at 115V.” to the end of the paragraph.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

3.8.7 Constant voltage discharge. Delete the first sentence and substitute "The battery shall produce not less than the current specified in table I after being tested in accordance with 4.5.8.

TABLE I. Constant voltage discharge.

Temperature	Peak Current (amperes)	Current at 15 Seconds	Current at 30 seconds	Capacity at 60 seconds
Room Temperature (see 4.4.1)	800 amperes	650 amperes	150 amperes	5.29 ampere-hours
-26°C	450 amperes	300 amperes	80 amperes	2.73 ampere-hours

3.8.9 Cycling. In the first sentence, delete "100 cycles" and substitute "85 cycles".

3.8.13.1 Ground storage. Delete the text and add: "The battery shall be capable of storage at temperature conditions from -26ºC to 50ºC for up to 30 days and maintain a sufficient state of charge to successfully complete three start cycles in accordance with figure 3 herein."

3.8.16 Output performance. Delete the paragraph in its entirety and substitute the following:

3.8.16 Standby power output performance.

3.8.16.1 The battery, when discharged into a 16-ohm resistive load, shall maintain a terminal potential of 24.0 volts or greater for the discharge time and temperature conditions shown below, when tested in accordance with 4.5.28 of MIL-PRF-8565 as modified herein.

TEMPERATURE (ºC)	DISCHARGE TIME (Hours)
-26	.5
-18	1.0
0	3.0
25	6.0
49	6.0

3.8.16.2 The battery, after completing a discharge into a 16-ohm load for the time and temperature conditions shown above, shall successfully complete three start cycles, with the energy required on figure 3, when tested in accordance with 4.5.28 of MIL-PRF-8565 as modified herein.

3.8.17 Cold and hot temperature charge. Delete the paragraph in its entirety and substitute the following:

3.8.17 Cold and hot temperature charging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

9. Add the following new paragraphs:

3.8.17.1 Half-hour charging. The battery, having 7.0 Ah capacity at temperatures in the range of -18 ºC to 55 ºC, shall be capable of delivering 14.0 Ah capacity after a 28.25 ± 0.5V charging source has been applied to the battery for 30 minutes, when tested in accordance with 4.5.29, as modified herein.

3.8.17.2 One-hour charging. The battery, when discharged at temperatures in the range of -40 ºC to -19 ºC at 15.0A to 18.0V, shall be capable of delivering 14.0 Ah capacity after a 28.25 ±0.5V charging source has been applied to the battery for 1.0 hour. The battery shall not be damaged when a 28.25 ± 0.5V charging source is applied continuously to the battery at -40ºC, when tested in accordance with 4.5.29.2.1, as modified herein.

10. The battery shall conform to MIL-PRF-8565, except as modified by the following:

4.5.10 Cycling test. In the second sentence, delete “100 cycles” and substitute “85 cycles”.

4.5.12 Charge and discharge test at low temperature. Delete paragraphs 4.5.12 and paragraphs 4.5.12.a through 4.5.12.g in their entirety.

4.5.19 Vibration test. Delete the paragraphs 4.5.19 and 4.5.19.a through 4.5.19.h in their entirety and substitute the following:

4.5.19 Endurance and performance random test. The battery assembly, including connectors and cable, shall be mounted to the test apparatus, as specified in 4.4.5, and subjected to the random vibration test procedure for equipment installed in jet aircraft, Procedure I.A, Method 514.2 of MIL-STD-810. The battery shall be vibrated along each orthogonal axis in accordance with the Random Vibration Test levels specified on figure 4 of this specification sheet for a period of 21 minutes per axis. The battery heaters shall be energized and the battery charge at 28.25 ± 0.5 volts during vibration and shall be discharged at 97.5A for 1 minute prior to beginning each axis of vibration. The cables connected to the battery shall consist of four size AN-6 cables (two connected to the positive terminal and two connected to the negative terminal) and shall be clamped to the test apparatus at a cable length of 46 ± 3 centimeters from the battery. After completion of the vibration test, constant potential charge the battery in accordance with 4.4.2. Discharge the battery at the 6.5C-rate for 3 minutes. Examine the battery for the requirements of 3.7 and 3.8.10.”

4.5.22 Ground storage test. Line 4.5.22.d delete and add: "Subject the battery to three start cycles in accordance with figure 3, with a 2-minute rest period between starts.

4.5.28 Output performance test. Delete paragraphs 4.5.28, 4.5.28.a, through 4.5.28.d in their entirety and substitute the following:

4.5.28 Standby power output performance test.

4.5.28.1 Performance at -26 ºC. Battery sample 2 shall be charged as specified in 4.4.2, and

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

then placed on open-circuit at -26 ºC for 12 ± .5 hours. The battery while remaining in the -26 ºC chamber, shall be discharged into a 16-ohm resistive load for 0.5 hour. The battery shall maintain a terminal potential of 24.0 volts or greater during the discharge. The battery shall be removed from the chamber and immediately subjected to three start cycles in accordance with figure 3, with a 2-minute rest period between starts. The battery shall meet the requirements of 3.8.16.

4.5.28.2 Performance at -18 ºC. Battery sample 3 shall be tested in accordance with 4.5.28.1, except that the test temperature shall be -18 ºC, and the discharge time into 16 ohms shall be 1.0 hour.

4.5.28.3 Performance at 0 ºC. Battery sample 1 shall be tested in accordance with 4.5.28.1, except that the test temperature shall be 0 ºC, and the discharge time into 16 ohms shall be 3.0 hours.

4.5.28.4 Performance at 25 ºC. Battery sample 2 shall be tested in accordance with 4.5.28.1, except that the test temperature shall be 25 °C, and the discharge time into 16 ohms shall be 6.0 hours.

4.5.28.5 Performance at 49 °C. Battery sample 1 shall be tested in accordance with 4.5.28.1, except that the test temperature shall be 49 °C, and the discharge time into 16 ohms shall be 6.0 hours.

4.5.29 Cold and hot temperature charge test. Delete paragraphs 4.5.29, 4.6.29.a through 4.5.29.g in their entirety and substitute the following:

4.5.29 Cold and hot temperature charge test.

4.5.29.1 Half-hour charging. Battery sample 2 shall demonstrate the cold and hot temperature charging requirements of 3.8.17. The test shall be conducted as follows:

a. Charge battery at 28.25 ± 0.5V for 2 hours at 25 ºC.

b. Stabilize the battery at -18 ºC, then discharge at 15.0A to 18.0V. The battery shall provide at least 7.5 Ah capacity.

c. Stabilize the battery at 25 ºC, then charge at 28.25 ± 0.5V for 2 hours.

d. Stabilize the battery at -18 ºC, then discharge at 15.0A to remove all but 7.5 Ah, as determined by 4.5.29.1.b.

e. Rest battery to stabilize at test temperature, then apply 28.25 ± 0.5V for 30 minutes.

f. Immediately following charge, remove battery from test chamber and discharge at 15.0A to 18.0V. The battery shall deliver 14.0 Ah minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

4.5.29.2 The battery shall be tested in accordance with 4.5.29.1 except that the test temperature shall be 55 ºC.

4.5.29.2.1 One hour charging. Battery sample 3 shall be subjected to a -40 ºC charge demonstration test and shall be conducted as follows:

a. Charge the battery at 28.25 ± 0.5V for 2 hours at 25 ºC.

b. Stabilize the battery at -40 ºC and then discharge at 15.0A to 18.0V.

c. Rest battery to stabilize at -40 ºC, then apply 28.25 ± 0.5V for 1.0 hour.

d. Immediately following charge, remove battery from test chamber and discharge at 15.0A to 18.0V. The battery shall deliver 14.0 Ah minimum.

11. Referenced documents: In addition to MIL-PRF-8565, this document references:

MIL-STD-810
MIL-PRF-18148/3

12. Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection of batteries and order of tests.

Inspection number	Inspections	Qualification inspection			Requirements Paragraph	Method of inspection paragraph	Quality conformance Inspection		
		Qualification sample number					Group A tests	Group B tests	
		1	2	3				1	2
1	Visual and mechanical examination	X	X	X	3.5, 3.6, and 3.8.2	4.5.2	X	X	X
2	Dimensions and weight	X	X	X	3.8.3	4.5.3	X	X	
3	Dielectric strength	X	X	X	3.8.4	4.5.4	X	X	X
4	Strength of vent tubes	X	X	X	3.8.5	4.5.5	X	X	X
5	Color and marking	X	X	X	3.6	4.5.2	X	X	X
6	Electrical test preparation	X	X	X		4.5.6		X	X
7	Capacity discharge	X	X	X	Requirement 1 herein, 3.8.6, and requirement (1) of table III	4.5.7	X	X	X
8	Constant voltage discharge	X	X		3.8.7	4.5.8	X	X	
9	Strength of Receptacle			X	3.8.8	4.5.9			X
10	Standby power output performance	X	X	X	3.8.16	4.5.28			
11	Cold and hot temperature charge	X	X	X	3.8.17	4.5.29			
12	Cycling	X			3.8.9	4.5.10		X	
13	Capacity discharge at 49 °C		X		3.8.6 and requirement (2) of table III	4.5.11			
14	Discharge while inverted		X		3.5.9 and requirement (5) of table III	4.5.13			X
15	Altitude		X		3.7 and 3.5.9.	4.5.14			X
16	Mechanical shock	X			3.7 and 3.8.10	4.5.15			
17	Temperature shock	X			3.7 and 3.8.10	4.5.16			
18	Temperature rise and float		X		3.8.11	4.5.17			X
19	Battery gas emission		X		3.8.12	4.5.18			

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

TABLE II. Inspection of batteries and order of tests - Continued.

Inspection number	Inspections	Qualification inspection			Requirements paragraph	Method of inspection paragraph	Quality conformance inspection		
		Qualification sample number					Group A tests	Group B tests	
		1	2	3				1	2
20	Vibration		X		3.7 and 3.8.10	4.5.19			X
21	Humidity		X		3.7 and 3.8.10	4.5.20			
22	Salt fog	X			3.7 and 3.8.10	4.5.21			
23	Ground storage			X	3.8.13.1	4.5.22			
24	Physical integrity at high temperature	X			3.8.7 and requirement (1) of table III	4.5.23			
25	Final examination	X	X	X	3.8.4	4.5.31		X	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Navy - AS
DLA - CC

Preparing activity:
Navy - AS

(Project 6140-2025-006)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:31Z
Check the source to verify that this is the current version before use.