INCH-POUND
MIL-F-43402D
INT. AMENDMENT 3(SH)
29 October 1992
USED IN LIEU OF
AMENDMENT 2
24 March 1988

# MILITARY SPECIFICATION

## FOOD CUTTER, ELECTRIC

This interim amendment is approved for use within the Naval Sea Systems Command, Department of the Navy, with MIL-F-43402D, dated 30 December 1982.

PAGE 2

2.1, under "STANDARDS MILITARY", Add the following:

"MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-167/1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited).
MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities.

Delete: MIL-STD-1188 - Commercial Packaging of Supplies and Equipment."

2.2: Add the following:

"D 3951 - Standard Practice for Commercial Packaging."

PAGE 3

2.2: Add the following:

"NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION STANDARDS (NEMA)

(Applications for NEMA standards should be addressed to the National Electrical Manufacturers Association, 2101 L St., N.W., Washington, DC 20037)."

AMSC N/A FSC 7320
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:20Z
Check the source to verify that this is the current version before use.

Add the following paragraph:

"2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained."

3.2: Delete and substitute:

"3.2 Code and standards. The food cutter shall conform to the applicable requirements of UL Standard No. 73 and NSF Standard Nos. 2 and 8. Satisfactory evidence that these requirements have been met shall be submitted to the contracting officer or his authorized representative prior to the start of production (see 4.3)."

3.2.1: Delete entirely.

PAGE 4

3.2.1.1: Delete entirely.

3.2.1.2: Delete entirely.

PAGE 5

Table I, under size 1 maximum bowl diameter: Delete "14-5/16" and substitute "15-1/4".

3.4.5.2: Delete last two sentences and substitute: "When specified (see 6.2), food cutters shall be provided with a 6 foot ±2 inches long electric cord. The cord shall have a NEMA 5-15 P plug for 120-volt, 1-phase, 60 hertz or a NEMA L-15-20P plug for 208-volt, 3 phase, 60 hertz."

PAGE 6

3.4.5.3, after last sentence: Add the following:

"When specified for shipboard use, requirements and test limits of class A4 for surface ships and class A5 for submarines of MIL-STD-461 apply. Shipboard equipment shall meet the emission and susceptibility requirements for CE01, CE03, and RE02."

3.8, Delete and substitute:

"3.8 Data-name plates. The food cutter shall be furnished with a data-name plate in accordance with the applicable requirements of MIL-STD-130 except the requirements for; (a) Methods of applying, (b) Identification tags, (c) Information not required and (d) Optional marking information shall not apply. The data plates shall be made of minimum 20 gauge corrosion-resisting metal and attached to the food cutter by rivets, screws or welding in such a manner as to meet the



Source: https://assist.dla.mil -- Downloaded: 202610-21T21:20Z
Check the source to verify that this is the current version before use.

applicable National Sanitation Foundation sanitary requirements for this equipment. The plate shall contain the following information which shall be stamped, engraved or applied by photosensitive means:

National Stock Number
Procurement Instrument Identification Number
Specification Data
Manufacturer's Name, Address and Telephone Number
Supplier's Name, Address and Telephone Number
(List only if different from Manufacturer)
Manufacturer's Model Number
Government Approved Manual Number (See 6.2)

Each plate shall be placed so that it is readily visible to operator during normal operating use and so as to not adversely affect the life and utility of the food cutter."

PAGE 7

Add the following new paragraphs:

"3.11.4 Inclined operation. When specified for shipboard use, the food cutter shall operate satisfactorily when inclined at an angle of 15 degrees each side of the vertical in each of two vertical planes at right angles to each other, with no spillage of fluid or product when tested as specified in 4.4.6.

3.11.5 Environmental suitability. When specified for shipboard use, the food cutter shall be capable of withstanding ship's vibration and motion. Controls, switches, moving parts and electrical circuits shall operate under shipboard conditions without malfunction, binding, excessive looseness, or damage when tested as specified in 4.4.7.

* 3.11.6 High voltage labels. When specified for shipboard use (see 6.2), a Danger High Voltage label shall be affixed to the equipments outer case assembly, on or adjacent to each service access cover and adjacent to one of the fasteners which secures the cover. A high voltage warning label shall also be placed near the high voltage components inside the equipment. The label shall include but is not limited to the following warnings:

a. A warning of high voltage.
b. Power supply must be disconnected before using.
c. Access covers must be in place during use.
d. Servicing should be done by authorized individuals.

3.12 Human factors criteria (for Navy use only). Human factors engineering criteria, principles, and practices, as defined in MIL-STD-1472, shall be incorporated into the design of the food cutter. Maintenance and operation activities shall permit safe and efficient performance by the 5th percentile female to the 95th percentile male as defined in MIL-STD-1472. Controls and switches shall be selected and integrated into the design of the cutters so as to meet the applicable requirements of MIL-STD-1472. Sufficient clearance or free area required



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:20Z
Check the source to verify that this is the current version before use.

around an item shall permit an individual with applicable 5th to 95th percentile body dimensions and physical capabilities to safely operate, maintain, remove, or replace that item. When establishing accessibility requirements, both physical and visual access must be provided along with access for the use of any tools, test equipment, or replacement parts needed. When inspecting for defects and performing tests, the equipment shall adhere to the human factors engineering considerations listed herein.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all the requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material."

PAGE 10

Table II: Delete:

"Marking for identification Missing, incomplete, illegible X"
and substitute:

| | | | |
|---|---|---|---|
| "Data name plates - | Omitted or not as specified | (minor) | X |
| | Information incomplete or not legible | (minor) | X |
| | Not located so as to be readily visible to operator | (minor) | X" |

4.2.2.2, line 2, after "specified": Add "in table I and (when applicable) 3.4.6."

4.2.2.3, line 2: Delete "and 4.4.3 when applicable" and substitute ", 4.4.6, 4.4.7, and 4.4.3 when applicable."

4.2.3, line 4: Delete "except it need not be closed".

PAGE 11

4.3: Delete and substitute:

"4.3 Certification compliance examination. Certifications, certified tests reports or listing marks for standards, submitted in accordance with 3.2 shall be examined and validated as proof of compliance. Prior to government approval of first shipment the contractor shall submit to the contracting officer or his authorized representative for approval certification that the food cutter he proposes to furnish meet the applicable requirements of UL and NSF as follows:



Source: https://assist.dla.mil -- Downloaded: 202640-21T21:20Z
Check the source to verify that this is the currenversion before use.

4.3.1 UL. Acceptable evidence of meeting the requirements of UL shall be the UL listing mark, or a certified test report from a recognized independent testing laboratory acceptable to the Government, indicating that the food cutters offered have been tested and conform to UL Standard No. 73.

4.3.2 NSF. Acceptable evidence of meeting the requirements of NSF shall be:

(1) A listing in the current edition of the NSF "Listing of Food Service Equipment" and display of the NSF seal on the finished food cutter, or
(2) A certification for the food cutter issued by the NSF under their special one-time contract evaluation/certification service or,
(3) A certified test report acceptable to the contracting officer with the advice of the Army Surgeon General from an independent testing laboratory, indicating the food cutters have been tested and conform to the specified NSF Standards."

4.4.3, line 3 after "method": Insert "CE01,".

PAGE 12

Add the following new paragraphs:

"4.4.6 Inclined operational test (for shipboard use). After the test in 4.4.5 is completed, position the food cutter with the base set at an angle of 15 degrees, then operate the food cutter for 30 seconds at each side of the vertical in each of two vertical planes at right angles to each other. At each of these positions observe for conformance with specified requirements (see 3.11.4). For the test, the food cutter shall be filled to capacity with processed meat or vegetables.

4.4.7 Shipboard environmental test. The food cutter under normal operating conditions, shall be tested in accordance with MIL-STD-167/1, type I equipment. The food cutter shall be secured to the test machine in the same manner that it will be secured on shipboard (see 3.10.3). Failure of the food cutter to perform its function during and after testing, or to meet the requirements of 3.11.5 shall constitute the failure of this test."

PAGE 13

5.1.2 and 5.2.3: Delete: "MIL-STD-1188" and substitute "ASTM D 3951".

5.3: Delete "MIL-STD-1188" and substitute "ASTM D 3951".

6.2: Add the following:

"(1) Government approved manual number to be included on data-name plate (see 3.8)."



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:20Z
Check the source to verify that this is the current version before use.

Add the following new paragraph:

"6.5 Technical manuals. The requirement for technical manuals should be considered when this document is cited on a contract. If technical manuals are required, a contract exhibit must be prepared to fully describe statement of work criteria and delivery instructions, and cite the applicable technical manual requirements. The technical manuals must be acquired by separate Contract Line Item Number (CLIN) in the contract."

"NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Preparing activity:
Navy - SH
(Project 7320-N894)



Source: https://assist.dla.mil -- Downloaded: 2026-10-21T21:20Z
Check the source to verify that this is the current version before use.