NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/126
15 November 1996
SUPERSEDING
MIL-B-41809/43A
21 September 1994

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, RECRUITER, AIR NATIONAL GUARD, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

Dash 1 & 2

Dash 3

Dash 4 & 5

DASH NO.
-1: Master Longevity Recruiter Badge
-2: Recruiter of the Year Badge
-3: Senior Longevity Recruiter Badge
-4: Basic Recruiter Badge
-5: Rookie Recruiter of the Year Badge

MATERIAL: Red Brass

DIMENSIONS
HEIGHT (Overall):
-1, -2: 3-1/6 inches (7.78 cm) (REF)
-3: 3 inches (7.62 cm) (REF)
-4, -5: 2-9/16 inches (6.51 cm) (REF)
WIDTH (Overall): 2-15/32 inches (6.27 cm) (REF)
THICKNESS (On Flat Background Next to Minuteman):
0.060 inch ± 0.010 inch (0.152 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:41Z
Check the source to verify that this is the current version before use.

FINISH:
-1, -3, -4: Soft Baked Enameled, Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.
-2, -5: Soft Baked Enameled, Gold Plated, Matte Finish, Polished Highlights Polished and shall match TIOH Metal Finish Chip Number 8.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Soft baked enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Red	1
Blue	18

3. Epoxy resin (stoning epoxy) may be used in lieu of soft baked enamel at the option of the manufacturer. When epoxy resin is used, the epoxy shall not be stoned.

4. A full forcer shall be used to bring up the detail of the design and reduce the weight.

5. Piercing shall be as indicated for Dash No. -1 and -2 only.

6. The attaching device shall be prong and clutch type. Three prongs shall be located on a 1-78 inch ± 1/64 inch (4.76 cm ± 0.04 cm) diameter circle. Each prong shall be 120° degrees apart with one prong located on the vertical center line at the top of the badge.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0866)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:41Z
Check the source to verify that this is the current version before use.