INCH-POUND

MIL-DTL-3628/126A
21 July 2014
SUPERSEDING
MIL-DTL-3628/126
15 November 1996

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, RECRUITER, AIR NATIONAL GUARD, U. S. AIR FORCE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.



Dash 1 & 2



Dash 3



Dash 4 & 5

DASH NO.
-1: Master Longevity Recruiter Badge
-2: Recruiter of the Year Badge
-3: Senior Longevity Recruiter Badge
-4: Basic Recruiter Badge
-5: Rookie Recruiter of the Year Badge

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

DIMENSIONS
HEIGHT (Overall):
-1, -2: 3-1/6 inches (REF)
-3: 3 inches (REF)
-4, -5: 2-9/16 inches (REF)
WIDTH (Overall): 2-15/32 inches (REF)
THICKNESS (On Flat Background Next to Minuteman): 0.060 inch $\pm$ 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:41Z
Check the source to verify that this is the current version before use.

FINISH:
-1, -3, -4: Epoxy resin, Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Standard Metal Finish Chip Number 14.
-2, -5: Epoxy resin, 24K Gold Plated, Matte Finish, Polished Highlights Polished and shall match TIOH Metal Finish Chip Number 8.

ATTACHING DEVICE:
1. The attaching device shall be prong and wing type clutch.

2. Three prongs shall be located on a 1-78 inch ± 1/64 inch diameter circle. Each prong shall be 120 degrees apart with one prong located on the vertical center line at the top of the badge.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. EPOXY: Epoxy resin shall be applied to the Badge as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

COLOR	CHIP NUMBER
Red	1
Blue	18

3. A full forcer shall be used to bring up the detail of the design and reduce the weight.

4. Piercing shall be as indicated for -1 and -2 only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2014-231)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:41Z
Check the source to verify that this is the current version before use.