MILITARY SPECIFICATION SHEET
BATTERY, DRY, BA-1087/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the dry battery described herein shall consist of this document and the latest issue of Specification MIL-B-18.




TABLE OF METRIC EQUIVALENTS

INCH	MILLIMETERS
.010	.25
.015	.38
1/32	.79
.320	8.13
.656	16.66
5 27/32	148.43

(A) denotes change

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:56Z
Check the source to verify that this is the current version before use.

FSC-6135

NOTES:

1. All dimensions shown on figure are in inches. Unless otherwise specified, tolerances are ± 1/32 inch.
2. Metric equivalents specified in table are for general information only and are based upon 1 inch = 25.4 millimeters.
3. The cells shall be made with a dialysis barrier or equivalent and shall be sealed with a nylon seal or equivalent.

REQUIREMENTS:

Dimensions and configuration: See figure.

Nominal voltage: 4.05 volts.

Usual number and type of cells: 3 "R-12R: cells.

Usual cell connection: Series.

Terminals: Flat surface.

Weight (Maximum): 5.0 ounces.

(A) Capacity tests: When the battery is tested in accordance with the methods of examination and test of this Specification, the minimum capacity-test requirements shall be not less than the minimum time specified for SLD or SLT.

(A) First Article inspection:

Visual and mechanical (External).
Battery voltage.
Vibration test.
Mechanical-shock test per MIL-STD-202, method 213, test condition I.
Insulation resistance test per MIL-STD-202, method 302, test condition Letter B, tolerance ±20 volts.
Capacity, D (without storage).
Jacket integrity test.

(A) Quality conformance inspection:

Visual and mechanical (External).
Battery voltage.
Insulation-resistance test per MIL-STD-202, method 302, test condition Letter B, tolerance ±20 volts.
Vibration test.
Mechanical-shock test per MIL-STD-202, method 213, test condition I.
Jacket integrity test.
Electrode leakage.
Capacity, D & T.

Source: https://assist.dla.mil - Downloaded: 2026-10-15T16:56Z
Check the source to verify that this is the current version before use.

Methods of examination and test: The methods of examination and test shall be specified in MIL-B-18 and as follows:

Capacity tests: See requirements for capacity specified herein.

Storage -	Test	Period
	D	12 months
	T	90 days

Discharge - The battery shall be discharged through 20 ohms continuously to a test-end voltage of 2.70 volts.

(A) Special marking on each unit package:

TO TEST THIS BATTERY WITH TS-183 ( )/U:

USE JACK NO.	MINIMUM PERMISSIBLE VOLTAGE
7	3.0 volts

Unless expressly authorized, this test information shall apply to Army and Air Force applications only

Custodian: (A)
Army - ER

Preparing activity: (A)
Army - ER

Review activities:
Navy - SH

Project Number: (6135-A171-1)

User activities:
Army - ME
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T16:56Z
Check the source to verify that this is the current version before use.