METRIC

MIL-PRF-26536G
11 July 2017

SUPERSEDING
MIL-PRF-26536F
1 April 2011

PERFORMANCE SPECIFICATION

PROPELLANT, HYDRAZINE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Comments, suggestions, or questions on this document should be addressed to AFPET/PTPS, 2430 C Street, Bldg. 70, Area B, Wright-Patterson AFB OH 45433-7631 or e-mailed to AFPET.PTPS@us.af.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 9135

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

CONTENTS

PARAGRAPH		PAGE
1	SCOPE	1
1.1	Scope	1
1.2	Classification	1
1.3	Part or identifying number (PIN)	1
2	APPLICABLE DOCUMENTS	1
2.1	General	1
2.2	Government documents	1
2.2.1	Specifications, standards, and handbooks	1
2.3	Non-Government publications	2
2.4	Order of precedence	2
3	REQUIREMENTS	2
3.1	Chemical and physical properties	2
3.2	Limiting values	2
3.3	Filter	2
3.4	Qualitative	2
4	VERIFICATION	3
4.1	Classification of inspections	3
4.2	Conformance inspection	3
4.2.1	Individual tests	3
4.2.2	Sampling tests	4
4.2.2.1	Sampling plan	4
4.2.2.1.1	Sample	4
4.2.3	Rejection	4
4.3	Test methods	4
4.3.1	Examination of product	4
4.3.2	Hydrazine assay and water	4
4.3.3	Particulate	4
4.3.4	Chloride	4
4.3.5	Iron	4
4.3.6	Non-volatile residue (NVR)	5
4.3.7	Aniline	5
4.3.8	Carbon dioxide	5
4.3.9	Carbonaceous material	5
5.	PACKAGING	5
5.1	Packaging	5
6	NOTES	5
6.1	Intended use	5
6.2	Acquisition requirements	5
6.3	Safety data sheets (SDS)	5
6.4	Subject term (key word) listing	6
6.5	Changes from previous issue	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

TABLE
I Chemical and physical properties 3
A-1 GC parameters 7
G-1 GC parameters 26

FIGURE
D-1 NVR apparatus 18
F-1 CO_2 apparatus 25

APPENDIX
A Hydrazine assay and water 7
B Chloride 10
C Iron 12
D Non-volatile residue (NVR) 15
E Aniline 20
F Carbon dioxide 23
G Carbonaceous material 26

CONCLUDING MATERIAL 30

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

1. SCOPE

1.1 Scope. This specification covers the requirements for two grades of hydrazine (N_2H_4).

1.2 Classification. Hydrazine will be of the following designated grades as specified (see 6.2).

GRADES

Monopropellant (MPH)	-	Normal production.
High Purity (HPH)	-	Special production with strict control of specified impurities.

1.3 Part or identifying number (PIN). The PINs to be used for hydrazine acquired to this specification are created as follows:

M 26536 – X Example of PIN: M26536-S

- X: Grade (see 1.2). Use “M” for monopropellant; “H” for high purity.
- 26536: Specification number.
- M: Prefix for military specification.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-25604	Propellant, uns-Dimethylhydrazine
MIL-PRF-27401	Propellant Pressurizing Agent, Nitrogen
MIL-PRF-27404	Propellant, Monomethylhydrazine
MIL-PRF-27407	Propellant Pressurizing Agent, Helium

(Copies of these documents are available online at http://quicksearch.dla.mil.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM D1068	Standard Test Methods for Iron in Water
ASTM D1193	Standard Specification for Reagent Water
ASTM D1976	Standard Test Method for Elements in Water by Inductively-Coupled Argon Plasma Atomic Emission Spectroscopy
ASTM D2276	Standard Test Method for Particulate Contaminant in Aviation Fuel by Line Sampling
ASTM E29	Standard Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
ASTM E394	Standard Test Method for Iron in Trace Quantities Using the 1,10-Phenanthroline Method

(Copies of these documents are available from https://www.astm.org.)

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY (EPA)

EPA 300.0	Determination of Inorganic Anions by Ion Chromatography.

(Copies of this document are available from https://www.epa.gov/cwa-methods/approved-cwa-chemical-test-methods.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Chemical and physical properties. The chemical and physical properties of the propellant shall conform to those listed in Table I when tested in accordance with (IAW) the applicable test methods.

3.2 Limiting values. The following applies to all specified limits in this specification. For purposes of determining conformance with these requirements, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit according to the Rounding Method of ASTM E29.

3.3 Filter. A filter with a rating of at least 2 micrometer (µm) nominal and 10 µm absolute rating shall be installed between the manufacturer’s plant system and the container to be filled for delivery.

3.4 Qualitative. The propellant shall be colorless, homogeneous liquid when examined visually by transmitted light.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

TABLE I. ***Chemical and physical properties***

Properties	Monopropellant Grade (MPH)	High Purity Grade (HPH)	Test Paragraph
Hydrazine wt%, min.	98.5	99.0	4.3.2
Water wt%, max.	1.0	0.75	4.3.2
Ammonia wt%, max.	---	0.3	4.3.2
Particulate mg/L, max.	1.0	1.0	4.3.3
Chloride wt%, max.	0.0005	0.0005	4.3.4
Iron mg/kg (ppmw), max.	20	1.0	4.3.5
Non-volatile residue mg/L, max.	50	10	4.3.6
Aniline wt%, max	0.50	0.003	4.3.7
Carbon dioxide /1 wt%, max	0.003	0.003	4.3.8
Carbonaceous Material, (Total of OVCM/2 + OCM/3), wt%, max	0.02	0.005	4.3.9

NOTES:

/1 Determination of CO_2 content must be performed before all other analyses to prevent further absorption of CO_2.

/2 OVCM – Other volatile carbonaceous material as the total of Unsymmetrical dimethylhydrazine (UDMH), Monomethylhydrazine (MMH), and Isopropyl Alcohol (IPA).

/3 OCM – Other carbonaceous material consisting of any impurity providing a positive FID response excluding OVCM and aniline.

4. VERIFICATION

4.1 Classification of inspections. The inspections shall be classified as quality conformance inspections.

4.2 Conformance inspection. The quality conformance inspection shall consist of the following:

a. Individual tests (see 4.2.1)

b. Sampling tests (see 4.2.2)

4.2.1 Individual tests. The propellant shall be subjected to the following test as described under 4.3:

a. Examination of product (see 4.3.1)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

4.2.2 Sampling tests. The propellant shall be selected according to 4.2.2.1 and subjected to the tests in Table I as described under 4.3.

4.2.2.1 Sampling plan. Unless otherwise specified (6.2), each filled shipping container shall be considered a lot and shall be sampled.

4.2.2.1.1 Sample. A sample consists of not less than 1500 milliliters (mL) of propellant for all tests specified in 4.2.2. Unless otherwise specified, conformance tests shall be made on the sample of propellant taken directly from the shipping container. When required, the sample shall be forwarded to a laboratory designated by the procuring activity for subjection to the conformance tests specified herein. The clear glass narrow mouth bottles intended for sampling shall be specially cleaned and handled according to the procedure described in ASTM D2276 Section 10 (Preparation of Flushing Apparatus) with the exception listed in 4.3.3d. Sampling shall be conducted in such a manner that atmospheric exposure of the contents of the shipping container and the sample is minimized.

4.2.3 Rejection. When any sample of the propellant tested in accordance with 4.3 fails to conform to the requirements specified herein, the entire lot represented by the sample shall be rejected.

4.3 Test methods.

4.3.1 Examination of product. The propellant shall be visually examined while performing test specified in 4.3.3 to determine compliance with the requirement as specified herein. Examination to ensure that the material conforms to 3.4 shall be conducted after a representative aliquot of the sample has been transferred to a clear glass vessel and compared to the same type vessel containing the same volume of purified water.

4.3.2 Hydrazine assay and water. The propellant and water content of the sample shall be determined by one of the Gas Chromatographic (GC) methods described in Appendix A. In case of a dispute, the capillary column method (A.2.1) shall be the referee.

4.3.3 Particulate. The propellant sample shall be tested gravimetrically for particulate contamination in accordance with ASTM D2276, with the following exceptions:

a. Mix the sample thoroughly without exposure to air. Immediately pour 1000 mL of the sample into a clean 1000 mL graduated cylinder.

b. Pass the sample aliquot through a Mitex disc polytetrafluoroethylene (PTFE) hydrophobic, 5 µm, 0.47mm, white filter or equivalent.

c. The oven temperature shall be set at 70°C (158°F).

d. Filtered American Chemical Society (ACS) reagent grade isopropyl alcohol shall be used for rinsing the sample bottle and filter holder instead of petroleum ether specified in ASTM D2276. Use a suitable solvent resistant filter disc with an absolute rating of at least 1.0 µm. Wet the filter with the filtered isopropyl alcohol prior to filtering the sample.

4.3.4 Chloride. The chloride (Cl^-) level shall be determined by a calibrated ion chromatograph (EPA 300.0), or one of the methods described in Appendix B (colorimetric with mercuric thiocyanate or combinations of silver nitrate and/or specific ion electrodes (Ag^+/AgCl)). In case of a dispute, the specific ion electrode method (B.2.1) shall be the referee.

4.3.5 Iron. The iron content of the propellant shall be determined by one of the methods described in Appendix C. In case of a dispute, the inductively coupled plasma method (C.2.1) shall be the referee.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

4.3.6 Non-volatile residue (NVR). The nonvolatile residue of the propellant shall be determined in duplicate by one of the methods in Appendix D. In case of a dispute, the hot plate method (D.2.1) shall be the referee.

4.3.7 Aniline. The aniline content of the propellant shall be determined by one of the methods found in Appendix E. In case of a dispute the spectrophotometric method (E.2.1) shall be the referee method for monopropellant and the gas chromatographic method in E.2.2 for high purity.

4.3.8 Carbon dioxide. The carbon dioxide content of the propellant shall be determined by the method described in Appendix F.

4.3.9 Carbonaceous material. Other volatile carbonaceous material (OVCM) + other carbonaceous material (OCM) shall be determined by the gas chromatographic method found in Appendix G.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended Use. The propellant described by this specification is intended for use as a fuel in rocket engines.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Grade of the propellant required (see 1.2).

c. Method of shipment, type and capacity of containers.

d. Quantity by weight.

e. When a different sampling plan is required (see 4.2.2.1).

f. Packaging requirements (see 5.1).

6.3 Safety Data Sheets. Contracting officers will identify those activities that require copies of completed Safety Data Sheets (SDS) prepared in accordance with the 29CFR1910.1200.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing.

Catalytic Engine

Fuel

Monopropellant

Rocket Engine

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

HYDRAZINE ASSAY AND WATER

A.1 SCOPE

A.1.1 Scope. This Appendix describes two Gas Chromatographic methods for the determination of propellant and water content in the sample. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

A.2 METHODS

A.2.1 Gas chromatographic method - capillary column.

A.2.1.1 Procedure. A 60 or 30 meters (m) x 0.53 millimeters (mm), 1.00 µm, DB-Wax column, a thermal conductivity detector (TCD), with a split injector and an ultra-inert, deactivated, glass wool packed split liner shall be used. Table A-1 provides a summary of the critical operating parameters. These parameters may vary depending on GC system and detector brands, and may be adjusted by the chemist to provide optimal component resolution.

Allow the instrument to stabilize, condition the column by adding a couple of injections to the sample sequence. Perform check runs by processing three consecutive injections of 1 microliter (µL) of sample. The checks must meet the quality control criteria in A.2.1.3.

This method may be used for aniline quantification for monopropellant hydrazine.

TABLE A-1. *GC parameters*

PARAMETER	CONDITION
Injector Port Temp	150 °C
Injection Mode	Split injection
Sample Volume.	1 µL
Split Ratio	10:1
Carrier Gas	He
Control Flow	10 mL/min
Control Mode	Flow
TCD Detector Temp.	210 °C
Equilibration Time	2.00 min
Initial Temp.(T_0)	60 °C
Initial Time (t_0)	3.00 min
Rate (1)	10 °C/min
Final Temp. (T_{f1})	100 °C
Final Time (t_{f1})	0.00 min
Rate (2)	20 °C/min
Final Temp. (T_{f2})	185 °C
Final Time (t_{f2})	3.75 min

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

A.2.1.2 Calculations.

$$\%N_2H_4 = \frac{A_{N_2H_4} \times 100}{\sum A_i}$$

$$\%H_2O = \frac{A_{H_2O} \times 100}{\sum A_i}$$

$$\%NH_3 = \frac{A_{NH_3} \times 100}{\sum A_i}$$

NOTE: % NH_3 for high purity grade only.

where,

$A_{N_2H_4}$ = The measured area of the N_2H_4 peak multiplied by its signal attenuation factor.

A_{H_2O} = The measured area of the H_2O peak multiplied by its signal attenuation factor.

A_{NH_3} = The measured area of the NH_3 peak multiplied by its signal attenuation factor.

$\sum A_i$ = The sum of all measured peak areas multiplied by their signal attenuation factors.

Assumption: The thermal conductivities of all components in the sample are equal.

A.2.1.3 Quality control. The following performance criteria must be met for fuel purity analysis,

GC replicate analyses (3 consecutive)	RSD[a] ≤ 5 %

a. RSD = Standard Deviation * 100% / Mean

A.2.1.4 Equipment.

(1) Gas chromatograph equipped with a TCD and a split injector.

(2) Agilent ChemStation or equivalent.

(3) A 60 m x 0.53 mm ID and 1.00 µm film thickness DB-wax capillary column (Agilent P/N 125-7062 or equivalent).

(4) Ultra-inert deactivated liner, split, straight, glass wool.

(5) No-bleed septa.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

A.2.2 Gas chromatographic method - packed column.

A.2.2.1 Assay column preparation. Cap one end of a 1/8 inch (in) outer diameter (OD) by 6 foot (ft) nickel tube and fill the tube with the Tenax TA column packing by pouring through a small funnel attached to the other end. Tap or mechanically vibrate the tube to ensure uniform packing. When the tube is filled, plug both ends with a small wad of glass wool, bend the column to the configuration required by the column oven, and connect the column to the inlet fitting in the oven. Condition the column with carrier gas (helium) flowing and the oven set at 200°C for one hour. After conditioning the column, connect the other end to the detector and set the carrier gas flow to approximately 25 milliliters per minute (mL/min), and the column oven to 50°C. The inlet and detector temperatures, if separately heated, shall be set to 100°C and 150°C, respectively. The detector current should be set to a nominal sensitivity value recommended for helium by the instrument manufacturer. The column temperature and carrier gas flow may be adjusted to provide adequate component resolution for minimum analysis time.

A.2.2.2 Procedure. Equilibrate the column with propellant by injection of three or more 1 – 2 µL samples into inlet. If more than 30 minutes (min) elapse between analyses, a single 1 µL injection of propellant should re-equilibrate the column. Inject 1 - 2 µL of propellant for analysis and record the areas of all peaks in the chromatogram, using the following time/temperature program:

Helium carrier gas flow	20 – 25 mL/min
Initial temperature	50°C
Rate	20°C/min
Final temperature	155°C
Final time hold	4 min

Each analysis should require less than 20 min for elution of all components. The elution order of possible components is as follows:

Air > ammonia> methylamine > water > hydrazine.

A.2.2.3 Calculations. Use equations in A.2.1.2.

A.2.2.4 Equipment and Reagents.

a. Equipment:

(1) Gas chromatograph equipped with a TCD.

(2) Agilent ChemStation or equivalent.

(3) Packed column may be commercially obtained.

b. Reagents:

Tenax TA 60/80 mesh or equivalent.

.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

CHLORIDE

B.1 SCOPE

B.1.1 Scope. This Appendix describes two methods for the determination of chloride content of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

B.2 METHODS

B.2.1 Specific ion electrode method.

B.2.1.1 Procedure. Rinse the propellant residue container in one vessel from 4.3.6 with a 5 mL aliquot of 1N sulfuric acid (H_2SO_4). Briefly stir and heat the liquid to boiling and cover with an inverted watch glass to prevent the condensate from escaping. Transfer the solution to a 25 mL volumetric flask. Rinse vessel with a second 5 mL aliquot of acid followed by one 5 mL aliquot of purified water. Combine the aliquots in the 25 mL volumetric flask and add two to three drops of bromocresol green indicator. Dropwise titrate the contents of the flask to a green endpoint with 1N sodium hydroxide (NaOH) and dilute to the mark with purified water. Mix the solution and transfer approximately 10 mL to a 25 mL beaker. Immerse the electrodes in the sample solution and record the millivolt reading (mV). Compare the mV reading from the sample to a calibration curve prepared from chloride standards and record the concentration (ppmv) of the sample.

B.2.1.2 Calculation. Calculate the percent chloride in the sample using the following formula:

$$\%Cl^- = \frac{(ppmv\ Cl^-)(V_d)}{(V_h)(D)(1 \times 10^4)}$$

where,

V_d = Final dilution volume taken from NVR residue in mL.

V_h = Volume of hydrazine used in NVR analysis in mL.

D = Density of hydrazine (1.01 g/mL).

B.2.1.3 Reagents and equipment. The following shall apply as test conditions of 4.3.4:

B.2.1.3.1 Reagents.

a. Purified water free of interfering substances; the water is considered free of interfering substances if a 100 mL sample used to dissolve 0.1 gram (g) of silver nitrate, shows no turbidity after standing in the dark for 24 hours. The purified water as described in this paragraph shall be used throughout the procedure.

b. 1N H_2SO_4; prepare by pouring 29 mL of ACS reagent grade concentrated H_2SO_4 into 300 mL of purified water contained in a 1000 mL volumetric flask (commercially available). Cool the solution to room temperature, dilute to the mark with the purified water, and mix thoroughly. Transfer the solution to a plastic bottle.

c. 1N NaOH; prepare by dissolving 40 g of ACS reagent grade, low carbonate, NaOH in 300 mL of purified water contained in a 1000 mL volumetric flask (commercially available). Cool the solution to

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

room temperature, dilute to the mark with purified water, and mix thoroughly. Transfer the solution to a plastic bottle and protect from long exposure to the atmosphere.

d. Standard sodium chloride (NaCl) solution, 1 mL = 1.00 mg Cl^-; weigh 1.648 g dry NaCl into a 1 liter (L) volumetric flask. Dilute to the mark with purified water. Transfer the thoroughly mixed solution to a clean polyethylene bottle for storage. A 1000 mg/L (ppmv) chloride standard may be commercially obtained; must be certified.

e. Bromocresol green indicator; 1% aqueous solution. Use purified water.

B.2.1.4.2 Equipment.

a. Chloride electrode – solid state Orion 9417BN, or equivalent.

b. Reference electrode - Orion 900200 Sure-Flow® double junction with 1M potassium nitrate (KNO_3) outer compartment filling solution, or equivalent.

c. pH/voltmeter, Orion 420A+ or equivalent.

B.2.2 Colorimetric method.

B.2.2.1 Procedure. Add to the propellant residue container in one vessel from 4.3.6 five milliliters of ferric alum indicator and transfer to a 100 mL volumetric flask. Rinse the vessel with three 5 mL purified water aliquots and combine into the volumetric flask. Set samples aside.

Prepare a calibration blank and at a minimum two standards to bracket the expected chloride concentration in the samples in 100 mL volumetric flasks, and add 5 mL of ferric alum indicator. Add 2.5 mL of mercuric thiocyanate solution to each volumetric flask, samples and standards, and dilute to the mark with purified water. Mix the solutions thoroughly and allow to stand in darkness for 15 – 30 min. Analyze in a UV-Vis spectrophotometer at 460 nm, at the wavelength recommended by the instrument manufacturer, or at that which provides the highest sensitivity using 5 cm cells. Use the blank to set the instrument to zero absorbance and determine the absorbances of standards and samples. Prepare a calibration curve of absorbance vs concentration and determine the chloride concentration in the samples. The calibration correlation coefficient shall be ≥ 0.999.

B.2.2.2 Calculation. Calculate the chloride content of the propellant using the formula in B.2.1.2.

B.2.2.3 Reagents and equipment.

B.2.2.3.1 Reagents.

a. Purified water of 18M-ohm or greater resistivity.

b. Ferric alum indicator, Volhard (oxidation reduction indicator) – Dissolve 10 g of ferric ammonium sulfate dodecahydrate ($FeNH_4(SO_4)_2 \cdot 12H_2O$) ACS reagent grade in approximately 50 mL of purified water. Add 10 mL of ACS reagent grade nitric acid, and dilute to 100 mL with purified water. (may be commercially obtained).

c. Mercuric thiocyanate, 4.17 g/L in methanol for chloride determination (commercially available).

d. Chloride standard, 1000 mg/L (may be commercially obtained; must be certified).

B.2.2.3.2 Equipment. UV-Vis Spectrophotometer, double beam, equipped with 5 cm cells.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

IRON

C.1 SCOPE

C.1.1 Scope. This Appendix describes three methods for the determination of iron content of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

C.2 METHODS

C.2.1 Inductively Coupled Argon Plasma-Atomic Emission Spectrometry. For each instrument interference effects must be evaluated, corrected as applicable (ASTM D1976), and instrument performance validated. The argon gas supply must have a purity of 99.99% or better. Choose the iron wavelength recommended by the instrument manufacturer or that which provides the highest sensitivity (most commonly used is 259.940 nm).

C.2.1.1 Procedure. Rinse the propellant residue contained in one vessel from 4.3.6 as follows: Add 5 mL of 5N H_2SO_4 to the vessel and place on a hot plate. Heat the mixture to near boiling, maneuver beakers so the acid contacts the surface area of the glass that the fuel mixture came in contact with, and maintain at that temperature for three to five minutes. Allow the solution to cool and transfer to a 100 mL volumetric flask. Rinse the vessel at least three times with 5 mL aliquots of 0.1N H_2SO_4 combining all rinses in the volumetric flask. Dilute to the mark with purified water and mix thoroughly.

NOTE: Nitric acid may be substituted for sulfuric acid in C.2.1.1 provided standards and samples are matrix matched (applies to all of C.2).

C.2.1.2 Calibration. Prepare an acid matrix blank and an Fe standard in a 0.1N H_2SO_4 acidified purified water solution to bracket the expected concentration range of the samples by combining an appropriate aliquot of a certified Fe stock standard. Prepare a mid-range check standard, from a different stock standard source to verify the calibration. Determine the concentration from the calibration curve prepared from the iron standard using the acid matrix blank as the zero point, and record the iron concentration of the sample.

C.2.1.3 Quality control. The instrumental drift shall be checked using the acid matrix blank and standard at the beginning of each run, at least every ten readings during the run, and at the end of the run. The blank shall read ≤ the detection limit and the standard shall fall within ± 10% of the standard value. If the recovery of the analyte falls outside of the required control limits, the source of the problem must be identified and resolved before continuing analyses.

C.2.1.4 Calculation. Calculate the iron content of the propellant using the following formula:

$$Fe\ ppmw = \frac{(Fe_{ppmv})(V_d)}{(V_h)(D)}$$

where,

Fe_{ppmv} = Iron content of the sample solution from the calibration curve.

V_d = Final dilution volume taken from NVR in mL.

V_h = Volume of hydrazine used in NVR analysis in mL.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

D = Density of hydrazine (1.01 g/mL).

C.2.1.5 Reagents and equipment. The following shall apply as test conditions of C.2.1.

C.2.1.5.1 Reagents.

a. Purified water of 18M-ohm or greater resistivity.

b. Iron standard, certified commercially obtained solution.

c. Sulfuric or nitric acid, concentrated, suitable for trace metal analysis.

C.2.1.5.2 Equipment.

a. Hot plate – controllable heat.

b. Inductively-coupled argon plasma atomic emission spectrometer (ICP-AES).

C.2.2 Atomic absorption.

C.2.2.1 Procedure. Prepare the sample solution in the same manner as described in C.2.1.1 or dilute the hydrazine sample 1:2 and use directly. Determine the absorbance of the sample at an iron wavelength closest to 2480 Å on a suitable atomic absorption spectrophotometer, after setting the instrument to zero absorbance, with 0.1N H_2SO_4. Compare the results to a calibration curve prepared from iron standards and record the iron concentration of the sample.

C.2.2.2 Calibration. Prepare a minimum of three calibration standards to bracket the expected iron concentration range of the samples and a mid-range check standard to verify the calibration in the same manner as described in C.2.1.2. After setting the instrument to zero absorbance with 0.1N H_2SO_4, determine the absorbance of the calibration standards and check standard. Prepare a calibration curve of absorbance vs iron concentration.

C.2.2.3 Calculations. Determine the iron content of the propellant as follows,

C.2.2.3.1 Iron from NVR residue. Use the formula in C.2.1.4.

C.2.1.3.2 Iron from direct hydrazine analysis.

$$Fe\ ppmw = \frac{(Fe_{ppmv})(DF)}{(D)}$$

where,

DF = Dilution factor used to dilute hydrazine.

D = Density of hydrazine (1.01 g/mL).

C.2.2.4 Quality control. Follow the guidelines described in ASTM D1068 Method A with the following exception:

a. The mid-range standard from C.2.1.2 shall be used as the laboratory control sample.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

C.2.2.5 Reagents and equipment.

C.2.2.5.1 Reagents. Same as in C.2.1.5.

C.2.2.5.2 Equipment. Atomic absorption spectrophotometer with an iron hollow cathode lamp.

C.2.3 Colorimetric method.

C.2.3 1 Procedure. ASTM E394 shall be followed with the following exceptions:

a. Add 5 mL of the ammonium acetate-acetic acid buffer solution to each empty 100 mL volumetric flasks (for standards and samples) and set aside.

b. Dissolve the residue of each vessel from 4.3.6 by adding 1 mL of concentrated acid (H_2SO_4 or HNO_3 as applicable) and carefully adding 50 mL purified water. Mix thoroughly.

c. Add 1 mL of concentrated acid (H_2SO_4 or HNO_3 as applicable), and 50 mL purified water to at least four empty 150 mL evaporating dishes for the standards.

NOTE: Make sure solution is thoroughly mixed after each component addition.

d. Add the 2 mL of hydroxylamine hydrochloride and the 5 mL of 1,10-phenanthroline as described in the method.

e. Add enough sodium acetate (instead of the buffer called out in the method) to bring the pH of the mixture to between pH 3 and pH 4 while swirling (add ~20 mL initially and then continue adding drop wise until desired pH is reached).

f. Transfer the solutions to their respective 100 mL volumetric flask from step a above, dilute to the mark, and mix thoroughly. Allow the flasks to set at room temperature in the dark for a minimum of 15 minutes.

g. Determine iron concentrations from the calibration curve prepared from the iron standards; the correlation coefficient shall be ≥ 0.990.

C.2.3.2 Calculations. Calculate the iron content of the propellant using the formula in C.2.1.4.

C.2.3.3 Reagents. The following reagents are in addition to those reagents listed in ASTM E394,

a. Sodium acetate solution. Dissolve 200 g $CH_3COONa•3H_2O$ in 1 L volumetric flask with 700 mL of purified water and dilute to the mark. An equivalent solution may be obtained commercially.

b. Sulfuric or nitric acid, concentrated, suitable for trace metal analysis.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

NON-VOLATILE RESIDUE (NVR)

D.1 SCOPE

D.1.1 Scope. This Appendix describes three methods for the determination of non-volatile residue of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

D.2 METHODS

D.2.1 Hot plate. This method involves the gradual evaporation of a hydrazine sample on an explosion proof hot plate in a fume hood. The difference in weight before and after evaporation is calculated as NVR.

D.2.1.1 Procedure. Place three clean borosilicate glass or platinum evaporation dishes in an oven at 110°C for 30 minutes. Label one as a blank and the others as samples A1 and A2. Remove evaporation dishes from the oven, place in a desiccator to cool for 15 minutes, and then place next to a five place balance long enough to equilibrate (usually around 30 min). Weigh each clean, dry evaporating dish to the nearest 0.0001 g until the weight remains constant to ± 0.1 mg. Record the sample evaporating dish weight as A1, A2 and the blank evaporating dish weight as C. Add 40 mL of water to each one of the evaporating dishes. Transfer 40 mL of hydrazine sample into the evaporating dishes marked A1 and A2. Hydrazine and water form an azeotrope (constant boiling mixture) with a maximum boiling point of 120.5°C (771 mmHg pressure). Therefore, when anhydrous hydrazine and water are mixed, a corresponding eutectic of 76.0 mole percent hydrazine is the maximum concentration obtained. This eliminates any significant hazard in evaporating a hydrated sample of hydrazine to dryness. Place each evaporating dish on a hot plate which is set to a temperature of 150 – 200°C. Evaporate to dryness, but do not bake. Remove the evaporating dishes from the explosion-proof hot plate and place them in oven set at 110°C for 30 minutes. Remove dishes from oven and place in a desiccator for 15 minutes to cool; then place them next to a five place balance long enough to equilibrate. Weigh each evaporating dish as before to a constant weight. (NOTE: A/C fluctuations/cycling may significantly affect the weights obtained for the evaporating dishes; a narrow range viscosity thermometer is recommended for monitoring room temperature during the weighing process). Record the sample evaporating dish weight as B1, B2 and the blank evaporating weight as D.

NOTE

Save the propellant residue for chloride (4.3.4) and iron (4.3.5) determinations.

D.2.1.2 Calculations. Calculate the non-volatile residue of the propellant as follows:

$$NVR, mg/L = \left[\frac{(Wt_B - Wt_A) - (Wt_D - Wt_C)}{Sample\ volume,\ mL}\right] \times 10^6$$

where,

A = Weight of the sample evaporating dish, g.

B = Weight of the sample evaporating dish and residue, g.

C = Weight of blank evaporating dish, g.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

D = Weight of blank and water residue, g.

D.2.1.3 Equipment.

a. Hot plate, explosion proof.

b. High efficiency fume hood.

c. Five decimal place analytical balance (semi-micro balance).

D.2.2 Dropwise method.

D.2.2.1 Procedure. Clean the unassembled apparatus with detergent and rinse thoroughly with purified water. Dry the parts in an oven at 110°C. Assemble the apparatus as shown in Figure D-1. Fill the water bath with purified water and turn on the heater. Adjust the water level of the bath to approximately one-half inch below the lowest fitting and mark this level on the bath. When the temperature bath reaches boiling, adjust the nitrogen purge to approximately 2 L/min and turn on the aspirator. With the sample delivery valve closed, the pressure in the apparatus should be below 30 mmHg. Open the sample delivery valve slowly to adjust the apparatus pressure to approximately 60 mmHg. Allow the apparatus to purge for approximately five minutes to remove traces of water. Remove the water bath and dry the outside of the residue vessel with a clean lintless tissue. Disconnect the aspirator from the apparatus and remove the residue vessel using a tissue to hold the vessel. Wipe the outside of the vessel and place it near the analytical balance. After at least 20 min, accurately weigh the residue vessel until the weight remains constant to ± 0.1 mg. Record the weight. Reassemble the apparatus and close the sample delivery valve. Replace the water bath, adjust the water level to the mark, and heat the water to boiling. Transfer 100 mL of propellant to the apparatus. With the nitrogen purge in place, turn on the water aspirator and reduce the apparatus pressure to less than 30 mmHg. Slowly open the sample delivery valve to admit propellant to the residue vessel and adjust the flow such that the apparatus pressure does not exceed 60 mmHg (approximately 2 drops per second). The quantity of propellant in the residue vessel should not exceed 2 - 4 mL at the equilibrium evaporation rate. Adjust the sample delivery valve to maintain the evaporation pressure at less than 60 mmHg. After 100 mL of propellant have been evaporated (approximately 30 min), allow the residue vessel to purge for an additional five minutes to ensure complete evaporation of volatile material. Remove the water bath, disconnect the aspirator, wipe the outside of the residue vessel, and remove it from the apparatus. Allow the residue vessel to stand near the analytical balance for at least 20 min before weighing. Weigh the residue vessel as above, and record the weight. To clean the residue vessel reflux 5 mL of 5N ACS reagent grade H_2SO_4 (or equivalent) in the vessel for several minutes followed by several rinses of purified water. The vessel may be dried as described above or by gently heating the vessel with a burner while purging with dry nitrogen. Regardless of the drying method used, allow at least 20 min for the vessel to equilibrate to ambient temperature and humidity before weighing.

NOTE

Save the propellant residue for chloride (4.3.4) and iron (4.3.5) determinations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

D.2.2.2 Calculations. Calculate the non-volatile residue of the propellant as follows:

$$NVR, mg/L = \left[\frac{W_2 - W_1}{V}\right] \times 10^6$$

where,

W_1= Weight of clean vessel, g.

W_2 = Weight of residue and vessel, g.

V = Volume of sample used, mL.

Report the averaged result of duplicate NVR determinations.

D.2.2.3 Equipment. The following equipment shall apply as test conditions of D.2.2.


a. Components described in Figure D-1.

b. Tubing – polyethylene, ½ in OD, borosilicate glass, ½ in OD.

c. Clamps – hose, to fit ½ in OD tube.

d. Five decimal place analytical balance (semi-micro balance).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.



A - GN_2

B - Water aspirator (glass or polyethylene)

C - Connector (polyethylene, separable)

D - Gauge (stainless steel, absolute pressure, 0 - 760 mmHg range)

E - Adapter (Swagelok SS-8-TA-7-4 or equivalent)

F - Union Tee (Swagelok SS-810-3 or equivalent; 2 ea.)

G - Pipette (100 mL, volumetric, borosilicate glass)

H - Joints (borosilicate glass, spherical, 12/5, ball, socket and clamp)

I - PTFE Ferrules (Swagelok T-814-1, T-813-1, T-404-1, T-403-1, or equivalent)

J - Connector (Swagelok SS-400-7-2 or equivalent)

K - Sample delivery valve (Swagelok SS-ORM2 or equivalent)

L - Syringe (100 mL glass with an 8 – 12 in PTFE needle).

M - Rod (PTFE or polyethylene, 1/4 in OD & a 1/16 in OD x 0.025 in wall tube inserted)

N - Reducer (Swagelok SS-400-R-8 or equivalent)

O - Beaker (glass, 1000 mL capacity)

P - Flask (25 mL volumetric, borosilicate glass)

Q - Hot plate (adjustable heat range)

NOTE: All fittings, stainless steel, Swagelok or equivalent.

FIGURE D-1. ***NVR apparatus***

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

D.2.3 Rotary evaporation.

D.2.3.1 Procedure. Dry a 250 mL round bottom flask in an oven at 110°C for one hour. Allow the flask to cool in a desiccator and weigh on the analytical balance until the weight remains constant to ± 0.1 mg. Transfer 100 mL of hydrazine into the 250 mL flask. Place the flask on the evaporator using a standard taper Teflon sleeve as a seal. Attach a water aspirator pump to the evaporator via a one liter suction flask and evaporate the hydrazine to dryness. A water bath may be placed around the rotating flask to aid evaporation.

WARNING

The contact of hydrazine vapor with metal surfaces, as in a metal rotary evaporator, must be avoided. Do not exceed 40°C during the initial evaporation phase when hydrazine liquid is present. Chemical splash proof goggles must be worn throughout the entire evaporation process.

When no more hydrazine distills over, the water bath is lowered. Final high boiling components (mainly aniline) are distilled under vacuum at temperatures up to 100°C using a hot air gun for heating. The flask is then removed and dried in an oven at 110°C for one hour and weighed as before to a constant weight.

NOTE

Save the propellant residue for chloride (4.3.4) and iron (4.3.5) determinations.

D.2.3.2 Calculations. Use equation in D.2.2.2.

D.2.3.3 Equipment.

a. All glass rotary evaporator, BÜCHI Rotavapor or equivalent.

b. Flask, round bottom, 250 mL, with standard neck to fit evaporator.

c. Water aspirator – glass or polyethylene.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

ANILINE

E.1 SCOPE

E.1.1 Scope. This Appendix describes three methods for the determination of aniline content of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

E.2 METHODS

E.2.1 Spectrophotometric method.

E.2.1.1 Procedure. For high purity, pipette or syringe 5 mL of propellant into a 25 mL volumetric containing approximately 15 mL of purified water; for monopropellant pipette or syringe 0.10 mL (100 µL) of propellant. Dilute to the mark with purified water, and mix the solution thoroughly. Fill two 1 cm pathlength silica spectrophotometer cells with purified water and place one in each position for sample and reference cells. Using the appropriate source and detector for the spectrophotometer, set the absorbance to zero at 320 nm and scan the region between 320 and 240 nm. If the baseline is relatively stable, the cells and purified water can be considered free from interfering substances. Exchange the water in the sample cell with the previously prepared sample, using several rinses with the sample solution, and rescan the 320 to 240 nm region, first ensuring that the instrument is set to zero absorbance at 320 nm. Using a baseline under the aniline peak at 280 nm, measure, and record the net absorbance of the peak. Determine the aniline content of the sample by comparing the net absorbance obtained to a calibration curve of net absorbance versus percent aniline.

E.2.1.2 Calibration. Pipette or syringe 0.025 mL (25 µL) of ACS reagent grade aniline into a 100 mL volumetric flask containing 50 mL of purified water. Shake the mixture to dissolve the aniline and dilute the solution to the mark with purified water. Mix the standard thoroughly. This standard is equivalent to 0.025%. Prepare a series of calibration standards in the aniline range expected to find in the samples. Determine the net absorbance of standards versus purified water in the same manner as with the sample. Plot net absorbance versus percent aniline and draw a curve through the points. A check standard shall be prepared fresh daily to check the calibration standards. If the check standard falls outside of ± 5% of the expected value, fresh calibration standards shall be prepared and the calibration check repeated until the required accuracy is demonstrated.

E.2.1.3 Equipment. Spectrophotometer, double beam, ultra violet, narrow band width, recording, equipped with 1 cm silica cells.

E.2.2 Gas chromatographic method – Stabilwax®-DB (carbonaceous material determination).

E.2.2.2 Procedure. Follow the procedure described in G.2.1.1.

E.2.2.3 Calibration. Follow the calibration procedure as described in G.2.1.2. Add approximately 120 µL ACS reagent grade aniline to the OVCM stock standard solution, and prepare the working standard as described in G.2.1.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

E.2.2.4 Calculation. Calculate the concentration by weight of aniline by using the following equations,

a. Standard stock solution:

$$Aniline\ ppmw = \frac{Wt_{aniline} \times 10^6}{Wt_{Total}}$$

where,

$$Wt_{Total} = Wt_{N_2H_4} + Wt_{UDMH} + Wt_{IPA} + Wt_{MMH} + Wt_{aniline}$$

b. Working standard:

$$Aniline\ ppmw = \frac{Aniline_{Stock\ Std\ Conc} \times Wt_{aniline\ added}}{Wt_{aniline\ added} + Wt_{N_2H_4}}$$

Sample calculation:

$$Aniline\ ppmw = \frac{Aniline_{Std\ Conc} \times A_s}{A_{aniline} - A_s}$$

where,

$A_{aniline}$ = The area of the aniline peak times its attenuation factor.

A_s = The area of the aniline in the sample times its signal attenuation factor.

The elution order is as follows:

UDMH < IPA < MMH < water < hydrazine < aniline

NOTE: Water and hydrazine co-elute.

E.2.3 Gas Chromatographic method - Carbowax 20M.

E.2.3.1 Procedure. A 0.53 mm OD x 15 m crosslinked “Carbowax 20M” capillary column shall be used. Helium is used as a carrier gas. A gradient temperature program is used from 40°C to 130°C. Splitless injection is used. Sample size should be 0.4 to 1 µL. Condition the column with several injections of the calibration mixture three minutes apart. After the fifth injection, allow sufficient time for the final injection of aniline to elude, approximately 10 min. Adjust flow rate to allow for baseline separation of the trace monomethylhydrazine from hydrazine.

E.2.3.2 Calibration (high purity hydrazine). Pipette or syringe 0.5 mL of aniline into a 1.0 L volumetric flask containing approximately 500 mL of purified water, and mix the solution thoroughly. Fill to the mark with purified water and thoroughly mix. Pipette 10 mL of this solution into a 100 mL volumetric flask and dilute to the mark. This calibration standard is equivalent to 0.005% aniline in

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

propellant. Inject 1.0 µL of the standard into the inlet of the chromatograph and record the area of the aniline peak.

E.2.3.3 Calculation. Use the following formula for the calculation of the aniline content of the propellant:

$$Aniline\ \% = \frac{0.005\ As}{Ac}$$

where,

As = Area of the sample aniline peak multiplied by its attenuation factor.

Ac = Area of the standard aniline peak multiplied by its attenuation factor.

E.2.3.4 Equipment. The following equipment shall apply to test conditions of E.2.3.

a. Gas chromatograph, equipped with a flame ionization detector (FID).

b. Agilent ChemStation or equivalent.

c. A 0.53 mm OD x 15 m crosslinked “Carbowax 20M” capillary column

E.2.4 Alternate capillary method

E.2.4.1 Procedure for monopropellant grade hydrazine. Aniline content may also be determined using the assay capillary column method described in Appendix A of this specification (A.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

CARBON DIOXIDE

F.1 SCOPE

F.1.1 Scope. This Appendix describes a method for the determination of carbon dioxide content of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance. Determination of the CO_2 content in the propellant must be performed before all other analyses to prevent further absorption of CO_2.

F.2 METHOD

F.2.1 Determination of carbon dioxide by non-dispersive IR analysis. This method is to be utilized to determine the carbon dioxide concentration in hydrazine within a 10 - 100 mg/kg (ppmw) range. The sample of propellant is injected into a solution of 30% phosphoric acid which absorbs the hydrazine and ammonia. Carbon dioxide is liberated from the acidic solution and is swept out of the solution by a stream of nitrogen through a silica gel drying tube to remove water vapor, and is measured by an infrared technique.

F.2.1.1 Calibration procedure.

a. Assemble the apparatus as shown in Figure F-1.

b. Adjust the flow of nitrogen purge gas according to the manufacturer's recommendation by use of a control valve and flow meter.

c. Add an appropriate amount of 30% phosphoric acid containing several drops of bromocresol green indicator to the CO_2 reaction flask, turn on the nitrogen (N_2) gas to give vigorous, constant mixing. The nitrogen flow (approximately 200 mL/min) should be kept constant throughout the analysis.

d. After the apparatus has stabilized, adjust the zero on the infrared analyzer.

F.2.1.2 Standardization. Direct instrument response (flow technique),

a. Inject via the septum on the phosphoric acid containing unit, an appropriate amount (approximately 200 µL) of the 100 ppm working CO_2 carbonate standard into the phosphoric acid solution to get a reading of 100 ppm on the instrument. Repeat the injection to ensure reproducibility is within ± 10 ppm.

b. Repeat as above with approximately 100 µL (50 ppm) and 50 µL (25 ppm) .

Alternatively if an integrator is used, a 5 point calibration curve may be prepared by using the 100 ppm stock standard and plotting the absorbance counts of the prepared working standards versus concentration. The correlation coefficient shall be ≥ 0.995. Use this curve to determine the CO_2 concentration in the sample.

F.2.1.3 Sample analysis. Inject an appropriate amount of hydrazine sample into the phosphoric acid reaction flask to obtain a reproducible result within the standards range. Record the reading from the infrared analyzer scale or strip chart recorder (from the zero point). Perform the sample analysis in triplicates (verifying reproducibility) and use the average to determine the CO_2 concentration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

F.2.1.3.1 Calculation.

$$CO_2Wt\% = \frac{(Std\ conc_{(ppmw)})(Std\ vol_{(\mu L)})(Sample\ response)}{(Sample\ volume_{(\mu L)})(Std\ response)(1 \times 10^4)}$$

F.2.1.4 Reagents.

a. Purified water, CO_2 free - Prepare by boiling purified water vigorously for 15 minutes or by bubbling nitrogen through it for several hours.

b. Carbon Dioxide Stock Solution, 1000 ppm - Dissolve 2.4083 g ACS reagent grade sodium carbonate, dried for one hour at 100°C, in CO_2 free purified water in a 1 L volumetric flask; fill to the mark and mix thoroughly. Transfer 1 mL of this solution to a 10 mL volumetric flask, fill to the mark with CO_2 free purified water to prepare a 100 ppm standard. Prepare fresh daily.

c. Phosphoric Acid, 30% by volume - Dilute 355 mL of 85% H_3PO_4 to 1 L with purified water. Add enough indicator to this solution to readily determine when the acid solution is depleted.

d. Dry nitrogen gas supply.

e. Silica gel desiccant.

F.2.1.5 Equipment.

a. Non-dispersive infrared analyzer, Rosemount Analytical Model XStream-X2GP or equivalent.

b. Glass reaction tube with replaceable septum.

c. Glass drying tube.

d. Needle valve to control flow into reaction tube.


e. PTFE tubing.

f. Fittings to achieve air tight connections.

g. Operating fume hood.

h. Suitable data acquisition device.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.



A - Sparge gas inlet

B - Needle valve

C - Reactor and phosphoric acid solution

D - Septum inlet for propellant

E - Concentrated H_2SO_4 trap for removing H_2O

F - Infrared analyzer

G - Recorder

H - Magnetic stirrer

I - Plastic spill trays

FIGURE F-1. *CO_2 apparatus*

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

CARBONACEOUS MATERIAL

G.1 SCOPE

G.1.1 Scope. This Appendix describes the method for the determination of the carbonaceous material (other volatile carbonaceous material (OVCM) + other carbonaceous material (OCM)) content of the propellant. This Appendix is a mandatory part of the specification. The information contained herein is intended for compliance.

G.2 METHOD

G.2.1 Gas chromatographic method.

G.2.1.1 Procedure. A 60 m x 0.53 mm x 1.00 µm film thickness Stabilwax®-DB column, an FID equipped with a split injector, and an ultra-inert, deactivated, glass wool packed split liner shall be used. Table G-1 provides a list of the GC parameters for initial setup. These parameters may vary depending on GC system and detector brands, and may be adjusted to provide adequate component resolution.

TABLE G-1. *GC parameters*

PARAMETER	CONDITION
Injector Port Temp	175 °C
Injection Mode	Split injection
Sample Volume.	1 µL
Split Ratio	10:1
Carrier Gas	He
Control Flow	10 mL/min
Control Mode	Flow
FID Detector Temp.	210 °C
Equilibration Time	2.00 min
Initial Temp.(T_0)	60 °C
Initial Time (t_0)	3.00 min
Rate (1)	10 °C/min
Final Temp. (T_{f1})	100 °C
Final Time (t_{f1})	0.00 min
Rate (2)	20 °C/min
Final Temp. (T_{f2})	185 °C
Final Time (t_{f2})	3.75 min

The OVCM elution order is as follows:

UDMH < IPA < MMH < water < hydrazine < aniline

NOTE: Water and hydrazine co-elute.

G.2.1.2 Calibration. Prepare a standard stock solution, and a working standard of UDMH, IPA, and MMH in propellant as described in G.2.1.2.1 and G.2.1.2.2. Run a blank of pure N_2H_4 (high purity meeting this specification) and subtract the areas of UDMH, IPA, and MMH from the areas of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

standard. The signal to noise ratio shall be such that it allows for the effective quantitation of at least 5 ppmw MMH. If any of the contaminants are found in a propellant sample, analyze the standard and sample(s) in triplicate; the RSD ≤ 10%.

G.2.1.2.1 Standard stock solution.

1. Weigh a 40 mL volatile organic analysis type septa vial to the nearest 0.0001 g and tare.

2. Add 30 mL of pure N_2H_4 to the tared vial; cap and weigh to the nearest 0.0001 g.

3. Using a gas-tight glass syringe add approximately 190 µL UDMH to the vial and weigh to the nearest 0.0001 g. Subtract the weight of the pure hydrazine from the weight obtained to determine the weight of UDMH added.

4. Follow same procedure as above with the additions of 190 µL IPA and 170 µL MMH.

5. Mix solution thoroughly and store in the fuel hood under a gaseous nitrogen purge.

G.2.1.2.2 Working standard.

1. Weigh an autosampler vial with its uncrimped cap to the nearest 0.0001 g. Record the weight.

2. Add 1.5 mL of pure N_2H_4 to the vial, crimp, and weigh to the nearest 0.0001 g. The difference in weight before and after the addition is the amount of N_2H_4 added.

3. Shake the standard stock solution and inject enough into the vial to obtain a mid-range concentration based on the maximum allowed limits for high purity and monopropellant hydrazine and weigh to the nearest 0.0001 g. Subtract the weight of the pure N_2H_4 from the weight obtained to determine the weight of standard stock solution added.

G.2.1.3 Calculation. Calculate the concentration by weight of UDMH, IPA, and MMH separately using the following equations,

a. Standard stock solution:

$$Analyte\ ppmw = \frac{Wt_{Analyte} \times 10^6}{Wt_{Total}}$$

where,

$$Wt_{Total} = Wt_{N_2H_4} + Wt_{UDMH} + Wt_{IPA} + Wt_{MMH}$$

NOTE: If aniline is a component of the solution, the total weight (Wt_{Total}) shall include the weight of aniline ($Wt_{aniline}$) (see E.2.2.4).

b. Working standard:

$$Analyte\ ppmw = \frac{Analyte_{Stock\ Std\ Conc} \times Wt_{Analyte\ added}}{Wt_{Analyte\ added} + Wt_{N_2H_4}}$$

c. Sample calculation:

$$UDMH\ ppmw = \frac{UDMH_{Std\ Conc} \times A_s}{A_{UDMH} - A_s}$$

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

$$MMH\ ppmw = \frac{MMH_{\ Std\ Conc}\ \times\ A_s}{A_{MMH}\ -\ A_s}$$

$$IPA\ ppmw = \frac{IPA_{Std\ Conc}\ \times\ A_s}{A_{IPA}\ -\ A_s}$$

where,

A_{UDMH} = The area of the UDMH peak times its signal attenuation factor.

A_{MMH} = The area of the MMH peak times its signal attenuation factor.

A_{IPA} = The area of the IPA peak times its signal attenuation factor.

A_s = The area of the respective analyte in the sample times its signal attenuation factor.

Calculate OVCM in weight percent using following equation,

$$OVCM\ Wt\% = \ UDMH\ Wt\% + \ MMH\ Wt\% + \ IPA\ Wt\%$$

Calculate OCM in weight percent by addition of all impurities providing a positive FID response excluding OVCM and aniline. Calculate the content in the propellant sample based on the MMH factor as follows,

$$OCM\ wt\% = \left[\frac{MMH_{Std\ Conc}\ \times A_i}{A_{MMH}}\right] \times\ 10^{-4}$$

where,

$MMH_{Std\ Conc}$ = The MMH concentration used in the calibration, ppmw.

A_i = The average (based on triplicates) of the sum of all the peak areas excluding OVCM and aniline.

A_{MMH} = The average peak area obtained for the MMH standard.

Report the carbonaceous material content of the propellant as the sum of OVCM + OCM.

G.2.1.4 Reagents and equipment. The following reagents and equipment shall apply as test conditions of G.2.1.2.

G.2.1.4.1 Reagents.

a. N_2H_4 - High purity grade conforming to this specification.

b. UDMH - Conforming to MIL-PRF-25604.

c. MMH - Conforming to MIL-PRF-27404.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

d. IPA - ACS reagent grade.

G.2.1.4.2 Equipment.

(1) Gas chromatograph equipped with an FID and a split injector.

(2) Agilent ChemStation or equivalent.

(3) A 60 m x 0.53 mm ID and 1.00 µm film thickness Stabilwax®-DB column.

(4) Ultra-inert deactivated liner, split, straight, glass wool.

(5) No-bleed septa.

(6) Analytical balance calibrated to 0.0001 g.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians
Navy – AS
Air Force – 68
DLA – PS

Preparing Activity
Air Force – 68
(Project: 9135-2017-002)

Review Activities
Air Force - 19

Civil Agency
NASA - NA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T09:48Z
Check the source to verify that this is the current version before use.