MIL-C-46916C(AR)
18 November 1987
SUPERSEDING
MIL-C-46916B(PA)
5 September 1975

MILITARY SPECIFICATION

CAP, BLASTING, NON-ELECTRIC INERT

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for one type of Blasting Cap designated as Cap, Blasting, Non-Electric, Inert.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8864810	-	Cap, Blasting, Non-Electric, Inert.
2123915	-	Inner Package.
2128219	-	Package, Shipping and Storage (For 192 Cap, Blasting, Non-Electric).
3139687	-	Pack, Shipping and Storage (For 768 Cap, Blasting, Non-Electric).

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Blasting cap. The blasting cap shall comply with all requirements specified on Drawing (Dwg.) 8864810 and with all requirements specified in applicable specifications.

3.3 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First Article Inspection.

b. Quality Conformance Inspection.

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the folflowing items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantity
Metal Parts	8830949	50
Assembly	8864810	50

4.3.2 Inspections to be performed. See MIL-A-48078, paragraph 4.4.2 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:16Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-C-46916C(AR)

PARAGRAPH	TITLE: Cap, Blasting, Non-Electric, Inert		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Metal Parts Dwg. 8830949 Examination for Defects	50		3.2	4.4.2.1
	Assemblies Dwg. 8864810 Examination for Defects	50		3.2	4.4.2.2

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the classification of defects and test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46916C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Cup	1 OF 1	8830949
			NEXT HIGHER ASSEMBLY: 8864810

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length, min.		0.40%	3.2	Gage
102	Inside diameter, max.		0.40%	3.2	Gage
103	Outside diameter		0.40%	3.2	Gage
104	Thickness of base, min.		0.40%	3.2	Gage
105	Crack or split		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.00%	3.3	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-46916C(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Cap, Blasting, Non-Electric, Inert	1 OF 1	8864810
			NEXT HIGHER ASSEMBLY 8864810

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of holes		0.40%	3.2	Gage
102	Location of holes		0.40%	3.2	Gage
103	Inert filler incomplete or missing		0.40%	3.2	Visual
104	Cup damaged		0.40%	3.2	Visual
105	Protective finish incomplete or inadequate		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.00%	3.3	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 20261022107:162
Check the source to verify that this is the current version before use.

4.4.3 Testing. There is no testing applicable to this specification.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraphs (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.5 Test methods and procedures. There are no methods or procedures applicable to this specification.

5. PACKAGING

5.1 PRESERVATION - PACKAGING.

5.1.1 Level A for Navy/Marine Corps Use. Unit packaging shall be in accordance with Drawing 2113915.

5.1.2 Level B. The inert blasting cap shall be preserved and packaged in accordance with MIL-STD-1169 requirements.

5.2 Packing.

5.2.1 Level A for Navy/Marine Corps. Line sides and ends of metal box with corrugated fiberboard. Place a cushion on box bottom and insert the required quantity of blasting caps with desiccant and a cushion on top as shown on Drawing 2128219.

5.2.2 Level B. The inert blasting cap shall be preserved and packed in accordance with MIL-STD-1169 requirements.

5.3 Marking.

5.3.1 Level A for Navy/Marine Corps use. Marking shall be in accordance with MIL-STD-129 and Drawing 8796522.

5.3.2 Level B. Marking of the cartons shall comply with MIL-STD-1169 and MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Distribution of ammunition data cards, inspection and test results. Distribution of ammunition data cards, inspection, and test results shall include Commander, ARDEC, Picatinny Arsenal, NJ 07806-5000, ATTN: AMSMC-QAT-M (D).

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Subject term (key word) listing.
Blasting Cap
Non-Electric
Enert
Cup

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A283)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U S ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-46916C	CAP, BLASTING, NON-ELECTRIC INERT

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:16Z
Check the source to verify that this is the current version before use.