INCH-POUND

MIL-C-46920B (AR)
AMENDMENT 2
23 March 1993
SUPERSEDING
AMENDMENT 1
22 January 1982

MILITARY SPECIFICATION

CHARGE, EXPELLING, FOR CARTRIDGE ILLUMINATING, 4.2 INCH, M335A2

This amendment forms a part of MIL-C-46920B (AR), dated 24 August 1981, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1, Inspection Equipment Drawings: Delete "9221798 - Envelope Drawing for Leaking Testing".

PAGE 3

* 4.3.1, Delete entire line containing "8886592" and "9219239"; Delete "(if applicable" at line containing "9219984."

PAGE 4

* Table I, Delete "8886592, 9219239," Delete "(if applicable)," Add "/4.3.2" after "4.4.2.1" and "4.4.2.2."

PAGE 6

* 4.4.2.1, Minor 201, 202, 203, 204 and 205, Change "0.65%" to "4.5.3".

AMSC N/A FSC 1315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

PAGE 7

* 4.4.2.2, Delete line under "DRAWING NUMBER" and substitute "9219984." Change "886594" to "8886594".

Minor 201, Delete in its entirety and substitute "Diameter... 4.5.3...3.2...Functional Fit.

Minor 202, Delete in its entirety and substitute "Thickness of bottom ...4.5.3...3.2... Gage."

Delete Minor 203 and 204.

PAGE 8

* 4.4.2.3, Add "8886595" under "Next Higher Assembly"

AQL or 100% Column: Delete "0.25% and substitute "100%".

PAGE 10

4.5.2, Delete para. in it's entirety and substitute:

"4.5.2 Quick leak test. The expelling charge assembly shall be submersed in water at a depth of 1 inch, min. A vacuum of three inches, min. of mercury shall be created above the water and maintained for 20 seconds, min. Any expelling charge assembly which leaks as evidenced by emitting a stream of bubbles shall be classed defective and be removed from the lot."

* 4.5.3, Add new paragraph as follows:

"4.5.3 Dimensional control of molded and plastic parts. In place of the normal sampling and inspections associated with the Classification of Defects, and after a curing time has been established (see Note 1), ten (10) parts (as molded) from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity for use in production. The molded parts shall carry the individual cavity identification. As control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraph 4.4 after continuous production of each 5,000 parts or at the end of the week, whichever occurs first. Of the ten (10) samples, two (2) samples shall be the first two (2) parts produced and two (2) samples shall be the last two parts produced. If any defective parts are found during qualification

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

of the cavity, the cavity producing the defective part will not be used in production. Further, that portion of production since the last control check shall be inspected for each separate type of defect according to MIL-STD-105, Level II using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. All cavities removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

NOTE 1: In establishing a cure time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g, every 5, 10, etc. mins) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. If there is a change in material, or in the cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1315-AE54)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.