MILITARY SPECIFICATION

CHARGE, PROPELLING DUMMY, M3 FOR CARTRIDGE TRAINING: 105MM, M14

1. SCOPE

1.1 This specification covers one type of propelling charge for 105MM, M14 designated as the M3 Dummy Propelling Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons; General Specification for.

MIL-P-10025 — Packaging and Mark for Domestic Shipment of Inert Ammunition Components.

MIL-I-45208 — Inspection Requirements, General Specification for.

MIL-I-45607 — Inspection Equipment, Supply and Maintenance of.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 — Quality Assurance Terms and Definitions.

DRAWINGS

ORDNANCE CORPS

8865039 — Charge, Propelling, Dummy: 105MM, M3 for Cartridge Training: 105MM, M14.

8865041 — Increment Loading Assembly.

PUBLICATIONS

ORDNANCE CORPS

ORD-M608-11 — Procedures and Tables for Continuous Sampling by Attributes.

IEL-8872533 — Index of Inspection Equipment Lists

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials shall be in accord-

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

ance with applicable drawings and specifications.

3.2 Propelling charge. The charge shall comply with all requirements specified on Drawing (dwg.) 8865039 and with all requirements specified in applicable specifications.

3.3 Workmanship. The charges shall be free from dirt, grease, rust and other foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. The supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements. Reference shall be made to MIL–STD–109 in order to define terms used herein. The provisions of MIL–A–2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of MIL–I–45208.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted.

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

(b) Number of units of product inspected.

(c) Results obtained for all inspection performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

(e) Certificates of analysis on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with MIL–I–45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions.

4.2.1 *Lot formation.* A lot shall consist of charges produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government shall not necessitate changing the lot number.

4.2.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with MIL-STD-105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Handbook ORD-M608-11 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 1.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Body increment (see dwg. 8865040 covering a detail of 8865039).

Categories	*Defects*	*Method of inspection*	*Code No. (see 6.2)*
Critical: None defined			
Major: None defined			
Minor:	AQL 2.50 percent		
201.	Length	Gage	01001
202.	Width	Gage	01002
203.	Distance from edge to seam	Gage	01003
204.	Stitching missing or improper	Visual	01004
205.	Marking misleading or unidentifiable	Visual	01005
206.	Evidence of poor workmanship (see 3.3)	Visual	01006

4.2.2.2 Increment Loading Assembly (see dwg. 8865041).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Weight	Balance	02001
202.	Any seam or opening incompletely stitched	Visual	02002
203.	Twine missing or improperly assembled	Visual	02003
204.	Loop missing	Visual	02004

4.2.2.3 Charge Assembly (see dwg. 8865039).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 percent		
201.	Assembly damaged to the extent that filler can escape	Visual	03001
202.	Knot incorrect	Visual	03002
203.	Any component missing or improperly assembled	Visual	03003
204.	Evidence of poor workmanship (see 3.3)	Visual	03004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

4.2.4 *Inspection Equipment.* Index of Inspection Equipment Lists Number IEL–8872533 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance of the equipment listed on the IEL shall be in accordance with MIL–I–45607.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.

5.1.1 *Level C.* Packing and marking shall be in accordance with MIL–P–10025.

6. NOTES

6.1 Ordering data. Procurement documents shall specify the following:

(a) Title, number and date of this specification.

6.2 Inspection code numbers. The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment. The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 *Inspection equipment lists.* Inspection equipment lists (IEL) indicate the availability of inspection equipment design by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes indicating "commercial item" or "contractor design". Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.2 and 6.3.3. Action required by the contractor with respect to "commercial item" inspection equipment is described in paragraph 6.3.4. The contractor will be required to prepare drawings for all the equipment coded as "contractor design" in the number column. The code will further indicate whether detailed or specification control drawings are required. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Ordnance designs.* Ordnance designs are detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Ordnance design is listed for an item of inspection equipment. Ordnance designs fall into two basic classifications; mandatory and non-mandatory. When an IEL references mandatory Ordnance designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such contractor prepared designs must be approved by the Government prior

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.3 *Specification control drawings.* Specification control drawings depict the device in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare drawings of their designs in support of specification control drawings. The IEL code will indicate whether drawings must be detailed. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirement of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Commercial items.* Commercial item inspection equipment is equipment that has a universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial item inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.5 *IEL codes.* The inspection equipment referenced in paragraphs 6.3.1, 6.3.2, 6.3.3 and 6.3.4 will be designated in the IEL by the following codes:

CDOF — Contractor's design responsibility on Ordnance format; ORDM–608–12.

CDCF — Contractor design responsibility on contractor format

OD — Ordnance design.

ODMU — Ordnance design, mandatory for use.

CE — Commercial equipment.

SCD — Specification control drawing.

6.3.6 *Use of standard measuring equipment.* If the contractor desires to use standard measuring equipment in lieu of government or contractor designed gages, diagrammatic sketches or other descriptions of the use of such equipment shall be submitted for approval as specified in 6.3.7.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA–ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodian:
Army—MU
Project No. 1315—A299

Preparing activity:
Army—MU

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.