MIL-C-46923A (MU)
12 March 1969
SUPERSEDING
MIL-C-46923 (MU)
22 January 1963

MILITARY SPECIFICATION

CHARGE, PROPELLING, FOR 75MM HOWITZER M1A1 AND M3

1. SCOPE

1.1 This specification covers one type of Propelling Charge for use in 75MM Howitzer M1A1 and M3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-C-843 - Cushioning Material, Cellulosic

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8865404 - Charge Propelling for 75MM Howitzer M1A1 and M3, Assembly
9217087 - Marking Diagram and Sealing of Steel Drums for Shipment of Propellant and Bagged Charges

PUBLICATIONS

ARMY

ET-8865404 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Propelling Charge.-The propelling charge shall comply with all requirements specified on Drawing (dwg.) 8865404 and with all requirements specified in applicable specifications.

3.3 Propelling charge increment weight.-The weight of the propelling charge shall not differ by more than the following from that specified in the loading authorization.

INCREMENT NUMBER	TOLERANCE OUNCES plus or minus
1	0.01
2	0.01
3	0.01
4	0.01

3.4 Workmanship.-All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. All parts shall be free of dirt, grease, and other foreign material. All required marking shall be neat and sharply defined.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for Inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of propelling charges shall contain propellant from not more than one lot.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

4.2.2.1 Body increment 1, 2, 3, and 4 (see dwg 8865406 a detail of dwg. 8865404)

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None defined.			
Major: None defined.			
Minor:	AQL 1.50 percent		
201.	Any seam or opening incompletely stitched	Visual	01001
202.	Marking misleading or unidentifiable	Visual	01002
203.	Evidence of poor workmanship (see 3.4)	Visual	01003

4.2.2.2 Increment loading assembly 1, 2, 3 and 4 (see dwg. 8865405 a detail of dwg. 8865404)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Assembly damaged to the extent that propellant can escape	Visual	02001
Minor:	AQL 1.50 percent		
201.	Any seam or opening incompletely stitched	Visual	02002
202.	Thread broken	Visual	02003
203.	Evidence of poor workmanship	Visual	02004

4.2.2.3 Charge Assembly (see dwg. 8865404)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Assembly damaged to the extent that propellant can escape	Visual	03001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

102.	Any component missing, damaged or improperly assembled	Visual	03002
Minor:	AQL 1.50 percent		
201.	Length of twine between charges	Scale	03003
202.	Cord improperly assembled to the charges	Visual	03004
203.	Marking misleading or unidentifiable	Visual	03005
204.	Evidence of poor workmanship (see 3.4)	Visual	03006

4.2.2.4 Drum sealed (see dwg. 9217087)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Gasket missing or improperly positioned	Visual	04001
102.	Locking ring improperly positioned	Visual	04002
Minor:	AQL 1.00 percent		
201.	Car seal missing or improperly positioned	Visual	04003
202.	Marking misleading or unidentifiable	Visual	04004

4.2.2.6 Fiber container (see dwg. 9217087)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

Major:	AQL 1.0 percent		
101.	Gasket missing or incomplete	Visual	05001
102.	Locking device damaged or improperly closed	Visual	05002
103.	Holes or breaks in cover or body	Visual	05003
104.	Damage to coating or cover .	Visual	05004
105.	Foreign matter or corrosion in interior	Visual	05005
Minor:	AQL 1.0 percent		
201.	Marking missing, misleading or unidentifiable	Visual	05006
202.	Interior or exterior torn or delaminated	Visual	05007

4.2.3 Testing

4.2.3.1 Propelling charge increment weight (see 3.3) - Major defect.-The increment shall be weighed and check-weighed 100 percent. The check weighing shall be accomplished independently of the original weighing using a different balance from that used for the original weighing and if performed manually, it shall be performed by another operator. Any increment which fails to comply with the applicable requirements shall be classified defective and removed from the lot. Inspection equipment shall be in accordance with 4.2.4.

CHARGE	CODE NO.
1	07001
2	07002
3	07003
4	07004

4.2.4 Inspection Equipment - Equipment Tabulation Number ET-8865404 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection equipment. The contractor shall make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment and verification of its accuracy shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 Level C.-The charges shall be packed in a fiber drum certified in accordance with ICC Specification 21C and meeting the following requirements. Size shall be 15-1/2 ± 1/2 inches in diameter by 26 ± 1 inches deep. A layer of aluminum foil shall be laminated into the body and the bottom if it is made of fiberboard. The bottom shall be either steel or asphalt laminated fiberboard. The bottom and top edge of the drum shall have 24 gauge welded galvanized steel chimes. The cover shall be either plain or interlocking (with bottom) design lever lock type with gasket and shall provide a moisture-proof seal. The cover shall be made with either a galvanized finish or a baked on varnish finish resistant to chipping, peeling and cracking. The drum shall be tested in accordance with ICC Specification 21C except the drum shall be filled with not less than 250 pounds of dry sand for the drop test. The exterior of the drum shall be coated with a water resistant material.

5.2 Marking.-Marking shall be in accordance with dwg. 9217087.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

6.4 Submission of ballistic test data and ammunition data cards.-In addition to the normal distribution of records, for loaded items procured by the Department of the Army, one copy of all ballistic test data and ammunition data cards shall be forwarded to the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-ND7 and DC
Dover, New Jersey 07801

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1315-A-671

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

MIL-C-46923A (MU)

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:17Z
Check the source to verify that this is the current version before use.