MILITARY SPECIFICATION
CARTRIDGE, 7.62MM, NATO, MATCH, M118

This amendment forms a part of Military Specification MIL-C-46934B(MU), 29 June 1965.

Paragraph 3.2, Delete and substitute:

"3.2 First article sample.- Requirements for the submission of first article samples by the contractor shall be as specified in the contract."

Paragraph 4.2, Delete and substitute:

"4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 400 cartridges. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and Test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval."

Paragraph 4.3.2.1; Under Table 1; Defect No. 47: Change classification of defect from "Major X" to "Critical X".

Footnote 2/, Delete and substitute:

"2/ Each light weight cartridge shall be disassembled and the propellant weighed. Each such cartridge found to contain 25 grains or more of propellant shall be classed as a major defect. Any cartridge containing less than 25 grains of propellant shall be classed as a critical defect."

Paragraph 4.4.9: Last sentence, delete the words "average of the".

Custodian:

Army - MU

Preparing activity:

Army - MU

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:20Z
Check the source to verify that this is the current version before use.

Project No. 1305-A479