INCH-POUND

MIL-C-46933A(AR)
AMENDMENT 7
30 January 1992

SUPERSEDING
AMENDMENT 6
28 March 1991

MILITARY SPECIFICATION

* CARTRIDGE, 7.62MM, NATO, BLANK, M82

This Amendment forms a part of Military Specification MIL-C-46933A(MU), dated 22 April 1966, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505 Volume 3" wherever it appears in the specification and substitute "SCATP-7.62".

PAGES 1 and 2

2.1 Add to STANDARDS: MIL-STD-1168 - Lot Numbering of Ammunition"

2.1 In Paragraph 2.1 and under Drawings, delete the following drawings and their titles:

"F8594726 and F10523070"

and substitute the following:

"F9362605 - Packing and Marking, 7.62mm, NATO, Blank, M82; Links; Box, Ammunition, M19A1; Wirebound Box

F9362607 - Packing and Marking for Box, Wirebound for Cartridge, 7.62mm"

PAGE 2

3.7: Add the phrase "when conditioned for not less than 2 hours at 68°F to 72°F (room temperature)" to the end of the paragraph.

3.8 Delete this paragraph entirely and substitute:

"3.8 Cyclic rate. The cartridge shall operate the M60 Machine Gun at a cyclic rate of not less than 450 cartridges per minute, the M14 Rifle at a cyclic rate of not less than 600 cartridges per minute and the M240 Machine Gun at a cyclic rate of not less than 650 cartridges per minute utilizing gas port setting No. 1."



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.

3.10 Add section 3.10 as follows:

"3.10 Waterproof. The blank cartridge shall not release more than one bubble of air when subjected to a pressure of 2 pounds per square inch (psi) below atmospheric pressure and held at that pressure for 15 seconds."

4.2.1 Delete "3000" and substitute "3600".

4.3.1.2 Delete this paragraph entirely and substitute:

"4.3.1.2 Lot identification. Each lot of ammunition shall be identified as to type, caliber and model as well as with a lot number assigned in accordance with MIL-STD-1168."

PAGE 4

4.3.2.1 In Table I, make the following changes:

Delete "39 Missing or Loose wad." and substitute "39 Incorrect 5-petal crimp".

Delete "40 Wad and joint between neck and wad not completely covered by lacquer" and substitute "40 Crimp not covered by lacquer."

Delete characteristics "41, 43 and 44" in their entirety.

PAGE 5

* 4.3.3.1 Delete the last sentence in this paragraph and substitue the following:

"With the exception of the samples for waterproof test, the cartridges selected shall be thoroughly mixed before being subdivided into samples for the various tests. The samples for waterproof test shall be selected after the packing operation."

4.3.3.1 Table II, delete

"Fouling 3/ 500 3.6"

and substitute

"Fouling 3/ 6/ 3.6



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.

4.3.3.1 Table II under Function and Casualty, add:

"Gun, Machine, 7.62mm, M240 400"

4.3.3.1 Add the following to Table II

"Waterproof 7/ 20 3.10"

4.3.3.1 Table II delete note 4 entirely and substitute the following:

"4/ The initial production sample shall be rejected when firing defects observed during the function and casualty and all other firing tests (including fouling tests) exceed the acceptance number for the first sample in Table III; no second sample shall be permitted. A production lot shall be rejected when firing defects observed during the function and casualty and all other firing tests exceed the acceptance number for the cumulative sample in Table III. If the number of defects found in the first tests exceeds the acceptance number for the first sample but is equal to or less than the acceptance number for the cumulative sample, a second sample consisting of double the quantity specified under function and casualty test shall be fired in the service weapons specified. This procedure shall apply regardless of the weapon or weapons in which the firing defects occurred in the first tests. If the total number of defects in the combined first and second sample exceeds the acceptance number for the cumulative sample, the lot shall be rejected. If in testing a second sample, defects other than those for which the second sample is being tested should occur to the extent that they exceed the acceptance number for the cumulative sample, the lot shall be rejected."

4.3.3.1 Table II add the following to Note 5:

"The function and casualty test shall be complete prior to any retest associated with failure to meet the cyclic rate requirement. Firings defects observed during a retest of the weapon type(s) solely for cyclic rate shall not exceed the first sample acceptance numbers in Table III."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.

4.3.3.1 Table II:

Add the following notes to Table II as follows:

"6/ Five-hundred (500) rounds shall be fired through both M60 and M240 machine gun without cleaning. The initial 200 rounds on each machine gun shall be fired concurrently with the function and casualty test. An additional 300 rounds shall be fired through one each of the M60 and M240 machine guns from the function and casualty test to fulfill the 500 rounds fouling test requirement.

7/ Failure of nine or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If more than four, but less than nine cartridges fail in the first test, a second sample consisting of double the number of cartridges in the first sample shall be tested. The lot shall be rejected if, in the combined first sample and second sample, nine or more cartridges fail to comply with the applicable requirement.

PAGES 6 and 7

4.3.3.2 Delete Table III entirely and substitute the following:

"TABLE III

| Defects | Acceptance Numbers First sample | Acceptance Numbers Cumulative First & Second Sample) |
|---|---|---|
| 1. Primer | | |
| a. Escape of gas through or around primer cup | 17 | 47 |
| b. Blown primer or primer falls out of pocket on retraction of bolt | 0 | 1 |
| 2. Case | | |
| Splits, neck, shoulder or mouth (mouth splits in excess of 0.50 inch) | 17 | 47 |
| Expansion, mouth or neck 3/ | 6 | 15 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.

| | | |
|---|---|---|
| Splits, body | 6 | 15 |
| Splits, through head | 1 | 3 |
| Complete rupture | 0 | 1 |
| Partial rupture | 6 | 15 |
| Detached metal 1/ | 0 | 1 |
| 3. Weapon Stoppage 2/ | 17 | 47 |
| 4. Misfire | 4 | 12" |

Add defect number 5 to Table III as follows:

| | | |
|---|---|---|
| "5. Hangfire 4/ | 0 | -" |

Add the following footnotes to Table III as follows:

3/ Any visual rifling impression or imprint on the case mouth or neck resulting from expansion against the rifling grooves shall be classified as a defect."

4/ For the definition of a hangfire, see SCATP-7.62 paragraph 10.6.2."

PAGE 7

4.3.4 In this paragraph, delete the second sentence "Occurrence of another model blank cartridge or a dummy cartridge shall be classed as a major defect". and substitute "Occurrence of another type blank cartridge (i.e., wad crimped cartridge) or a dummy cartridge shall be classed as a major defect".

PAGE 8

4.4.4 Delete the first sentence entirely and substitute:

"The cartridge shall be fired in bursts of 50 cartridges and 20 cartridges in machine gun and rifle respectively. After firing of 100 cartridges, the weapon shall be cooled to ambient temperature."

4.4.5 Delete in the second sentence "Two machine guns" and substitute "Two M60 machine guns, two M240 machine guns".

4.4.5a Delete section a. completely and substitute "a. The machine guns shall be fired in burst of 50 rounds from a mount with a solenoid."



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.

4.4.8 Add section 4.4.8 as follows:

4.4.8 Waterproof. The test shall be conducted in accordance with SCATP-7.62. The container shall be evacuated to a pressure of 2 pounds per square inch (psi) below atmospheric pressure and held at that pressure for 15 seconds."

PAGES 8 and 9

5. Delete paragraph 5 in its entirety and substitute the following:

"5. PREPARATION FOR DELIVERY

5.1 Preservation and packing.

5.1.1 Packing, Level A. The cartridges shall be packed in accordance with drawings 9362607 or 10521861 as appropriate.

5.1.2 Marking. Markings shall be in accordance with Dwgs 9362607 or 10521861 as appropriate.

5.2 Shipping. When cartridges from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit."

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections or deletions) from the previous amendment were made. This was done as a convenience only and the government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army-AR

Preparing activity
Army-AR

(Project 1305-AE05)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:19Z
Check the source to verify that this is the current version before use.