MIL-O-46910C (AR)
3 April 1981
SUPERSEDING
MIL-O-46910B (MU)
21 August 1967

MILITARY SPECIFICATION

OBTURATING MECHANISM PARTS FOR

This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts and packing of one type of obturating mechanism for the 4.2 Inch Mortar.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals, form a part of this specificaion to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedure Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

DRAWINGS (see 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

8863660 - Obturating Mechanism

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing (dwg.) 8863660 and associated drawings and with all requirements specified on applicable specifications and standards.

3.3 Workmanship. The parts and assemblies shall be free from burrs, chips, dirt, grease and other foreign matter. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. Quality conformance inspection shall be conducted on this item.

4.3 First article inspection. Not required

4.4 Quality conformance inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Point, Striker				8835181
					NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length from shoulder to point		0.40%	3.2	Gage
Minor					
201	Total length, min.		0.65%	3.2	Gage
202	Large outside diameter		0.65%	3.2	Gage
203	Diameter of shank		0.65%	3.2	Gage
204	Length of large outside diameter		0.65%	3.2	Gage
205	Radius missing		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8835180
4.4.2.2	Plate, Striker				NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness of plate		0.65%	3.2	Gage
202	Width of tab		0.65%	3.2	Gage
203	Diameter of hole in tab		0.65%	3.2	Gage
204	Diameter of plate		0.65%	3.2	Gage
205	Length of tab hole		0.65%	3.2	Gage
206	Radius of tab		0.65%	3.2	Gage
207	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.3	Nut Striker				8863663
					NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of small thread		0.40%	3.2	Gage
102	Minor diameter of small thread, max.		0.40%	3.2	Gage
103	Pitch diameter of large thread		0.40%	3.2	Gage
104	Minor diameter of large thread, max.		0.40%	3.2	Gage
Minor					
201	Concentricity of large thread pitch diameter with small thread pitch diameter		0.65%	3.2	Gage
202	Perpendicularity of small thread end face with small thread pitch diameter		0.65%	3.2	Gage
203	Perpendicularity of large thread end face with large thread pitch diameter		0.65%	3.2	Gage
204	Concentricity of counterbore with small thread pitch diameter		0.65%	3.2	Gage
205	Concentricity of outside diameter with small thread pitch diameter		0.65%	3.2	Gage
206	Outside diameter		0.65%	3.2	Gage
207	Inside diameter of small thread end, min. (above and below thread)		0.65%	3.2	Gage
208	Depth to thread from small thread end face		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.3	Nut Striker	2 OF 2	8863663
			NEXT HIGHER ASSEMBLY 8863660

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
209	Diameter of thru hole		0.65%	3.2	Gage
210	Diameter of counterbore		0.65%	3.2	Gage
211	Depth to bottom of counterbore from large thread end face		0.65%	3.2	Gage
212	Depth to shoulder above counterbore from small thread end face		0.65%	3.2	Gage
213	Total length		0.65%	3.2	Gage
214	Length to small thread from shoulder above counterbore		0.65%	3.2	Gage
215	Length of full large thread, min.		0.65%	3.2	Gage
216	Chamfer or radius missing		0.65%	3.2	Visual
217	Finish improper		0.65%	3.2	Visual
218	Protective finish inadequate		0.65%	3.2	Visual
219	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Striker Nut Assembly	1 OF 1	8863662
			NEXT HIGHER ASSEMBLY: 8863660

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Striker point extends thru striker plate		100%	3.2	Gage
102	Length to furthest point of tab from plate		0.40%	3.2	Gage
Minor					
201	Striker point insecurely riveted		0.65%	3.2	Visual/Manual
202	Striker plate inadequately crimped		0.65%	3.2	Visual/Manual
203	Crimp not lacquered		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8835188
4.4.2.5	Plate, Pressure				NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Back face painted with red ink		100%	3.2	Visual
102	Front face not painted with red ink		100%	3.2	Visual
103	Outside diameter		0.40%	3.2	Gage
104	Concentricity of hole with outside diameter		0.40%	3.2	Gage
105	Angle of taper		0.40%	3.2	Gage
106	Length of taper		0.40%	3.2	Gage
107	Thickness		0.40%	3.2	Gage
108	Diameter of hole		0.40%	3.2	Gage
Minor					
201	Finish improper		0.65%	3.2	Visual
202	Radius missing or improper		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Nut, Pressure Plate				8835186
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of faces to pitch diameter of thread		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Outside diameter		0.65%	3.2	Gage
203	Pitch diameter		0.65%	3.2	Gage
204	Minor diameter, max.		0.65%	3.2	Visual
205	Knurl missing or improper		0.65%	3.2	Visual
206	Chamfer missing or improper		0.65%	3.2	Visual
207	Finish improper		0.65%	3.3	Visual
208	Evidence of poor workmanship				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8835189
4.4.2.7	Disc, Rotating				NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Hardness of outer circumference		0.40%	3.2	Test
102	Outside diameter		0.40%	3.2	Gage
103	Concentricity of outside diameter with hole		0.40%	3.2	Gage
104	Depth of slot		0.40%	3.2	Gage
105	Symmetry of slot with hole		0.40%	3.2	Gage
106	Width of slot		0.40%	3.2	Gage
107	Diameter of thru hole at hub side		0.40%	3.2	Gage
Minor					
201	Diameter of thru hole at counter-bore side		0.65%	3.2	Gage
202	Total height		0.65%	3.2	Gage
203	Hub diameter		0.65%	3.2	Gage
204	Depth of taper		0.65%	3.2	Gage
205	Angle of taper		0.65%	3.2	Gage
206	Large inside diameter		0.65%	3.2	Gage
207	Finish improper		0.65%	3.2	Gage
208	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.8	Container, Cartridge				8835185
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cartridge container does not accept ring gage for entire length		0.40%	3.2	Gage
102	Pitch diameter of internal thread		0.40%	3.2	Gage
103	Minor diameter of internal thread, max.		0.40%	3.2	Gage
104	Pitch diameter of small external thread		0.40%	3.2	Gage
105	Major diameter of small external thread, min.		0.40%	3.2	Gage
106	Pitch diameter of large external thread		0.40%	3.2	Gage
107	Major diameter of large external thread, min.		0.40%	3.2	Gage
108	Concentricity of pitch diameter of small external thread with pitch diameter of internal thread and perpendicularity to front and rear shoulders		0.40%	3.2	Gage
109	Length of small external thread, min.		0.40%	3.2	Gage
110	Lenth of internal thread, min.		0.40%	3.2	Gage
111	Concentricity corner forward end with pitch diameter of internal thread		0.40%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.8	Container, Cartridge				8835185
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
112	Concentricity outside diameter forward of large external thread with pitch diameter of internal thread		0.40%	3.2	Gage
113	Outside diameter forward of large external thread		0.40%	3.2	Gage
114	Diameter forward of external thread for length		0.40%	3.2	Gage
115	Burrs in cavity		0.40%	3.2	Visual
Minor					
201	Outside diameter small end		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Total length		0.65%	3.2	Gage
204	Width of slot		0.65%	3.2	Gage
205	Diameter of slot		0.65%	3.2	Gage
206	Length from small end face to shoulder		0.65%	3.2	Gage
207	Length from large end face to shoulder		0.65%	3.2	Gage
208	Diameter of flash holes		0.65%	3.2	Gage
209	Length of large external thread, min.		0.65%	3.2	Gage
210	Diameter of corner forward end		0.65%	3.2	Gage
211	Finish improper		0.65%	3.2	Visual
212	Protective finish improper or incomplete		0.65%	3.2	Visual
213	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Holder, Propellant				8835182
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Opening between loops		0.65%	3.2	Gage
202	Protective finish improper or incomplete		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Pin		9204359
			NEXT HIGHER ASSEMBLY 8863660

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Total length		100%	3.2	Gage
102	Diameter of shaft		0.40%	3.2	Gage
Minor					
201	Perpendicularity of flange with shaft		0.65%	3.2	Gage
202	Thickness of flange		0.65%	3.2	Gage
203	Diameter of flange		0.65%	3.2	Gage
204	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Support, Pin				9204360
					NEXT HIGHER ASSEMBLY
					8663660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Symmetry of hole with diameter and flats		0.40%	3.2	Gage
102	Perpendicularity of hole with face		0.40%	3.2	Gage
103	Diameter of hole		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Diameter, min.		0.65%	3.2	Gage
203	Chamfer missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.12	Extension Assembly				9204361
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread, min.		0.40%	3.2	Gage
103	Concentricity of small counterbore, knurl end with pitch diameter of thread		0.40%	3.2	Gage
104	Concentricity of counterbore, thread end, with pitch diameter of thread		0.40%	3.2	Gage
Minor					
201	Width of slot		0.65%	3.2	Gage
202	Diameter of slot		0.65%	3.2	Gage
203	Length of knurl		0.65%	3.2	Gage
204	Diameter of small counterbore, knurl end, max.		0.65%	3.2	Gage
205	Diameter of counterbore, thread end, max.		0.65%	3.2	Gage
206	Overall length		0.65%	3.2	Gage
207	Outside diameter		0.65%	3.2	Gage
208	Concentricity of outside diameter with pitch diameter of thread		0.65%	3.2	Gage
209	Depth to bottom of small counterbore, knurl end		0.65%	3.2	Gage

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9204361
4.4.2.12	Extension Assembly				NEXT HIGHER ASSEMBLY 8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
210	Depth of counterbore, thread end		0.65%	3.2	Gage
211	Depth of small counterbore, knurl end		0.65%	3.2	Gage
212	Length to shoulder, thread end		0.65%	3.2	Gage
213	Nylon fastener missing		0.65%	3.2	Visual
214	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T07:15Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-O-46910C (AR)

PARAGRAPH	TITLE		SHEET		DRAWING NUMBER
4.4.2.13	Extension Parts Arrangement		1 OF 1		9204362
					NEXT HIGHER ASSEMBLY
					8863660
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Support, pin load test*		0.40%	3.2	Test
102	Support, pin thread end stake missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.3	Visual

NOTES:

* Samples shall not be returned to the lot.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.4.5 Methods of inspection. Not required.

5. PACKAGING

5.1 Packaging and marking. Packaging and marking shall be in accordance with MIL-STD-1169 and the following additional instructions:

Disc, rotating. One hundred discs shall be packed five per layer in a fiber box complete with plain paperboard pads and die-cut fiberboard pads. The paperboard pad shall consist of plain chipboard .040 inch thick, minimum. The die cut fiberboard pad, shall consist of a sheet of A or B flute double-faced fiberboard having a bursting strength of 200 psi. or better, with 5 die cut holes arranged in a 2 by 2 pattern with one hole centered between the rows. Holes shall be 4 1/8 + 1/32 inches in diameter and shall be centered approximately 2 7/16 inches from all edges of the fiberboard pad and 4 1/2 inches (center to center) from each other. A plain paperboard pad shall be placed on the bottom of the box, between each die-cut pad and on top of the contents. Additional paperboard pads shall be added as required for a tight pack. Die-cut pads may be spot-glued to paperboard pad at contractor's option. Pad size shall be approximately 12 3/8 x 9 1/2 inches.

6. NOTES

6.1 Intended use. The obturating mechanism covered by this specification is intended for use in the 4.2 Inch Mortar.

6.2 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T07:15Z
Check the source to verify that this is the currentversion before use.

6.3 Submission of inspection equipment for design approval. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Drawings. Drawings listed in Section II of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A355

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T07:15Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-O-46910C OBTURATING MECHANISM PARTS FOR

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T07:15Z
Check the source to verify that this is the currentversion before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T07:15Z
Check the source to verify that this is the currentversion before use.