NOT MEASUREMENT SENSITIVE

MIL-DTL-3628/138
15 November 1996
SUPERSEDING
MIL-B-41809/41B
21 September 1994

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, POLICE, CAP, DEFENSE PROTECTIVE SERVICE, DEPARTMENT OF DEFENSE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Gilding Metal

DIMENSIONS:
HEIGHT (Overall) 3 inches (7.62 cm) (REF)
WIDTH (Overall): 2 inches (5.08 cm) (REF)
THICKNESS (At "POLICE" Lettering): 0.085 inch ± 0.010 inch (0.215 cm ± 0.025 cm)

FINISH: Hard Enameled, Soft Baked Enameled, Gold Plated, Matte Finish, Highlights Polished and shall match TIOH Metal Finish Chip Number 8.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:45Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A full forcer shall be used to bring up the details of the design.

3. Piercing shall be as indicated.

4. The attaching device shall be a screw post and thumb nut with two registering prongs.

a. The screw post shall be located on the vertical center line of the badge 1-3/4 inch ± 1/64 inch (4.45 cm ± 0.04 cm) from the bottom of the badge.

b. The registration prongs shall be located a horizontal line 1/8 inch ± 1/64 inch (0.32 cm ± 0.04 cm) in from the widest portion of the top of the shield on each side.

c. The screw post shall be 9/16 inch ± 1/32 inch (1.43 cm ± 0.08 cm) long and 0.125 inch ± 0.10 inch (0.32 cm ± 0.025 cm) in diameter and shall have a NO 5-4 OUNC-2A thread.

d. The thumb nut shall be 0.625 inch ± 0.010 inch (1.59 cm ± 0.25 cm) in diameter and shall have a NO 5-4 OUNC-2B thread.

e. The registration prongs shall be 1/4 inch ± 1/64 inch (0.64 cm ± 0.04 cm) in length and 0.045 inch ± 0.002 inch (0.114 cm ± 0.005 cm) in diameter.

5. Enamel color shall be as indicated. The enamel color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Green	12
Black	26
Blue	33

6. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel and soft baked enamel at the option of the manufacturer. When epoxy resin is used in lieu of soft baked enamel, the epoxy resin shall not be stoned.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45
Navy - NU

Review activities:
Air Force - 32, 82, 99
Navy - MC
Coast Guard - CG
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0866)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:45Z
Check the source to verify that this is the current version before use.