INCH-POUND

MIL-DTL-3628/138C
20 May 2019
SUPERSEDING
MIL-DTL-3628/138B
22 July 2014

DETAIL SPECIFICATION SHEET

BADGE, IDENTIFICATION, POLICE, CAP, DEFENSE PROTECTIVE SERVICE, OFFICE OF THE SECRETARY OF DEFENSE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3628.



MATERIAL: Red Brass 85/15 (UNS Alloy C-230)

FINISH: Epoxy resin (Stoning epoxy), Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Standard Metal Finish Chip Number 6.

DIMENSIONS:
HEIGHT (overall): 3 inches (REF)
WIDTH (overall): 2 inches (REF)
THICKNESS (at "POLICE" lettering): 0.085 inch ± 0.010 inch

ATTACHING DEVICE:
1. The attaching device shall be a screw post and thumb nut with two registering prongs.

2. The screw post shall be located on the vertical center line of the badge 1-3/4 inch ± 1/64 inch from the bottom of the badge.

3. The registration prongs shall be located on a horizontal line 1/8 inch ± 1/64 inch in from the widest portion of the top of the shield on each side.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:45Z
Check the source to verify that this is the current version before use.

4. The screw post shall be 9/16 inch ± 1/32 inch long and 0.125 inch ± 0.10 inch in diameter and shall have a NO. 5-4 OUNC-2A thread.

5. The thumb nut shall be 0.625 inch ± 0.010 inch in diameter and shall have a NO. 5-4 OUNC-2B thread.

6. The registration prongs shall be 1/4 inch ± 1/64 inch in length and 0.045 inch ± 0.002 inch in diameter.

EPOXY: Epoxy resin shall not be stoned. Both hard enamel and soft baked enamel may be used at the option of the manufacturer in lieu of epoxy resin. If hard enamel and soft baked enamel are used then the material will be Gilding Metal 95/5 (UNS Alloy C-210). Epoxy and enamel colors shall conform to TIOH Hard Enamel Chip Numbers listed below:

COLOR	CHIP NUMBER
Green	12
Black	26
Blue	33

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die. TIOH Drawing Number B-16-10 may be used as additional reference.

2. A full forcer shall be used to bring up the details of the design.

3. Piercing shall be as indicated.

4. Both hard enamel and soft baked enamel may be used at the option of the manufacturer in lieu of epoxy resin. If hard enamel and soft baked enamel are used then the material will be Gilding Metal 95/5 (UNS Alloy C-210). Epoxy and enamel colors shall conform to TIOH Hard Enamel Chip Numbers listed below:

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2019-221)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:45Z
Check the source to verify that this is the current version before use.