NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/140C
01 May 2024
SUPERSEDING
MIL-DTL-3628/140B
1 July 2019

DETAIL SPECIFICATION SHEET


BADGE, IDENTIFICATION, AND INSIGNIA, SERVICE CAP, CIVILIAN POLICE AND CIVILIAN GUARD, DEPARTMENT OF DEFENSE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



-1, -2, -3, -4



-5, -6

DASH NO.
- -1: Identification (Non-Supervisory)
- -2: Service Cap (Non-Supervisory)
- -3: Identification (Supervisory)
- -4: Service Cap (Supervisory)
- -5: Identification (Civilian Guard)
- -6: Service Cap (Civilian Guard)

MATERIAL:
-1, -2, -5, -6: Red Brass 85/15 (UNS Alloy No. C-230) or Nickel Silver (UNS Alloy No.C-752)
-3, -4: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1, -2, -5, -6:
LETTERING, RIM, BAND OF SHIELD AND SCROLL: Nickel Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Chip Number 16.
EAGLE: Nickel Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 18.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:46Z
Check the source to verify that this is the current version before use.

PEBBLED BACKGROUND OF SHIELD AND PEBBLED AREA BEHIND EAGLE AND SROLL: Nickel Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 17.

-3, -4:

LETTERING, RIM, BAND OF SHIELD AND SCROLL: 24k Gold Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

EAGLE: 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

PEBBLED BACKGROUND OF THE SHIELD AND PEBBLED AREA BEHIND EAGLE AND SCROLL: 24k Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DIMENSIONS:

HEIGHT (Overall): 2-7/16 inches (REF)
WIDTH (Overall): 1-5/8 inches (REF)
THICKNESS (At lowest edge): 0.065 inch $\pm$ 0.010 inch

ATTACHING DEVICE:

1. The attaching device for -1, -3 and -5 shall be a coil pin type with heavy duty side opening catch. The pin stem shall be 1-3/4 inches $\pm$ 1/64 inch long. The pin and catch shall be hard soldered or fused on the vertical center line with the joint located 11/16 inch $\pm$ 1/64 inch down from the top of the badge.

2. The attaching device for -2, -4 and -6 shall be a screw post and thumb nut with one registering prong. The screw post shall be hard soldered or fused on the vertical center line 1 inch $\pm$ 1/32 inch from the top of the badge. The registration prong shall be located on the vertical center line 1/4 inch $\pm$ 1/32 inch down from the top of the badge.

a. The screw post shall be 1/2 inch $\pm$ 1/32 inch long and 0.125 inch $\pm$ 0.10 inch in diameter and shall have a NO 5-4 OUNC-2A thread.

b. The thumb nut shall be 0.625 inch $\pm$ 0.010 inch in diameter and shall have a NO 5-4 OUNC-2B thread.

c. The registration prong shall be 1/4 inch $\pm$ 1/64 in length and 0.045 inch $\pm$ 0.002 inch in diameter.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. A mock forcer may be used to bring up the areas of the shield and eagle.

3. -1, -2, -5 and -6 may be rhodium plated with the lettering, rim, scroll and band of shield having a mirror-like polish.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:46Z
Check the source to verify that this is the current version before use.

Custodians:
Army - IH
Air Force - 11
Navy - NU

Preparing activity:
Army - IH

Review activities:
Navy - CG1
DLA - CT

(Project No. 8455-2024-129)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:46Z
Check the source to verify that this is the current version before use.