INCH-POUND

FF-B-2844/07
15 FEBRUARY 1994

FEDERAL SPECIFICATION SHEET

BEARING, BALL, ANNULAR: SINGLE ROW, RADIAL, NON-FILLING SLOT, LIGHT SERIES (LS - SERIES) (CHROMIUM ALLOY STEEL)

The General Services Administration has authorized the use of this specification by all Federal Agencies.

The complete requirements for procuring the bearings described herein shall consist of this document and the latest issue of FF-B-2844 GEN.




FIGURE 1.
OPEN(NO SHIELDS OR SEALS)




FIGURE 2.
SINGLE SHIELD




FIGURE 3.
DOUBLE SHIELD




FIGURE 4.
SINGLE SEAL




FIGURE 5.
DOUBLE SEAL




FIGURE 6.
SINGLE SHIELD AND SEAL

BEARING CONFIGURATIONS

AMSC/NA

FSC 3110

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 20260-26111:47Z
Check the source to verify that this is the current version before use.

REQUIREMENTS

1. Boundary dimensions. The boundary dimensions shall be specified in the part number by the bore codes in Table I.

2. MATERIAL

2.1 Rings and balls. The rings and balls of bearings covered by this specification shall be made of chromium-alloy steel 52100 (UNS 52986).

2.2 Closures. The shields and seals shall be fabricated from any material unless otherwise specified and shall be removable or non-removable type. Seals shall be impervious contact type. The number of shields and seals required shall be specified in the part number by using the codes listed in Table IV.

2.3 Cage material. Cages shall be manufactured from any material unless otherwise specified. The type of cage required shall be specified in the part number by using the codes listed in Table II.

3. METROLOGY

3.1 Radial internal clearance. The tolerance limits for radial internal clearance are specified in ANSI/AFBMA STD-20 and shall be specified in the part number by using the code listed in Table III.


3.2 Tolerance class. The tolerance limits for tolerance class ABEC-1, and ABEC 5, shall be in accordance with ANSI/AFBMA STD 20 and shall be specified in the part number by using the codes listed in Table III.

4. Lubricant or preservative compound. The lubricant or preservative compound shall be specified in the part number by using the codes listed in Table IV. Preservative compound shall be applied to all open bearings (no shields or seals) and to single closure bearings (single shield or single seal) that have no additional lubricant requirement. Thus, for these bearings, the bearing part number shall include the "C", "F" or "L" suffix from Table IV. For double closure or single closure bearings that require lubricant, the bearing part number shall include the preferred suffix from Table IV as required. When grease is required, the bearing void (the airspace between the inner and outer ring of the assembled bearing) shall be 25% to 50% filled for non-instrument size bearings and 25% to 40% filled for instrument size bearings.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:47Z
Check the source to verify that this is the current version before use.

5. Part number. The part number consists of the Federal Specification prefix letters FFB, the basic number of the Federal Specification, the specification sheet number, bore code, and alpha or numeric codes for cage, radial internal clearance and tolerance class, lubricant and closures.

EXAMPLE: FFB2844 /07 BD 4 A P



FFB2844/07BD4AP indicates - Bearing Bore 1.3570 inches; outside diameter 3.0000 inches; width 0.6875 inches; cage type, machined non metallic; radial internal clearance, tight; tolerance class, ABEC 1; single shield and single seal; lubricant in accordance with DoD-G-24508.

Source: https://assist.dla.mil -- Downloaded: 202610-26T11:47Z
Check the source to verify that this is the current version before use.

TABLE 1. BOUNDARY DIMENSIONS 1/

Bore Code	OB Bore Diameter (inch)	OB Bore Diameter (MM)	OD Outside Diameter	W Width	Chamfer Min. 2/	Dia. Series 3/	Dynamic Load Rating (lbs)
AA	0.5000	12.7000	1.3125	0.3750	.031	2	1311
AB	0.6250	15.8750	1.5625	0.4375	.047	2	2014
AC	0.7500	19.0500	1.8750	0.5625	.062	2	2622
AD	0.8750	22.2250	2.0000	0.5625	.062	2	2993
BA	1.0000	25.4000	2.2500	0.6250	.062	2	3002
BB	1.1250	28.5750	2.5000	0.6250	.062	2	4123
BC	1.2500	31.7500	2.7500	0.6875	.062	2	4470
BD	1.3750	34.9250	3.0000	0.6875	.062	2	5434
BE	1.5000	38.1000	3.2500	0.7500	.093	2	6175
BF	1.6250	41.2750	3.5000	0.7500	.093	3	6916
BG	1.7500	44.4500	3.7500	0.8125	.093	3	7410
BH	1.8750	47.6250	4.0000	0.8125	.093	3	7964
CA	2.0000	50.8000	4.0000	0.8125	.093	2	7964
CB	2.2500	57.1500	4.5000	0.8750	.093	3	9239
CC	2.5000	63.5000	5.0000	0.9375	.093	2	12,212
CD	2.7500	69.8500	5.2500	0.9375	.093	2	12,978
DA	3.0000	76.2000	5.7500	1.0625	.093	3	14,072
DB	3.2500	82.5500	6.0000	1.0625	.093	2	16,495
DC	3.5000	88.9000	6.5000	1.1250	.125	2	17,382
DD	3.7500	95.2500	6.7500	1.1250	.125	2	17,263
EA	4.0000	101.6000	7.2500	1.2500	.125	2	20,023
EB	4.2500	107.9500	7.5000	1.2500	.125	2	20,952
EC	4.5000	114.3000	8.0000	1.3125	.125	2	23,992
ED	4.7500	120.6500	8.2500	1.3125	.125	2	23,873
FA	5.0000	127.0000	9.0000	1.3750	.125	2	27,001
FB	5.5000	139.7000	9.5000	1.3750	.125	2	28,083

1/ All dimensions are in inches unless otherwise specified.
2/ The chamfer on bearings will clear a maximum fillet radius equal to the minimum chamfer.
3/ Diameter series is a soft metric conversion of the inch outside diameter and width in comparison with the boundary dimension in ANSI/AFBMA STD 20.

TABLE II. CAGES

CODE	CAGE
1	Pressed Steel or Molded Plastic
2	Machined Brass or Bronze
3	Machined Non Metallic (phenolic)
4	Pressed Brass

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

Table III. RADIAL INTERNAL CLEARANCE AND TOLERANCE CLASS

Code	Symbol	Tolerance
A B C D	2 (Tight) 0 (Normal) 3 (Loose) 4 (Extra Loose)	ABEC 1
E F G H	2 (Tight) 0 (Normal) 3 (Loose) 4 (Extra Loose)	ABEC 5

Table IV. LUBRICANTS AND CLOSURES

Code	Lubricant	Closure
A B C	DOD-G-24508 MIL-G-81322 Preservative 1/	OPEN (FIG 1)
D E F	DOD-G-24508 MIL-G-81322 Preservative 1/	SINGLE SHIELD (FIG 2)
G H	DOD-G-24508 MIL-G-81322	DOUBLE SHIELD (FIG 3)
J K L	DOD-G-24508 MIL-G-81322 Preservative 1/	SINGLE SEAL (FIG 4)
M N	DOD-G-24508 MIL-G-81322	DOUBLE SEAL (FIG 5)
P R	DOD-G-24508 MIL-G-81322	SINGLE SHIELD AND SEAL (FIG 6)

1/ Preservative shall be in accordance with MIL-P-197.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Activity:
DLA - IS

Custodians:
Army - AT
Air Force - 11

Review Activities:
Army - AR, EA, MI Navy - OS

User Activities:
Army - GL, ME

CIVIL AGENCY COORDINATING ACTIVITIES:
GSA - FSS Military Coordinating

Preparing Activity:
DLA - IS

(Project 3110-0887-07)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.