GG-R-42B
August 8, 1974
SUPERSEDING
Int. Fed. Spec. GG-R-0042A (GSA-FSS)
December 2, 1968

FEDERAL SPECIFICATION

RACKS, RUBBER STAMP

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers racks for holding rubber stamps.

1.2 Classification.

1.2.1 Types and sizes. The rubber stamp racks shall be of the following types and sizes, as specified (see 6.2):

Type I - Wheel rack.
 Size 1 - 6 stamps (1 wheel).
 Size 2 - 14 stamps (2 wheels).
 Size 3 - 24 stamps (3 wheels).
Type II - Strip rack.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specification:

PPP-B-636 - Boxes, Shipping, Fiberboard.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC; Atlanta, Chicago, Kansas City, MO; Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:48Z
Check the source to verify that this is the current version before use.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, NW., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The base, wheel(s), and stud(s) of the type I rack, and the flat strip of the type II rack shall be metal suitable for finishing as required by 3.3. The locking device for the type I rack may be fabricated of metal or plastic. Spring tension clips for type I and II racks shall be full hard cold-rolled steel not less than 0.025 inch in thickness and shall retain its shape and spring tension after being formed. Alternatively, at the option of the supplier, spring tension clips may be fabricated from 400 series (AISI) quarter hard stainless steel not less than 0.020 inch in thickness. The width of the steel for spring tension clips shall be 3/8 inch ± 1/16 inch.

3.2 Design and construction.

3.2.1 Type I wheel rack. The type I rack shall consist of a base, wheel(s), extension stud(s), and a locking device. The base, extension studs, and locking device shall be provided with appropriate threads.

3.2.1.1 Base. The base shall be circular, hexagonal, or octagonal in shape and not less than 5-1/4 inches in diameter. Hexagonal and octagonal bases shall be measured across the flats to determine the diameter measurement. The base shall be of sufficient weight that the rack will be stable and will not upset during normal usage.

3.2.1.2 Wheels. The wheels shall be designed to revolve easily and smoothly when the locking device and extension studs are securely tightened. Spring tension clips shall be permanently and securely attached to the wheels. The clips shall be designed for holding rubber stamp handles with a holding area diameter of 1/2 inch ± 1/8 inch. The rack shall have the number of wheels indicated for the respective capacities specified in 1.2.1.

3.2.1.3 Extension studs. The extension studs shall have a minimum cross sectional diameter of 3/8 inch and shall be of sufficient length to provide a minimum distance of 2-7/8 inches between wheels, and between the bottom wheel and the base. The studs shall be provided with a suitable shoulder so that the wheels will revolve as specified in 3.2.1.2.

3.2.1.4 Locking device. The locking device shall be designed to hold the top wheel in place, and shall lock tight against the shoulder of the stud when tightened down.

3.2.2 Type II strip rack. The type II rack shall be designed for fastening to a flat vertical surface with screws. The rack shall consist of nine tension clips permanently and securely attached to a flat metal strip which shall have a hole at each end. The strip shall be 12 inches ± 1 inch in length, not less than 7/16 inch in width, and not less than 3/32 inch thick. The clips shall be designed for holding rubber stamp handles with a holding area diameter of 1/2 inch ± 1/8 inch. Two appropriate wood screws shall be furnished.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:48Z
Check the source to verify that this is the current version before use.

3.3 Finish and color. The spring tension clips shall be bright nickel or chrome plated. Stainless steel, if used, shall have a No. 4 general purpose polished finish. Unless of corrosion resistance material, the other parts of the rack shall be bright nickel or chrome plated, or shall have a gray baked enamel finish. The enamel finish shall level out to produce a uniform surface and color without runs, grit, areas of thin film, chips, flaking, and cracks.

3.4 Identification marking. Each rack shall be marked with the manufacturer's name or trademark of such known character that the source of manufacture may be readily determined.

3.5 Workmanship. All parts shall be free from burrs, slivers, and sharp edges. The racks shall be free from defects and imperfections which affect appearance or impair serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. For purpose of sampling, a lot shall consist of all rubber stamp racks of one type and size offered for delivery at one time.

4.2.2 Sampling for visual and dimensional inspection. A random sample of racks shall be taken from each lot in accordance with MIL-STD-105, inspection level S-4, acceptable quality level (AQL) 4.0 percent defective. The sample unit shall be one rack.

4.2.3 Sampling for preparation for delivery. Sampling shall be in accordance with MIL-STD-105. For examination of interior packages, the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

4.3 Visual and dimensional examination. Samples taken in accordance with 4.2.2 shall be examined for defects listed in Table I. Any rack in the sample containing one or more defects shall be rejected. If the number of defective racks in the sample exceeds the acceptable number for the sample, the lot represented by the sample shall be rejected.

TABLE I. Classification of rubber stamp rack defects

Examine	Defects
Classification	Not type and size (holding capacity) specified (see 1.2.1)
Material	Not as specified in 3.1.
Design & construction:	
Type I	Components and threads not as specified in 3.2.1.
Base	Shape, size, and weight not as specified in 3.2.1.1.
Wheels	Do not revolve easily and smoothly when locking device and studs are securely tightened (see 3.2.1.2).
	Clips and number of wheels not as specified in 3.2.1.2.
Extension studs	Diameter or length not as specified in 3.2.1.3.
	Shoulder not as specified in 3.2.1.3.
Locking device	Does not hold the top wheel in place (see 3.2.1.4).
	Does not lock tight against the shoulder of the stud when tightened down (see 3.2.1.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:48Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of rubber stamp rack defects (cont'd)

Examine	Defects
Design & construction (cont'd)	
Type II	Not designed as specified in 3.2.2. Components not as specified in 3.2.2. Clips and strip not as specified in 3.2.2. Screws missing or not as specified in 3.2.2.
Finish & color	Clips not finished as specified in 3.3. Other parts not finished as specified in 3.3.
Identification marking	Not marked as specified in 3.4.
Workmanship	Not as specified in 3.5.

4.4 Inspection of preparation for delivery requirements. Samples taken in accordance with 4.2.3 shall be examined to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with Table II.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings	Omitted, incorrect, illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.
Contents	Number per container is more or less than required; net weight exceeds requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.2).

5.1.1 Level A. Each rack shall be packaged unassembled in a close-fitting box conforming to PPP-B-636, style OPF, class weather-resistant. The box shall be closed in accordance with the appendix to the box specification.

5.1.2 Level B. Each rack shall be packaged in accordance with paragraph 5.1.1, except that box material shall be class domestic.

5.1.3 Level C. The racks shall be packaged in accordance with the manufacturer's standard practice, provided that this insures protection for racks during shipment and provides for safe delivery to their destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Strip type. One hundred and twenty unit packages of strip type racks shall be packed together in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix of the box specification.

5.2.1.2 Wheel type. Forty-eight unit packages of one wheel type racks, 40 unit packages of two wheel type racks, or 32 unit packages of three wheel type racks shall be packed in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix of the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:48Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 Strip type. One hundred and twenty unit packages of strip type racks shall be packed together in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix of the box specification.

5.2.2.2 Wheel type. Forty-eight unit packages of one wheel type racks, 40 unit packages of two wheel type racks, or 32 unit packages of three wheel type racks shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix of the box specification.

5.2.3 Level C. Racks packaged as specified in 5.1 shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the National Motor Freight Classification rules or the Uniform Freight Classification rules.

5.3 Marking. Marking shall be in accordance with paragraph 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, the interior packages and shipping container shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military requirements. In addition to any special markings required by the contract or order, the interior packages and shipping container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The racks are intended for use in holding rubber stamps in an orderly and convenient arrangement.

6.2 Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type and size, as applicable, of racks (see 1.2.1).
(c) Selection of applicable level of packaging, packing, and any special marking required (see 5.1, 5.2, and 5.3).

MILITARY INTEREST

DOD has waived coordination

PREPARING ACTIVITY: GSA-FSS

User Interest:

Army-GL

U. S. GOVERNMENT PRINTING OFFICE : 1974 - 585-644/1347

Orders for this publication are to be placed with General Services Administration, acting as an agent for the Superintendent of Documents. See Section 2 of this specification to obtain extra copies and other documents referenced herein. Price 30 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:48Z
Check the source to verify that this is the current version before use.