INCH-POUND
A-A-55439
16 Aug 1994

COMMERCIAL ITEM DESCRIPTION

BATTERY, STORAGE, VEHICULAR IGNITION, LIGHTING, AND STARTING

The General Services Administration has authorized the use of this Commercial Item Description as a replacement for W-B-131 which is cancelled.

Scope. This description covers vehicular lead acid storage batteries.

Classification. Batteries furnished under this description shall be of the SAE/BCI battery type numbers and identified by a type designation number.

Type designation number. Batteries covered by this description are identified by a type designation number formed as indicated below. This type designation number is intended for cataloging and ordering purposes and not for surface printing on the vehicular battery.

Class of battery

Class 1 - Passenger car and light commercial, 12 volt.
Class 2 - Heavy duty commercial, 12 volt.
Class 3 - Passenger car and light commercial, 6 volt
Class 4 - Heavy duty commercial, 6 volt.
Class 5 - Maintenance-free passenger car and light commercial, 12 volt.
Class 6 - Maintenance-free heavy duty commercial, 12 volt.
Class 7 - Maintenance-free cycling service, 12 volt.
SAE Type No.: from SAE J537

Activation.

D - Dry charged.
W - Wet charged.
F - Maintenance-free.

Example:

A-A-55439	-	5	-	71-275	-	F
Description no.		Class of Battery		SAE Type No.		Activation. Maintenance Free

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any other data which may improve this document should be sent by letter to: Commander, Defense, General Supply Center, Attn: DGSC-SSM, Richmond, VA 23297-5000

AMSC - N/A FSC - 6140

Distribution Statement A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

Salient characteristics.

1. Dimensions. Batteries shall be within the dimensional limitations specified in SAE J537.

2. Materials. All material used in the construction of batteries purchased under this description shall conform to standards of the best commercial practices.

3. Containers. Containers shall be free of leaks, cracks, or other defects that would adversely affect performance. Containers shall be of one piece construction and shall be made of non-absorbent acid-resistant, hard rubber or polypropelene plastic.

Electrical breakdown. At a temperature of 80°F the container walls and partitions shall be capable of withstanding for 5 seconds a voltage of 100V/mil of wall thickness for hard rubber containers, 300V/mil of wall thickness for plastic containers, (30,000 volts maximum for either hard rubber or plastic) without being perforated or burned through.

Acid resistance. Specimens of the container material shall be capable of being immersed in sulfuric acid at 150°F for a period of 28 days without increasing in weight by more than 1.5%, increasing dimensionally by more than 2%, or blistering, cracking or showing other visible damage.

Impact resistance, hard rubber containers. At a temperature of 80°F the container shall be capable of withstanding, without damage, the impacts from a 2 pound steel ball dropped on the spans of the container positioned horizontally, with the minimum impact resistance specified in Table I. The points of impact and number of impacts shall be as specified in BCI Battery Technical Manual.

Impact resistance, plastic containers. At a temperature of 80°F the plastic containers shall be capable of withstanding, without damage, the impact resistance tests entitled "Plastic Container and Cover Testing Procedures" in BCI Battery Technical Manual, with the minimum impact resistance specified in Table I.

TABLE I CONTAINER IMPACT RESISTANCE

	Minimum Impact Resistance	
Battery Class	Hard Rubber Container	Plastic Container
Classes 1,3,5,6 and 7	12 In. lb Avg. for all spans No impact failure below 8 In. lb.	50 In. lb Avg. for all spans No single impact failure failure below 35 In. lb.
Classes 2 and 4	20 In. lb. Avg. all spans No impact failure below 16 In. lb.	75 In. lb Avg for all spans No single impact failure below 50 In. lb.

Bulge resistance, hard rubber containers. The hard rubber containers shall be capable of maintaining bulge resistance when filled with water to within 5/8 inch from the top, having the water heated to 158°F and held at that temperature for 3 hours, and letting the water gradually return to

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

75°F over a period of 10 hours minimum. Maintaining bulge resistance will be evidenced by the container not increasing in any dimension by more than 1/16 inch from measurements taken at 75°F prior to filling it with water.

Bulge resistance, plastic containers. The containers shall be capable of maintaining bulge resistance when tested as specified in "Plastic Container and Cover Testing Procedures" of BCI Battery Technical Manual, at a test temperature of 80°F.

4. Covers. Covers shall meet the same physical, chemical, and electrical requirements as the container material. Covers may be one-piece or multiple cell construction. The cell cover for non maintenance free batteries shall have an opening for each cell for a filling plug and the observation of the electrolyte level. The plugs may be of the screw, bayonet, gang or push-in type and shall incorporate baffles or other means of minimizing the splashing of electrolyte. The material in the plugs shall be non-absorbent, acid-resistant, and have no adverse effect on the electrolyte. The filler plugs shall incorporate an anti-flame propagation device and shall be vented.

5. Sealing compound and heat sealing. The seal resulting from sealing by compound or heat shall be acid-resisting and shall be unbroken between the cover and the container throughout a temperature range 0° to 150°F, with no adhesion failures.

6. Maintenance free batteries, Classes 5, 6 and 7. Maintenance free batteries shall not require the addition of water during normal service life. Provision for the anti-flame propagation device and gas venting shall be incorporated in the design. Opening in the battery cover to allow for the addition of water shall not be provided. The battery cover and vent system shall be designed to prevent electrolyte loss during service and up to a 45 degree tilt to keep the top of the battery free from electrolyte.

Side terminal batteries. Side terminals shall be of the type which are to be mated with sealed terminal connectors to tightly secure and seal the termination from corrosion and assure a maintenance-free connection.

7. Terminal seals. Terminal seals shall be provided to prevent leakage between terminals and the battery cover or container and shall be acid-resistant.

8. Metal parts. All metal parts, other than lead alloys, shall be coated with lead, or otherwise treated to resist acid.

9. Plates. Plates used in construction of batteries shall be of the size, number, and thickness that will enable the battery to meet its electrical performance requirements as specified in SAE J537.

10. Intercell connectors and post straps. Intercell connectors of 12-volt batteries shall not be exposed.

11. Separators. The separators shall be of material that will enable the battery to meet the performance requirements specified in SAE J537.

12. Double insulation. When specified, double insulation shall be furnished in batteries of the types in which double insulation is available. The double insulation shall be furnished in batteries recommended for motor coach or bus service. When a battery is built with double insulation, the cold activation, reserve capacity, and cold cranking requirements shall be reduced 15% from the values listed in SAE J537. For the purpose of this description, double insulation is defined as the use of a retaining sheet of perforated, porous

Source: https://assist.dla.mil -- Downloaded: 20260-26T09:46Z
Check the source to verify that this is the current version before use.

material, including glass mats, between the positive plate and the customary single separator.

13. Terminals. The terminals and polarity marking shall be in accordance with SAE J537.

14. Electrolyte. Unless otherwise specified, wet charged batteries shall be furnished with electrolyte that at full charge has a specified gravity of 1.265 ± 0.010 at 80°F at time of shipment. Unless otherwise specified, electrolyte shall not be furnished with batteries shipped dry charged.

Electrolyte level classes 1, 2, 3 and 4. Electrolyte level shall be not less than 3/8 inch above the top of the separators and the level shall be easily observable.

Dry charged batteries. After activation in accordance with the manufacturer's instructions, batteries shall meet the performance requirements specified in SAE J537.

15. Cycling service. Batteries shall contain plate thickness and formulation suitable for withstanding the high cycling type of service encountered in vehicles such as law enforcement, school bus, and delivery and shall be capable of meeting the cycle life test requirements of SAE J240. The class 7 battery shall be capable of yielding a minimum total cycles equal to 50 times its reserve capacity minute rating.

16. Cold activation of dry charged batteries. At 30°F dry charged batteries shall be capable of producing a terminal voltage, under load, at the end of 15 seconds discharge equivalent to 1.2 volts per cell minimum when tested as specified in BCI battery technical manual for cold activation performance.

17. Reserve capacity. After cold activation and conditioning as specified in SAE J537, batteries shall be capable of meeting the reserve capacity requirements as specified in BCI Battery Technical Manual Test sequence. A minimum of 90% of the batteries shall be capable of meeting or exceeding the specified reserve capacity of SAE J537. The remaining batteries shall be capable of meeting or exceeding 90% of the specified reserve capacity when tested as specified in SAE J537.

18. Cold cranking. At 0°F the battery shall be capable of meeting the performance requirements of SAE J537.

19. Charge rate. The battery shall be capable of accepting a minimum charge rate of 2% of the cold cranking rating of SAE J537.

20. Retention of charge. After cold activation and conditioning as specified in SAE J537 and after being on open circuit for 4 weeks at 75°F, without recharging at the end of this period, the battery shall be capable of meeting the following requirements.

Classes 1, 2, 3 and 4. 75% of the reserve capacity rate of SAE J537.

Classes 5, 6 and 7. 90% of the reserve capacity rate of SAE J537.

21. Internal resistance for dry batteries. For dry charged batteries the average terminal-to-terminal resistance of each cell in the assembled battery shall be not less than 50,000 ohms.

Source: https://assist.dla.mil -- Downloaded: 202610-26T09:46Z
Check the source to verify that this is the current version before use.

22. Leakage. Each cell shall be capable of independently maintaining a pressure of 2 psi for a period of 5 seconds with a maximum loss of 0.1 psi.

23. Vibration. Batteries shall be capable of meeting the leakage requirement and the cold cranking requirement for 0°F, and shall not have any electrolyte leakage after being subjected to 2 units of vibration as specified in SAE J537.

24. Identification marking. The following data shall be molded on the sides, the top of the cover, or applied to a permanent electrolyte resistant label or plate securely and permanently attached to the battery container.

Battery Identification Number
Cold Cranking at 0°F Rating (the test name or abbreviation thereof followed by the rating)
Manufacturer's Name or Identification (Manufacturer's name or identification may include private branding)

Date of manufacture (month, year) and plant of manufacture, if the same battery is manufactured at more than one plant, shall be legibly stamped or branded on the outside cell connector, top or side of the cover or container. A plate or label permanently affixed to the top or side of the outer cover or container, or a tag permanently affixed to the terminal post is acceptable. Coded information is acceptable provided the key to the code is made available.

25. Condition for shipment. Batteries shall be in one of the following conditions at the time of shipment.

Batteries intended for immediate use or wet storage with charging equipment. Filled with electrolyte and fully charged.

Batteries intended for storage, unfilled, and without charging. The vent hole for each cell shall be closed by easily removable, air-tight, and moisture-proof type seals or appropriate tape, which shall be held firmly in place until removed. Seals for vent holes are not required when the battery is enclosed in a six-sided box and sealed with weather resistant tape along the seams when the battery is enclosed and sealed in an air-tight and moisture-proof bag. Plates and separators of dry charged batteries shall meet the performance requirements when activated.

Maintenance free. Filled with electrolyte and fully charged.

26. Instruction for placing battery into service. Instructions for placing the battery into service, shall be provided with each battery. The instructions shall show the latest recommended date for placing the battery in service and shall include the specific gravity of electrolyte for filling (charged and dry) and charging instructions. The method of providing the instructions shall be in accordance with the manufacturer's standard practice.

27. Workmanship. Containers, covers, and vent caps shall be free from cracks, lead, and broken parts. Lead burning or welding shall be homogeneous and free from blow holes or imperfect bonds between parts which have been burned or welded together. Handles and metallic parts shall be free of burrs, sharp edges, and corrosion. Marking shall be clear and distinct. The sealing compound shall not be cracked or separated from the holding surfaces.

28. Warranty. The manufacturers' standard commercial warranty or the warranty specified in Federal Supply Schedule Group 61, Part 1, batteries: 6 or 12-volt lead-acid storage shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

Regulatory Requirements. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

Metric Products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest version of Federal Standard No. 376, and all other requirements of this Commercial Item Description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch/pound units, a request should be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of the Commercial Item Description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Preservation, packaging, packing and marking. Preservation, packaging, packing and marking for shipment shall be in accordance with American Society for Testing and Materials (ASTM) D 3951 or as specified in the contract or order.

Notes

Intended use. The batteries covered by this specification are intended primarily for starting, lighting, and ignition service on passenger cars, motor-trucks, and motor-coaches equipped with regulated charging systems.

Addresses for obtaining reference documents.

Battery Council International (BCI):

BCI Battery Technical Manual

Application for copies should be addressed to Battery Council International, 401 N. Michigan Ave., Chicago, IL 60611-4267.

Society of Automotive Engineers, Inc., (SAE)

Storage Batteries - SAE J537
Life Test for Automotive Storage Batteries SAE J240

Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15906.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM):

Packaging, Commercial - ASTM D 3951

American Society for testing and materials
1916 Race St.
Philadelphia, PA 19103

Ordering Data.

a) Title, number, and date of this document.
b) Type designation No.
c) Double insulation, if required (see paragraph 12).
d) Specific gravity of electrolyte, if other than specified (see paragraph 14).
e) Condition of battery at time of shipment (see paragraph 25).
f) Special packaging requirements.

National Stock Numbers. The NSN's covered by this document are listed in Appendix A.

MILITARY INTEREST:

Review Activity

AIR FORCE-80

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

User Activities
DC GOVT - DDG
USPS - POS
USDA - AFS

PREPARING ACTIVITY:
DLA - GS

PROJECT NO. - 6140-0784

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

Appendix A

NSN	Type Designation Number
6140-00-184-3415	A-A-55439-4-7D-900-D
6140-00-190-9828	A-A-55439-2-8D-900-D
6140-00-190-9831	Not Available (2-4D-640-D)
6140-00-190-9840	A-A-55439-3-2E-475-D
6140-00-190-9842	A-A-55439-3-2E-485-D
6140-00-190-8502	--
6140-00-191-8506	A-A-55439-3-1-475-D
6140-00-191-8519	A-A-55439-3-4-700-D
6140-00-195-5841	A-A-55439-3-1-475-W
6140-00-199-4988	A-A-55439-4-7D-900-W
6140-00-199-4991	A-A-55439-2-8D-900-W
6140-00-397-2647	A-A-55439-1-24C-410-W
6140-00-397-2658	--
6140-00-397-2662	Not Available (17M1A)
6140-00-397-2665	Not Available
6140-00-397-2670	A-A-55439-1-24F-375-D
6140-00-397-2678	A-A-55439-1-74-335-D
6140-00-407-3440	--
6140-00-434-5873	A-A-55439-3-2E-595-D
6140-00-434-5878	Not Available (Use 00-191-8490)
6140-00-434-5883	Not Available (3-2-520-D)
6140-00-434-5884	--
6140-00-434-5885	A-A-55439-3-1-545-D
6140-00-434-5887	A-A-55439-3-4-720-D
6140-00-434-5893	A-A-55439-3-2-650-D
6140-00-438-0208	Not Available
6140-00-438-0215	Not Available (Use 01-203-4912)
6140-00-438-0299	Not Available (2-30H-580-D)
6140-00-446-6758	A-A-55439-1-75-455-D
6140-00-446-6773	Not Available (1-74-410-D)
6140-00-446-6813	Not Available (Use 00-836-1279)
6140-00-446-6829	Not Available (Use 00-984-0159)
6140-00-446-6875	A-A-55439-1-24-375-D)
6140-00-446-6891	Not Available (Use 00-984-0159)
6140-00-473-1565	Not Available (1-24C-410-D)
6140-00-504-0968	--
6140-00-538-9984	A-A-55439-1-27-355-D
6140-00-538-9986	Not Available (1-24-385-D)
6140-00-539-8488	Not Available (1-27-355-W)
6140-00-539-8491	A-A-55439-3-4-700-D
6140-00-539-8507	A-A-55439-1-32N-350-D
6140-00-643-0495	Not Available (1-24-305-D)
6140-00-643-0496	--
6140-00-643-0502	Not Available (Use 00-836-1280)
6140-00-643-0507	A-A-55439-3-2-560-D
6140-00-729-8974	A-A-55439-1-27R-430-D
6140-00-822-0397	A-A-55439-1-22NF-245-D
6140-00-822-0410	A-A-55439-1-53-210-D
6140-00-822-0414	A-A-55439-1-29NF-330-D
6140-00-822-0415	A-A-55439-1-29NF-330-W
6140-00-822-0419	A-A-55439-1-27H-435-D
6140-00-836-1279	A-A-55439-1-24T-370-D

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

Appendix A

NSN	Type Designation Number
6140-00-836-1280	Not Available (1-60-360-D)
6140-00-836-1282	A-A-55439-1-3EE-300-W
6140-00-836-1283	A-A-55439-1-3EE-300-D
6140-00-864-7458	--
6140-00-889-1134	A-A-55439-1-24F-330-W
6140-00-984-0068	A-A-55439-1-24F-330-D
6140-00-984-0143	A-A-55439-2-30H-460-D
6140-00-984-0146	A-A-55439-1-27F-455-W
6140-00-984-0147	A-A-55439-1-27F-455-D
6140-00-984-0149	Not Available (1-3ET-425-D)
6140-00-984-0155	A-A-55439-1-27F-355-D
6140-00-984-0158	A-A-55439-1-24-430-W
6140-00-984-0159	A-A-55439-1-24-430-D
6140-00-984-0166	--
6140-01-010-3228	A-A-55439-1-22F-350-D
6140-01-013-2782	A-A-55439-1-22F-350-W
6140-01-013-2783	A-A-55439-1-24F-440-D
6140-01-014-5979	A-A-55439-1-24F-440-W
6140-01-031-6873	A-A-55439-5-71-275-F
6140-01-031-6874	A-A-55439-5-72H-430-F
6140-01-031-6875	A-A-55439-5-22F-375-F
6140-01-031-6876	A-A-55439-5-24F-470-F
6140-01-031-6877	A-A-55439-5-27-550-F
6140-01-031-6878	A-A-55439-5-27F-550-F
6140-01-031-6879	A-A-55439-6-24-475-F
6140-01-031-6881	A-A-55439-6-31-475-F (Tap Post)
6140-01-031-6882	A-A-55439-6-31-620-F (Tap Post)
6140-01-032-1326	A-A-55439-6-31-475-F (Stud)
6140-01-032-3618	A-A-55439-5-74-465-F
6140-01-032-3619	A-A-55439-5-24-470-F
6140-01-037-9173	Not Available (5-74-500-F)
6140-01-111-1016	--
6140-01-111-1017	--
6140-01-112-1056	--
6140-01-112-1057	--
6140-01-112-1058	--
6140-01-112-1059	Not Available
6140-01-112-1060	--
6140-01-112-1061	--
6140-01-112-1062	--
6140-01-112-1064	--
6140-01-112-1065	--
6140-01-112-1066	Not Available
6140-01-112-1067	--
6140-01-112-1068	--
6140-01-112-1069	--
6140-01-112-1070	--
6140-01-112-1071	--
6140-01-112-1072	--
6140-01-112-1073	--
6140-01-112-1074	--
6140-01-112-1075	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.

Appendix A

NSN	Type Designation Number
6140-01-112-1076	--
6140-01-112-1077	--
6140-01-112-8336	--
6140-01-112-6562	--
6140-01-113-6563	--
6140-01-114-2462	--
6140-01-114-2463	--
6140-01-114-2464	--
6140-01-115-5277	--
6140-01-115-5278	--
6140-01-115-9999	--
6140-01-200-0999	--
6140-01-202-9231	A-A-55439-5-55-380-F
6140-01-202-9232	A-A-55439-7-27-480-F
6140-01-203-3468	A-A-55439-7-24-375-F
6140-01-203-3469	Not Available (5-78-550-F(Tap Post))
6140-01-203-3470	A-A-55439-5-76-750-F
6140-01-203-3471	Not Available (5-73-465-F)
6140-01-203-3472	A-A-55439-5-71-390-F
6140-01-203-3473	A-A-55439-5-70-405-F
6140-01-203-3474	A-A-55439-5-33-1050-F
6140-01-203-3475	A-A-55439-5-26-405-F
6140-01-203-3476	A-A-55439-5-25-370-F
6140-01-203-3477	Not Available (5-24-500/1-F)
6140-01-203-3478	A-A-55439-5-24-500-F
6140-01-203-3479	A-A-55439-3-4-700-W
6140-01-203-4689	A-A-55439-5-24-410-F
6140-01-203-4690	A-A-55439-5-24-470/1-F
6140-01-203-4691	A-A-55439-5-24-470-F
6140-01-203-4692	Not Available (5-24-520/1-F)
6140-01-203-4693	Not Available (5-24-545/1-F)
6140-01-203-4694	A-A-55439-5-24-545-F
6140-01-203-4695	A-A-55439-5-24-550-F
6140-01-203-4696	Not Available (5-22F-300-F)
6140-01-203-4697	A-A-55439-5-22F-330-F
6140-01-203-4698	A-A-55439-5-22F-490-F
6140-01-203-4699	A-A-55439-5-64-535-F
6140-01-203-4700	A-A-55439-5-64-475-F
6140-01-203-4701	A-A-55439-5-63-450-F
6140-01-203-4702	A-A-55439-5-58-450-F
6140-01-203-4703	A-A-55439-5-57-310-F
6140-01-203-4704	A-A-55439-5-56-450-F
6140-01-203-4705	A-A-55439-7-31-580-F(Tap. Post)
6140-01-203-4706	A-A-55439-5-75-630-F
6140-01-203-4899	A-A-55439-2-U1-225-D
6140-01-203-4900	A-A-55439-5-78-550-F(Th. Hole)
6140-01-203-4901	A-A-55439-5-25-430-F
6140-01-203-4902	A-A-55439-5-24R-500-F
6140-01-203-4903	Not Available (5-24F-375-F)
6140-01-203-4904	A-A-55439-5-24C-425-F
6140-01-203-4905	A-A-55439-5-24C-440-F
6140-01-203-4906	Not Available (5-24C-500-F)

Source: https://assist.dla.mil -- Downloaded: 202640-26T09:46Z
Check the source to verify that this is the currenversion before use.

Appendix A

NSN	Type Designation Number
6140-01-203-4907	A-A-55439-5-24-390-F
6140-01-203-4908	A-A-55439-5-54-330-F
6140-01-203-4909	A-A-55439-7-31-580-F(Th. Ter.)
6140-01-203-4910	A-A-55439-2-8D-1000-D
6140-01-203-4911	Not Available (2-8D-1000-W)
6140-01-203-4912	A-A-55439-2-4D-925-D
6140-01-203-4913	Not Available (2-4D-925-W)
6140-01-203-4914	A-A-55439-5-26-335-D
6140-01-203-8807	A-A-55439-5-70-310-F
6140-01-203-8808	A-A-55439-5-65-850-F
6140-01-203-8809	A-A-55439-1-U1-255-W
6140-01-203-8810	A-A-55439-5-24F-475-F
6140-01-203-8811	Not Available (5-70-355-F)
6140-01-203-8812	Not Available (5-70-315-F)
6140-01-203-8977	A-A-55439-1-U1-235-D
6140-01-203-8978	A-A-55439-1-U1-235-W
6140-01-203-8979	Not Available (5-24-520-F)
6140-01-203-8980	A-A-55439-5-62-380-F
6140-01-203-8981	A-A-55439-5-61-310-F
6140-01-203-8982	A-A-55439-5-58-410-F
6140-01-203-8983	A-A-55439-5-58-380-F
6140-01-203-8984	A-A-55439-7-74-375-F
6140-01-203-8985	A-A-55439-5-78-515-F
6140-01-203-8986	Not Available (5-76-1075-F)
6140-01-204-4569	A-A-55439-3-3D-1310-D
6140-01-204-5431	A-A-55439-5-75-500-F
6140-01-204-5432	A-A-55439-5-24-500/2-F
6140-01-205-4572	A-A-55439-3-3D-1310-W
6140-01-210-1963	A-A-55439-7-31-580-F
6140-01-211-9635	A-A-55439-3-2-725-D
6140-01-212-7523	A-A-55439-3-2-725-W
6140-01-323-1330	--
6140-01-331-5708	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:46Z
Check the source to verify that this is the current version before use.