INCH-POUND


MIL-DTL-28875/10C
20 January 2015
SUPERSEDING
MIL-DTL-28875/10B
15 June 2010

DETAIL SPECIFICATION SHEET

AMPLIFIERS, RADIO-FREQUENCY AND MICROWAVE, SOLID-STATE, WIDEBAND, TO CONFIGURATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the amplifiers described herein shall consist of this specification sheet and MIL-DTL-28875.



	Inches		Millimeters	
	Max	Min	Max	Min
B	N/A	.17	N/A	4.32
C	.455	.445	11.56	11.30
D	.510	.490	12.95	12.45
E	.019	.016	.48	.41
F	.160	.140	4.06	3.56
G	.310	.290	7.87	7.37
H	.160	.140	4.06	3.56
J	.310	.290	7.87	7.37
K	.05	N/A	1.3	N/A

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only (1.00 inch = 25.4 mm).

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (25°C unless otherwise specified).

Dash No.	Frequency range	DC input power		Gain (dB)	Gain flatness (dB)	RF output power (dBm)	VSWR Max		Noise figure (dB)	Intercept point 3rd order (dBm)	Harmonic output (dBc)	Gain versus temp. (dB)	RF input power (mW)	Isolation (dB)	Phase linearity (deg)
	(MHz)	Voltage	Curr. Max (mA)	Min	Max	Min	IN	OUT	Max	Min			Max	Min	Max
S1 01 S2 N	2-250	15 Nom	55	29	±1.0	+7	2.0:1	2.0:1	5.5	+17	N/A	+1.0	+60	N/A	N/A
S1 02 S2 N	2-250	15 Nom	98	13	±1.0	+20.0	2.0:1	2.0:1	7	+30	N/A	1.0	+13	N/A	N/A
S1 03 S2 N	5-250	+15 ±1%	40	29	±1.0	+7.0	2.0:1	2.0:1	5.5	+21	N/A	1.0	+17	N/A	N/A
S1 04 S2 N	5-1000	+15 ±1%	29	13	±1.0	+6.0	2.0:1	2.0:1	7	+21	N/A	1.0	+17	N/A	N/A
S1 05 S2 N	100-1000	+15 ±1%	34	14	±1.0	+5.0	2.0:1	2.0:1	7	+18	N/A	1.0	+17	N/A	N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

TABLE II. Dimension, physical and environmental characteristics.

Dash number	Dimension A in inches (mm) Max	Mass Max (Grams)	Temperature range		Burn-in temperature (case temp)	Seal	Salt
			Operating case temp	Nonoperating			
01 S1 S2 N	.22 (5.6)	3.1	-54/+100°C	-62/+125°C	+100°C	Hermetic	N/A
02 S1 S2 N	.22 (5.6)	3.1	-54/+100°C	-62/+125°C	+100°C	Hermetic	N/A
03 S1 S2 N	.22 (5.6)	3.1	-54/+100°C	-62/+125°C	+100°C	Hermetic	Applicable
04 S1 S2 N	.18 (4.6)	3.1	-54/+100°C	-62/+125°C	+125°C	Hermetic	N/A
05 S1 S2 N	.22 (5.6)	3.1	-54/+100°C	-62/+125°C	+125°C	Hermetic	N/A

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table II.

Electrical characteristics: See table I.

Physical and environmental characteristics: See table II.

Part number. M28875/10-(dash number from tables I and II).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

Referenced documents. This specification sheet only references MIL-DTL-28875.

The margins of this specification sheet are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodian:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5996-2015-005)

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.