INCH-POUND

MIL-DTL-28875/12B
20 January 2015
SUPERSEDING
MIL-DTL-28875/12A
24 August 2000


DETAIL SPECIFICATION SHEET

AMPLIFIERS, RADIO-FREQUENCY AND MICROWAVE, SOLID-STATE, WIDEBAND, LOW PROFILE, TO CONFIGURATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Inactive for new design after 20 May 2010

The requirements for acquiring the amplifiers described herein shall consist of this specification sheet and MIL-DTL-28875.



	Inches		Millimeters	
	Max	Min	Max	Min
A	.207	.197	5.26	5.00
B	---	.17	---	4.3
C	.555	.545	14.10	13.84
D	.610	.590	15.49	14.99
E	---	.17	---	4.3
F	.210	.190	5.33	4.83
G	.410	.390	10.41	9.91
H	.031	---	0.79	---

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only (1.00 inch = 25.4 mm).
3. Unless otherwise specified, tolerance is ±.005.

FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics (25°C unless otherwise specified).

Dash No.	Frequency range (MHz)	DC input power		Gain (dB)	Gain flatness (dB)	RF output power (dBm)	VSWR Max		Noise figure (dB)	Intercept point 3rd order (dBm)	Harmonic output (dBc)	Gain versus temp. (dB)
		Voltage	Curr. Max (mA)	Min	Max	Min	IN	OUT	Max	Min		
S1 01 S2 N	5-500	+15 ±1%	131	25	±0.7	+20.5	2.0:1	2.0:1	4.5	+30	N/A	±1
S1 02 S2 N	5-500	+15 ±1%	131	29	±0.7	+20	2.0:1	2.0:1	4.5	+30	N/A	±1
S1 03 S2 N	10-1000	+15 ±1%	131	24.5	±0.7	+21	2.0:1	2.0:1	5.0	+29	N/A	±1
S1 04 S2 N	200-2000	+15 ±1%	129	14.5	±1.0	+15.5	2.0:1	2.0:1	7.5	+20	N/A	±1
S1 05 S2 N	200-3000	+15 ±1%	129	11.0	±1.0	+15.5	2.0:1	2.0:1	8.5	+20	N/A	±1
S1 06 S2 N	200-2000	+15 ±1%	175	8.0	±1.0	+23.5	2.0:1	2.0:1	4.5	+32	N/A	±1

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

TABLE II. Dimension, physical and environmental characteristics.

Dash number	Mass Max (Grams)	Temperature range		Burn-in temperature (case temp)	Seal	Salt
		Operating case temp.	Non-operating			
01 S1 S2 N	10	-55/+85°C	-65/+125°C	+85°C	Hermetic	Applicable
02 S1 S2 N	10	-54/+85°C	-55/+125°C	+85°C	Hermetic	Applicable
03 S1 S2 N	10	-54/+85°C	-55/+125°C	+85°C	Hermetic	Applicable
04 S1 S2 N	10	-55/+85°C	-65/+125°C	+85°C	Hermetic	Applicable
05 S1 S2 N	10	-54/+85°C	-62/+125°C	+85°C	Hermetic	Applicable
06 S1 S2 N	10	-55/+85°C	-62/+125°C	+85°C	Hermetic	Applicable

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table II.

Electrical characteristics: See table I.

Physical and environmental characteristics: See table II.

Part number. M28875/12-(dash number from tables I and II).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.

Referenced documents. This specification sheet only references MIL-DTL-28875.

The margins of this specification sheet are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodian:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5996-2015-006)

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T20:23Z
Check the source to verify that this is the current version before use.