
Review activities:
Army - ME, AT
Navy - SH
Air Force - 11, 85
Defense Supply Agency - GS
User activities:
Army - EL
Navy - AS
Air Force - None

FED. SUP CLASS
6240



MS part number	Industry number	Rated volts	Design amperes	Candle power (approx.)	Filament designation	Avg. life (hours)	Finish	Primary service
MS15573-1	51	6	0.22	1	C-2R	1000	Clear	Auto and indicator
MS15573-2	51R	6	0.22	0.1 (E)	C-2R	1000	Red	Instrument dial lighting, truck light control
MS15573-3	356	28	0.17	3.5	C-2V	500	Clear	Instrument and indicator light
MS15573-4	53	12	0.12	1	C-2V	1000	Clear	Automotive
MS15573-5	1450	24	0.035	0.23	C-2V	3000	Clear	Automotive
MS15573-6	354	2.47	0.30	0.50	C-2R	15	Clear	Distress marker, aircrew

NOTES:
1. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
2. Referenced documents shall be of the issue in effect on date of invitations for bid.

NOTE: Revision C inadvertently omitted red finish and assigned MS15573-2 to clear finish. The red finish is hereby reinstated with original part (MS15573-2), and the remaining part numbers have been reassigned accordingly.

(E) This revision consists of changing the candle power rating for MS15573-2 and inserting the figure which was inadvertently omitted from revision D.

APPROVED 25 JUNE 1954 REVISED (D) 7 February 1968 (E) 31 May 1968

Project 6240-0186

P.A. SH Other Cust ME 11	TITLE LAMP, INCANDESCENT, G-3-1/2, MINIATURE BAYONET BASE, SINGLE CONTACT	MILITARY STANDARD MS 15573
PROCUREMENT SPECIFICATION W-L-111	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 COORDINATED

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:49Z
Check the source to verify that this is the current version before use.