
FED. SUP CLASS
5305



NOMINAL SIZE	D		E (.086)	A (.112)	C (.138)	R (.164)
THREADS PER INCH			56NC	40NC	32NS	32NS
BODY DIAMETER	D_s	Max	.0860	.1120	.1380	.1640
		Min	.0717	.0925	.1141	.1399
HEAD DIAMETER	A	Max	.167	.219	.270	.322
		Min	.155	.205	.256	.306
HEAD HEIGHT	E	Max	.053	.068	.082	.096
		Min	.045	.058	.070	.085
SLOT WIDTH	J	Max	.031	.039	.048	.054
		Min	.023	.031	.039	.045
SLOT DEPTH	T	Max	.031	.041	.050	.058
		Min	.023	.030	.038	.043
RADIUS ON HEAD	R_1	Max	.035	.052	.066	.092
RADIUS UNDER HEAD	R	Max	.013	.018	.023	.023

LENGTH, L		Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD OR WASHER IF PROVIDED.	1/8	+0 -1/32	1	11	21	31
	3/16		2	12	22	32
	1/4		3	13	23	33
	5/16		4	14	24	34
	3/8		5	15	25	35
	7/16		6	16	26	36
	1/2		7	17	27	37
	5/8		8	18	28	38
	3/4		9	19	29	39
	7/8		10	20	30	40
	1			21		41
	1-1/8	+0 -1/16		22		42
	1-1/4			23		43
	1-3/8					
	1-1/2					
Minimum Complete Thread Length of 1-3/8.	1-3/4	+0 -1/32				
	2					
	2-1/4					
	2-1/2					
	2-3/4					
	3					

MATERIAL: Carbon Steel, Specification QQ-W-409 or QQ-S-633, except Brasscraft compositions: 55,000 PSI minimum ultimate tensile strength.

FINISH: Cadmium plated, Specification QQ-P-416, Type II, class C.

THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services Handbook H-28.

NOTES: (1) Referenced documents of issue in effect on date of invitation for bids shall apply.
(2) In case of conflict with any referenced document, this standard will govern.
(3) The MS part number consists of the MS sheet number, plus the dash number. Example: MS 35223-1.
(4) All dimensions in inches.

(B) CANCELLED - SEE SHEET 2
(EXCEPT DASH NO. 61, WHICH IS INACTIVE.)

(B) For changes see sheets 1 and 2.

APPROVED 9 FEB 1954 REVISED (A) 15 JUN 1962 (B) 15 JAN 1973

P.A.	MC
Other Coms	Navy

TITLE: SCREW, MACHINE, PAN HEAD, SLOTTED, CARBON STEEL, CADMIUM PLATED, NC-2A AND UNC-2A

MILITARY STANDARD
MS 35223

PROCUREMENT SPECIFICATION: FF-S-92

SUPERSEDES

SHEET 1 OF 2

DD FORM 672-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:11Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5305

NOMINAL SIZE	D		10 (.190)	1/4	5/16	3/8
THREADS PER INCH			24UNC	20UNC	18UNC	16UNC
BODY DIAMETER	D_o	Max	.1900	.2500	.3125	.3750
		Min	.1586	.2187	.2712	.3287
HEAD DIAMETER	A	Max	.373	.492	.615	.740
		Min	.357	.473	.594	.716
HEAD HEIGHT	H	Max	.110	.144	.178	.212
		Min	.099	.130	.162	.195
SLOT WIDTH	J	Max	.060	.075	.084	.094
		Min	.050	.064	.072	.081
SLOT DEPTH	T	Max	.067	.087	.109	.130
		Min	.050	.070	.092	.113
RADIUS ON HEAD	R_1	Max	.061	.087	.099	.143
RADIUS UNDER HEAD	R	Max	.031	.035	.027	.031

LENGTH	L	Tolerance	Dash Number	Dash Number	Dash Number	Dash Number
THREADS SHALL EXTEND TO WITHIN 2 THREADS OF THE BEARING SURFACE OF THE HEAD, OR CLOSER IF PRACTICABLE.	1/8	+0 -1/32	58			
	3/16		59			
	1/4		60	76		
	5/16					
	3/8		61	77	92	
	7/16		62	78	93	
	1/2		63	79	94	107
	5/8		64	80	95	108
	3/4		65	81	96	109
	7/8		66	82	97	110
	1		67	83	98	111
	1-1/8		68	84	99	112
	1-1/4	+0 -1/16	69	85	100	113
	1-3/8		70	86	101	114
	1-1/2		71	87	102	115
	1-3/4		72	88	103	116
Minimum Complete Thread Length of 1-3/4.	2					
	2-1/4	+0 -1/32	73	89	104	117
	2-1/2		74	90	105	118
	2-3/4		75	91	106	119
	3					

NOTE: For illustration, material, finish, and other pertinent data, see sheet 1.

(8) CANCELLED AFTER 15 JUN 1962 - USE MS35206
(EXCEPT DASH NO. 61, WHICH IS INACTIVE FOR NEW DESIGN AFTER 15 JAN 1973. USE FOR MAINTENANCE PURPOSES ONLY.)

INTERCHANGEABILITY RELATIONSHIP - MS35206 can replace the cancelled screws of the same size. The cancelled MS35223 cannot always replace MS35206 and should be used until existing stock is depleted. Then use only the superseding MS35206 screws of the same size for design and replacement.

APPROVED 9 FEB 1954 REVISED (4) 15 JUN 1962 (8) FOR CHANGES SEE SHEETS 1 AND 2.

F.A.	WC	TITLE	MILITARY STANDARD
Other Govt	9**	SCREW, MACHINE, PAN HEAD, SLOTTED, CARBON STEEL, CADMIUM PLATED, NC-2A AND UNC-2A	MS 35223
PROCUREMENT SPECIFICATION FF-S-92		SUPERSEDES	SHEET 2 OF

DD FORM 672-1 (Continued)

☆ U. S. GOVERNMENT PRINTING OFFICE: 1973 -714-541/3530

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:11Z
Check the source to verify that this is the current version before use.