MILITARY SPECIFICATION

LIFE PRESERVERS, UNDERARM, PNEUMATIC

This amendment forms a part of Military Specification MIL-L-38484(USAF) dated 12 December 1966.

PAGE 1

2.1: Under SPECIFICATIONS, Military add:

"MIL-P-3454 Packaging And Packing Of Life Preservers"

PAGE 2

2.1: Under DRAWINGS add:

"59J6709 Harness - Personnel Parachute, Chest, Assembly Of"

PAGE 5

* 3.6.1, lines 10, 11, and 12: Delete "0.15 pound per square inch (PSI) 20 seconds after discharge of the Cylinger and 1.0 PSI 45 seconds after discharge of the Cylinders" and substitute ".50 pound per square inch (PSI 1.0 minutes after discharge of the Cylinder."

PAGE 6

* 3.7.3: Add the following sentences. "The inflation assembly shall be Model FLU-1/P in accordance with revision B to MIL-L-27639 dated 16 November 1966. The Model FLU-1A/P in accordance with revision C to MIL-L-27639 shall not be used."

PAGE 7

4.1, second sentence: Delete and substitute: "Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government."

Following 4.1 add:

"4.1.1 Conformance of components and materials. The contractor shall provide certification as to the conformance of all components and materials to the requirements of their respective applicable documents. This certification shall include test data (see 6.2) from inspections conducted at the contractor's facility or at his sources facility."

FSC 4220

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

Following 4.3.4 add:

"4.3.5 Test harness. The contractor shall provide a Type ME-1 parachute harness conforming to Drawing 59J6709-30 and modified in accordance with the applicable technical order specified in 6.6. This harness shall be used to perform the operation test of 4.6.2 for the LPU-3/P life preserver. A suitable vest with zippers located in the correct position may be substituted."

PAGE 9

* 4.6.2, lines 9 thru 14: Delete "The minimum internal cell pressure 20 seconds after discharge of the Cylinders shall be 0.15 PSI. The minimum internal cell pressure 45 seconds after discharge of the Cylinders shall be 1.0 PSI" and substitute "The flotation Cells shall inflate to a minimum of .50 PSI 1.0 minutes after discharge of the Cylinder."

PAGE 11

Following 4.6.12 add:

"4.7 Inspection of preparation for delivery requirements. Sample items or packs and the inspection of the preservation, packaging, packing, and marking for shipment and storage shall be in accordance with the requirements of Section 5, or the documents specified therein."

Section 5: Delete in its entirety and substitute:

"5. PREPARATION FOR DELIVERY

"5.1 Preservation, packaging, packing, and marking of the life preservers shall be in accordance with level A, B, or C of MIL-P-3454, as specified (see 6.2).

"5.2 In addition to any special markings required by the contract, order, or MIL-P-3454, the unit, intermediate, and exterior containers shall be marked as follows:

LIFE PRESERVER, UNDERARM, PNEUMATIC LPU-3/P (OR LPU-10/P AS APPLICABLE) WITH CARBON DIOXIDE FOR INFLATION, MIL-L-38484(USAF)"

6.2c: Delete and substitute:

"c. Test data requirements (DD Form 1423). (See 4.1.1 and 4.4.1.1)."

6.2g: Delete and substitute:

"g. Selection of applicable levels of preservation, packaging, and packing."

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

6.3: Delete and substitute:

"6.3 Standard color samples. Request for access to a standard color sample for the cell should be addressed to the San Antonio Air Materiel Area, Engineering Division (MMEDO), Kelly AFB Texas 78241."

Following 6.4 add:

"6.5 Superseding data. The Type LPU-10/P life preserver covered by this specification replaces the Type LPU-2/P life preserver covered by MIL-L-26558B(USAF).

"6.6 Modification of Type ME-1 parachute harness. The applicable technical order for modification of the Type ME-1 parachute harness is T.O. 14S2-3-21 (See 4.3.5)."

* Concluding material: Delete and substitute the following:

"Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99"

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Project No. 4220-F230

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.