MIL-L-38484 (USAF)
12 December 1966
SUPERSEDING
MIL-L-26558B(USAF)
6 April 1960, and
MIL-L-26559A(USAF)
12 October 1961

MILITARY SPECIFICATION

LIFE PRESERVERS, UNDERARM, PNEUMATIC

1. SCOPE

1.1 Scope. This specification covers the requirements for two types of pneumatic underarm life preservers.

1.2 Classification. The life preservers shall be of the following types, as specified (see 6.2):

LPU-3/P - For parachute installation

LPU-10/P - With adjustable harness

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

V-T-295	Thread, Nylon

Military

MIL-L-5024	Lubricant, Inner Tube, Aircraft Tire
MIL-A-5540	Adhesive, Polychloroprene
MIL-V-5774	Valve, Oral Inflation
MIL-C-7515	Cord, Nylon, Coreless
MIL-C-19002	Cloth Coated; and Tape, Coated Cloth-Chloroprene on Nylon, Pneumatic Life Preserver
MIL-C-19377	Cloth, Nylon, Twill, Inflatable Life Preserver
MIL-C-25369	Cylinder, Carbon Dioxide, for Inflation of Pneumatic Life Preservers
MIL-L-27639	Life Preserver Inflating Assembly FLU-1/P

STANDARDS

Federal

FED-STD-151	Metals; Test Methods
FED-STD-601	Rubber: Sampling and Testing
FED-STD-751	Stitches, Seams, and Stitchings

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification of US Military Property
MIL-STD-143	Specifications and Standards, Order of Precedence for the Selection of
MS33586	Metals, Definition of Dissimilar

FSC 4220

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

DRAWINGS

52B6586	Tube - Oral Inflation, Pneumatic Survival Equipment
58J3590	Container - Parachute Flotation Cell, Pneumatic Underarm Life Preserver
58K3588	Cell - Flotation, Pneumatic Underarm Life Preserver
58K3589	Container-Harness, Flotation Cell, Pneumatic Underarm Life Preserver
61B4286	Stem - Inflator Valve, Life Preserver Cell, Assembly of

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 Components. The life preservers shall consist of the following major components:

Item No.	Quantity	Item Name
1	2	Flotation cell
2	2	Container
3	2	Inflation assembly, mechanical

3.3 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.4 Materials

3.4.1 Elastomeric or rubber materials. Unless otherwise specifically approved by the procuring activity, all elastomeric or rubber materials and component parts used in the life preservers shall have been manufactured within 12 months of the date of delivery to the Government.

3.4.2 Metals. Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to salt spray or atmospheric conditions likely to be met in storage or normal service.

3.4.2.1 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MS33586.

3.4.3 Flotation cell cloth. The coated cloth used in the construction of the flotation cells shall conform to type I of MIL-C-19002 with the exceptions specified in 3.4.3.1. All defects in the cloth coating not specifically covered by the applicable table of MIL-C-19002 shall be reinforced on the coated side with 1-inch-diameter discs of tape. Not more than two such discs shall be permitted in any one cell. The discs shall be applied by cementing. The tape used in the construction of the cells shall conform to type II, III, or IV of MIL-C-19002.

3.4.3.1 Exceptions to MIL-C-19002. The following exceptions shall apply to the type I coated cloth covered by MIL-C-19002:

a. In the paragraph entitled "Base Cloth" of MIL-C-19002, the sentence which states that the base cloth shall conform to the requirements of MIL-C-19377 shall be modified to read as follows: The base cloth shall conform to the requirements of

Source: https://assist.dla.mil -- Downloaded: 202640-21T12:42Z
Check the source to verify that this is the current version before use.

MIL-C-19377 except that any amendments made to MIL-C-19377 shall not apply and that, in lieu of the table entitled "Table of Defects," the following shall apply:

(1) The cloth shall be subjected to the quality conformance inspection. The quality conformance inspection shall consist of testing samples from each lot for conformance to section 3 of the specification and an examination of the sample of the filled shipping container from each lot for conformance to the packaging, packing, and marking requirements. A lot shall consist of cloth made essentially under the same conditions and in a single production run. In addition, a sample shall be selected from each lot in accordance with MIL-STD-105 and shall be tested by running it over a bank of lights having sufficient intensity to reveal defects in the cloth at a distance of 2 feet. All visible irregularities, including burl marks, shall be considered defects and shall be graded as specified herein.

(2) Defects up to 1/2 inch in any dimension shall be graded one point. Defects more than 1/2 inch but not more than 3 inches in any dimension shall be graded two points. Defects more than 3 inches but not more than 6 inches in any dimension shall be graded three points. Defects exceeding 6 inches to full width of one running yard shall be graded four points. For the purpose of evaluation under MIL-STD-105, the number of points shall be defined as the number of defects. The number of points or defects shall be evaluated using an acceptable quality level of 150 defects per 100 yards.

(3) Three-point and four-point defects shall be flagged in the selvage for removal in the fabrication process. All imperfections protruding from the surface of the cloth such as knots, fuzz balls, slubs, and kinky filling shall be removed by careful burling before the cloth is offered for delivery.

b. The paragraph entitled "Resistance to Accelerated Weathering" in MIL-C-19002 shall be changed to specify the following: After exposure of the coated cloth to the 24-hour accelerated weathering test, by exposing the uncoated side of the cloth to the light source, the breaking strength shall be not less than 145 pounds in the warp direction and 130 pounds in the filling direction, and the ultimate elongation shall be not less than 22 percent in the warp and the filling directions when tested by the ravel strip method. Specimens which are tested by the grab method shall have a minimum breaking strength of 80 pounds in the warp direction and 90 pounds in the filling direction and an ultimate elongation of 20 percent in either direction after weathering. A colorfastness to light equal to the standard color sample shall be maintained after weathering. (Note: Access to the standard color sample may be obtained as specified in 6.3).

c. The paragraph entitled "Base Cloth Defects" of MIL-C-19002 shall be changed to specify the following: After the coating process, the number of visible defects which are attributable to the base cloth shall not exceed the number existing in the base cloth before the coating process. Defects which are attributable to the base cloth shall not be considered as coated fabric defects. Critical coating defects shall not be accepted. All coating defects in an accepted roll of finished coated cloth shall be marked on the defect and at the selvage edge adjacent to the defect.

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:42Z
Check the source to verify that this is the current version before use.

3.4.4 Thread. Unless otherwise specified, the thread used in the construction of the preservers shall be nylon, type I or II, size E, class 1 of V-T-295.

3.4.5 Cement. Unless otherwise indicated, the cement used in the construction of the flotation cells shall conform to class 1, 2, or 3 of MIL-A-5540.

3.4.6 Container material. The container materials shall conform to Drawing 58K3589 or 58J3590, as applicable.

3.5 Design and construction. The life preserver shall consist of two containers attached either to an adjustable harness (LPU-10/P) or to slide fasteners for parachute installation (LPU-3/P) and two flotation cells (a right-hand cell and a left-hand cell) with mechanical inflation assemblies. The cells shall be packed into the containers as described in 3.5.1.

3.5.1 Unit assembly. The flotation cells shall be deflated, and a charged cylinder and inflator assembly with antichafing pad, gaskets, and cap shall be mounted on the inflator valve stem of each cell so that the cylinder lies on the cylinder outline marked on the cell. The actuating lever of the inflator shall be safety tied with a single strand of nylon thread, type I or II, class 1, size E, conforming to V-T-295. The cylinder shall be inserted into the cylinder holder of the container. The cylinder retaining strap shall be passed around the inflator stem between the inflator and the flotation cell. The strap shall be snapped to the back of the container. The cell shall be placed so the three grommets are over the three grommets in the back of the container. A doubled length of braided nylon cord conforming to type I of MIL-C-7515 shall be passed through the center grommet of the container and then through the center grommet of the cell, leaving a 1/2-inch loop at the back of the container. One end of the doubled cord shall be passed through the grommets to the right of the center grommet and through the loop at the back of the container. The other end shall be passed through the grommets on the left. All slack shall be pulled out, and the two ends shall be tied using a square knot. The ends of the cord shall be seared. The rear lobe shall be folded to fit into the space between the cylinder and top edge of the container. The front lobe shall be folded over the rear lobe with the oral tube along the top edge of the container and with the oral valve toward the front edge of the container. Using a length of cord, the webbing closure loop shall be pulled through the grommets in the container flaps, and the closure pin shall be inserted as shown in view A of Drawing 58K3589 or 58J3590, as applicable. The loop shall be safety tied to the closure pin with a single strand of type I or II, class 1, size E nylon thread conforming to V-T-295. (Note: All preservers shall have charged carbon dioxide cylinders installed prior to final assembly for shipment (see 3.6.4).

3.5.2 Operation of preserver. When the complete life preserver is properly assembled and donned, a pull on the knobs of the inflator lanyards shall operate the life preserver as follows:

a. Break the safety ties on the closure pins

b. Withdraw the closure pins from the loops

c. Break the safety ties on the inflator lever

d. Actuate the inflator levers to inflate the flotation cells.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

3.5.3 Stitching. Except where otherwise indicated, all stitches used in the construction of the preserver shall conform to type 301 of FED-STD-751, with 8 to 10 stitches per inch. All seams shall be backstitched not less than 1/2 inch. Stitching shall not be used in the gas retaining portion of the flotation cells.

3.5.4. Cementing. Either cementing or pressure curing by heat shall be used in the construction of seams, sealing areas, and attachments of all component parts of the preserver. All surfaces to be cemented shall be clean. All cement shall be fresh and shall be mixed within 8 hours of application. Fresh cement shall not be put into containers containing congealed cement. The cement shall be applied over the total contact areas and shall extend beyond all seam tapes and attachments by at least 1/8 inch on the inside and the outside of the cells and not more than 3/8 inch on the outside of the cells. After cemented areas are joined, trapped air and wrinkles shall be rolled out. The interior of each cell shall be dusted lightly with compound conforming to MIL-L-5024 to prevent adherence of noncemented surfaces.

3.6 Performance

3.6.1 Operation. After the life preserver has been properly assembled as specified in 3.5.1, it shall be donned by an individual who shall actuate the respective cells. The carbon dioxide cylinders shall be discharged when a reasonable pull is applied to the lanyards. The flotation cells shall inflate, in the time specified, to the following minimum pressures: 0.15 pound per square inch (psi) 20 seconds after discharge of the cylinder and 1.0 psi 45 seconds after discharge of the cylinders. The maximum pressure in the cells shall not exceed 3.0 psi when the temperature of the flotation cells reaches 70 (plus or minus 2) degrees Fahrenheit. The cells shall not leak after this test.

3.6.2 Pressure. Each flotation cell shall withstand an inflation pressure of 5 psi for a period of 5 minutes without evidence of failure of the materials or cemented areas or without evidence of permanent distortion of the cell from its designed shape.

3.6.3 Leakage. Each flotation cell shall be inflated to 2 psi. After 24 hours the pressure in the cells shall be not less than 1-1/2 psi.

3.6.4 Cylinder weight. Before the cylinder is installed on the preserver, the cylinder and the carbon dioxide charge shall weigh not less than the gross weight marked on the cylinder.

3.6.5 Burst. The flotation cell shall not burst when subjected to an inflation pressure of 12 psi.

3.6.6 Oral valve attachment. The oral valve shall be attached to the oral tube to withstand a load of 50 pounds.

3.6.7 Adhesion. The adhesion of all seams and attachments to the flotation cells shall be not less than 5 pounds per inch of width after joining coated to uncoated sides of the cell cloth and not less than 7-1/2 pounds per inch of width after joining coated to coated sides of the cell cloth.

3.6.8 Leakage after operation. After the preserver has been inflated 10 times as specified in 4.6.10, the cells shall not leak.

3.6.9 Buoyancy. When the flotation cells of a completely assembled preserver are inflated by the carbon dioxide cylinders, or oil-free air, the preserver shall support a weight of 76 pounds in water.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

3.6.10 Salt spray. Unless otherwise specified, all metal parts used in the construction of the preserver shall withstand a 96-hour exposure to salt spray without corrosion of the base metal.

3.6.11 Color matching. The color of the materials used in the preserver shall approximately match the color of the standard samples. (See 3.8 and 6.3.)

3.7 Details of components

3.7.1 Flotation cells. The flotation cells shall have an oral inflation system consisting of an oral inflation valve (MIL-V-5774) and an oral inflation tube (Drawing 52B6586) and shall conform to Drawing 58K3588. The cells less the mechanical inflation system shall weigh not more than 0.60 pound.

3.7.2 Container

3.7.2.1 LPU-3/P. The container for the LPU-3/P shall conform to Drawing 58J3590.

3.7.2.2 LPU-10/P. The container for the LPU-10/P shall conform to Drawing 58K3589.

3.7.3 Mechanical inflation assembly. The mechanical inflation assembly shall consist of an inflating assembly conforming to MIL-L-27639 and a carbon dioxide cylinder conforming to type II, MIL-C-25369. An inflator valve stem conforming to Drawing 61B4286 shall be cemented on the cell as shown on Drawing 58K3588.

3.8 Color. The exposed surface of the flotation cells shall be molten orange. The uncoated side of the container shall be sage green. Unless otherwise specified, the color of all webbings (when applicable), tapes, cords, and threads shall match the color of the uncoated side of the container fabric. The color of exposed cement shall blend with the color of the flotation cell fabric. Individual materials which have shade variations that are readily apparent shall not be used in one unit.

3.9 Identification of product. Unless otherwise specified, all markings shall be made with a durable nonmigrating ink of a color to contrast with the color of the surface marked. The ink shall have no deleterious effect on the surface marked. Marking shall be in accordance with MIL-STD-130.

3.9.1 Container marking. The preserver container identification label shall include the following information:

Life Preserver, Underarm, Pneumatic, LPU-3/P or LPU-10/P, as applicable

Specification MIL-L-38484 (USAF)

Manufacturer's Identification _____

Container Part No. _____

Contract or Order No. _____

Date of Manufacture _____

3.9.2 Flotation cell marking. Each flotation cell shall be marked with the following information:

Part No. _____

Manufacturer's Identification _____

Contract or Order No. _____

Date of Manufacture _____

Serial No. _____

Source: https://assist.dla.mil -- Downloaded: 202640-21T12:42Z
Check the source to verify that this is the current version before use.

3.10 Workmanship. Workmanship shall be in accordance with high grade manufacturing practice covering this class of work. Because of the emergency use of this equipment, it is required that all details of workmanship shall be of the highest quality in order to insure proper functioning of the preservers at all times.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of life preservers shall be classified as follows:

a. Preproduction tests

b. Acceptance tests.

4.3 Test conditions

4.3.1 Atmospheric conditions. Unless otherwise specified, all tests shall be made at an atmospheric pressure of 28 to 32 inches of mercury, a temperature of 70 (plus or minus 18) degrees Fahrenheit, and a relative humidity of 80 percent or less. When tests are concluded with atmospheric pressure or temperature differing from the starting values, corrections shall be made for the change in values.

4.3.2 Temperature corrections. If the ambient temperature changes during the 24-hour leakage test, adjustment shall be made on the basis of a change in pressure of 0.0312 psi per degree Fahrenheit change in temperature.

4.3.3 Barometric corrections. If the barometric pressure changes during the leakage test, adjustment shall be made on the basis of a change in pressure of 0.489 psi per inch (mercury) change in barometric pressure.

4.3.4 Test cylinders. Cylinders used for test purposes only need not be plated. Reworked cylinders may be used for test purposes provided the frangible plug and cylinder conform to the exterior dimensions specified in MIL-C-25369. The material and thickness of the frangible portion of the plug shall also conform to the frangible portion of the cylinder specified in MIL-C-25369. If recharged cylinders are utilized for test purposes, the weight of the carbon dioxide charge shall not exceed 28 grams.

4.4 Preproduction testing

4.4.1 Preproduction test samples. The preproduction test samples shall consist of two complete untested life preservers and two complete life preservers tested by the contractor in accordance with 4.4.2. The type of samples shall be as specified in the contract or purchase order.

4.4.1.1 Test data. Test data on the two contractor-tested preproduction samples shall be as specified by the procuring activity (see 6.2).

4.4.1.2 Submission of preproduction samples. Submission of preproduction samples shall be as specified by the procuring activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:42Z
Check the source to verify that this is the current version before use.

4.4.1.2.1 Identification of samples. The preproduction samples submitted shall be plainly identified by securely attached tags marked with the following information: Sample submitted by (name) (date) for preproduction test in accordance with MIL-L-38484 (USAF) under Contract No. _____.

4.4.1.3 Disposition of samples. Disposition of samples shall be as specified by the procuring activity (see 6.2).

4.4.2 Preproduction tests. Preproduction tests shall consist of all the tests specified under 4.6.

4.5 Acceptance tests. Acceptance tests shall consist of:

a. Individual tests

b. Sampling plans and tests.

4.5.1 Individual tests. Each life preserver shall be subjected to the following tests as described under 4.6.

a. Examination of product

b. Operation

c. Pressure

d. Leakage

e. Cylinder weight.

4.5.1.1 Rejection. Defects in rejected preservers may be corrected and the preservers submitted to the procuring activity for acceptance, but an air-retaining seam shall not be reworked, under any circumstances, more than one time.

4.5.2 Sampling plans and tests

4.5.2.1 Lot. A lot shall consist of life preservers manufactured under essentially the same conditions and submitted for inspection at substantially the same time. A lot shall not exceed 200 life preservers for sampling plans A and B and shall be in accordance with inspection level S-3 of MIL-STD-105 for sampling plan C.

4.5.2.2 Sampling plan A. One life preserver selected at random from each lot of 200, or fraction thereof, shall be subjected to the following tests as described under 4.6.

a. Burst

b. Oral valve attachment

c. Color matching.

4.5.2.2.1 Rejection, plan A. When one or more items from a lot fail the specified tests, the entire lot shall be rejected. Before resubmitting the lot, the contractor shall fully explain to the inspector both the corrections made and the cause of previous rejection. Preservers that have been rejected may be replaced or repaired and resubmitted for acceptance. Preservers rejected after resubmission shall not be submitted again without specific approval of the procuring activity. An air-retaining seam shall not be reworked after the preserver is submitted for acceptance.

4.5.2.3 Sampling plan B. An adhesion test sample shall be prepared from cell fabric by each worker each time a different batch of cement is used by the worker. The sample shall be identified with the lot in production. Five adhesion

Source: https://assist.dla.mil -- Downloaded: 202610-21T12:42Z
Check the source to verify that this is the current version before use.

test samples shall also be prepared from each incoming roll of cell fabric. The cementing procedure shall be the same as that used in the construction of the flotation cells. In addition, five sample seams and five sample patches shall be cut from the flotation cell used in sampling plan A. These samples shall be subjected to the adhesion test specified in 4.6.9.

4.5.2.3.1 Rejection, plan B. When one or more of the adhesion test samples specified in 4.5.2.3 fail the specified test, production shall be halted until the cause of failure is determined and the corrections made. When a sample seam from a flotation cell fails the specified test, the lot represented shall be rejected. Lots rejected on the basis of seam-adhesion tests may be resubmitted for acceptance provided five additional flotation cells selected at random from the lot are tested for adhesion and each is found to conform to requirements.

4.5.2.4 Sampling plan C. Upon completion of the individual tests specified in 4.5.1, random samples shall be selected from each lot in accordance with inspection level S-3 of MIL-STD-105. The sample size shall be based only on the applicable size code letter corresponding to the inspection level S-3. Each life preserver selected as a sample unit shall be forwarded to an inspection activity selected by the procuring activity (see 6.2) for the following tests and examination:

a. Operation

b. Pressure

c. Leakage

d. Examination of product.

4.5.2.4.1 Rejection, plan C. The acceptance number shall be zero, and the rejection number shall be one for each test and examination. The lot from which the life preserver samples were selected shall not be shipped until the samples have been approved by the procuring activity and the lot has been accepted by the cognizant quality control representative. The lot from which the life preserver sample was selected shall be rejected if any sample fails to meet any requirement of the tests specified in 4.5.2.4. A rejected lot shall not be resubmitted except with the approval of the procuring activity. Upon completion of the tests and examinations, the sample will be returned to the manufacturer.

4.6 Test methods

4.6.1 Examination of product. Each life preserver shall be visually examined to determine compliance with the requirements of this specification with respect to workmanship, materials, marking, and construction.

4.6.2 Operation. The life preserver, assembled as specified in 3.5.1, shall be adjusted to an individual to simulate actual service use. The carbon dioxide cylinders shall be discharged simultaneously with a reasonable pull to determine if the cells will come out of the container (see 3.5.2) and inflate to their designed shape. The minimum internal cell pressure 20 seconds after discharge of the cylinders shall be 0.15 psi. The minimum internal cell pressure 45 seconds after discharge of the cylinders shall be 1.0 psi. The maximum internal cell pressure shall not exceed 3.0 psi when the cell temperature has reached 70 (plus or minus 2) degrees Fahrenheit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

Failure of the cells to inflate as specified or evidence of leakage or failure of the mechanical inflation assembly shall be cause for rejection. After this test is completed, the flotation cells shall be completely deflated by means of a vacuum source, and the life preservers shall be subjected to the test specified in 4.6.3.

4.6.3 Pressure. Each cell of the preserver shall be inflated to 5 psi with oil-free air. After a minimum of 10 minutes, the pressure shall be checked and readjusted, if necessary, to the original pressure of 5 psi. The temperature and pressure shall be recorded at this time. After a minimum of 5 minutes following the readjustment period, the pressure shall be measured and corrected for any change in temperature or barometric pressure. The corrected pressure shall be not less than 4.60 psi. After these measurements and corrections, the pressure shall be released. Any evidence of failure of the material of the cemented areas or any evidence of permanent distortion of the cell shall be cause for rejection.

4.6.4 Leakage. For this test, the carbon dioxide cylinders shall be attached. Each cell of the preserver shall be inflated with oil-free air to a pressure of 2 psi. After a minimum of 15 minutes, the pressure shall be checked and readjusted, if necessary, to the original pressure of 2 psi. The pressure source shall then be removed. After a minimum of 24 hours following the readjustment period, the pressure shall be measured and corrected for any change in temperature or barometric pressure. The corrected pressure shall not be less than 1-1/2 psi. This test shall follow the test specified in 4.6.3. Failure to meet these requirements shall be cause for rejection.

4.6.5 Cylinder weight. Each cylinder shall be weighed not more than 72 hours prior to its installation on the preserver. The weight of the cylinder and carbon dioxide charge shall be not less than the gross weight marked on the cylinder.

4.6.6 Burst. The flotation cells shall be subjected to an inflation pressure sufficient to cause failure of material or seam areas. The pressure at which failure occurs and the type of failure shall be recorded. Failure at a pressure of 12 psi or less shall be cause for rejection.

4.6.7 Oral valve attachment. The strength of attachment of the oral valve in the tube shall be determined by applying force along the longitudinal axis of the assembly in the tensile machine with a jaw separation of 12 inches (plus or minus 1/2 inch) per minute. Failure to withstand a load of 50 pounds shall be cause for rejection.

4.6.8 Color matching. The color of the flotation cells shall be compared to and shall approximately match the color of the standard shade (see 6.3). The color of the containers shall be compared to the requirements of 3.8. Individual materials having shade variations that are apparent shall not be used together in the same unit.

4.6.9 Adhesion. Conformance to the adhesion requirement in 3.6.7 shall be determined in accordance with method 8011 of FED-STD-601.

4.6.10 Leakage after operation. The life preserver shall be subjected to 10 operations as specified in 4.6.2. At the conclusion of these operations, the internal cell pressure shall be adjusted to 2-1/2 psi and

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

the cells submerged in water for not less than 2 minutes. Any evidence of leakage of the cells or inflation assemblies shall be cause for rejection. Any nonconformance to the pressure requirements of 4.6.2 during the 10 operations shall be cause for rejection.

4.6.11 Buoyancy. A completely assembled life preserver shall be inflated with carbon dioxide cylinders. The discharged cylinders shall be left in the inflators. Each of the flotation cells shall have a 35-pound steel weight attached by a 2-foot length of cord so that the 70 pounds is distributed evenly. The weighted preserver shall be placed in water and shall not submerge. Failure of the preserver to support the weights as specified shall be cause for rejection. In lieu of carbon dioxide gas, 1-1/2 psi of oil-free air may be substituted; however, the inflating assembly and an empty carbon dioxide cylinder shall be installed.

4.6.12 Salt spray. Each metal part or assembly not protected against corrosion by salt spray in accordance with Government specifications, standards, or drawings, shall be subjected to a 96-hour salt spray test in accordance with method 811 of FED-STD-151. After this test the metal part or assembly shall be examined for corroded areas. A corroded area, which is defined as exposure or corrosion of the base metal, shall be cause for rejection of the part or assembly.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the instructions of the procuring activity.

6. NOTES

6.1 Intended use. The life preservers covered by this specification are intended to be used by aircrewmembers as emergency flotation gear.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. Type of life preserver (see 1.2)

c. Test data requirements for contractor-performed preproduction tests (DD Form 1423). (See 4.4.1.1.)

d. Instructions for submission of preproduction samples including inspection activity (see 4.4.1.2)

e. Disposition of preproduction samples (see 4.4.1.3 and 6.4)

f. Selection of inspection activity and disposition of samples for sampling plan C (see 4.5.2.4)

g. Preparation for delivery requirements.

6.3 Standard color samples. Requests for access to a standard color sample for the cell should be addressed to the Systems Engineering Group, Attn: SEMCE, Wright-Patterson Air Force Base, Ohio 45433.

6.4 Disposition of samples. Preproduction testing will result in the destruction of the samples.

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

Review activities:
Air Force - 11, 84

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:42Z
Check the source to verify that this is the current version before use.

FOLD

SEG (SEPS)
WRIGHT-PATTERSON AFB, OHIO

POSTAGE AND FEES PAID

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

Commander
Systems Engineering Group
ATTN: SEPS
Wright-Patterson AFB, Ohio

FOLD

Source: https://assist.dla.mil -- Downloaded: 202640-21T12:42Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD, FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE C-8278

Source: https://assist.dla.mil -- Downloaded: 202640-21T12:42Z
Check the source to verify that this is the current version before use.