MIL-T-38473A(USAF)
AMENDMENT 2
15 Feb 85
SUPERSEDING
AMENDMENT 1
1 July 1978

MILITARY SPECIFICATION

TIMER, PRECISION, BOMBING, 0-30 MINUTES

This amendment forms a part of Military Specification MIL-T-38473A(USAF) dated 30 June 1972, and is approved for use by the Department of Air Force and is available for use by all Departments and Agencies of the Department of Defense.

* Add to bottom of Page 1:

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Engineering Division, San Antonio ALC/MMEDO, Kelly AFB, Texas 78241 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 1

2.1, delete in its entirety and substitute the following 2.1 and add new paragraph 2.1.1:

* 2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

* Under SPECIFICATIONS, Federal, add the following:

PPP-B-601	Boxex Wood Cleated - Plywood
PPP-B-636	Box, Shipping, Fiberboard

* Under SPECIFICATIONS, Military MIL-E-5400, change title to read "Electronic Equipment, Aerospace, General Specification For."

PAGE 2

* MIL-L-25467 - delete title and substitute "Lighting, Integral, Red, Aircraft Instrument, General Specification For."

Under STANDARDS, Military:

* Delete "MIL-STD-100" and substitute "DOD-STD-100" same title.

* Delete title opposite MIL-STD-461 and substitute "Electromagnetic Emmission and Susceptibility Requirements for the Control of Electromagnetic Interference.

* Delete title opposite MIL-STD-701 and substitute "Lists of Standard Semiconductor Devices."

FSC 6645

Source: https://assist.dla.mil - Downloaded: 2026-10-21T12:41Z
Check the source to verify that this is the current version before use.

* Delete title opposite MIL-STD-704 and substitute "Aircraft Electric Power Characteristics."

* Delete title opposite MIL-STD-810 and substitute "Environmental Test Methods and Engineering Guidelines."

* Delete title opposite MS24266 and substitute "Relay 10 AMP, 4 PDT, Type 1, Hermetically Sealed, Solder Hoops."

* Delete title opposite MS90386 and substitute "Indicator, Elapsed Time, Electrochemical (Mercury) 115 Volt AC, 50/2400 CPS 28 Volt DC or 5 Volt DC."

* Delete parenthetical source paragraph and substitute the following:

"(Copies of specifications and standards required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)"

Add the following new paragraph 2.1.2:

* "2.1.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable."

Add the following industry standard and parenthetical source statement.

* AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 Standard Practice for Commercial Packaging.

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

Add the following new paragraph 2.1.3:

* "2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence."

PAGE 3

3.1, delete in its entirety and substitute the following:

* "3.1 First Article - When specified, a sample shall be subject to first article inspection. (See 4.4 and 6.4)."

Add the following new paragraph 3.3.1.1

* "3.3.1.1 Reclaimed materials. The use of reclaimed materials shall be encouraged to the maximum extent possible."

Source: https://assist.dla.mil - Downloaded: 2026-10-21T12:41Z
Check the source to verify that this is the current version before use.

PAGE 11

* 3.6, line 3 delete "MIL-STD-100" and substitute "DOD-STD-100."

PAGE 13

* 4.1. line 2 and line 4, delete "supplier" and substitute "contractor."

* 4.2 delete subparagraph a and b and substitute the following:

"a. First article tests. (See 4.4)"

PAGE 14

* 4.4 delete "Qualification testing" and substitute:

"4.4 First Article Inspection"

* 4.4.1 delete last sentence.

* 4.4.3 delete in its entirety and substitute

"4.4.3 First Article Test - The first article test shall consist of all the tests specified under 4.6."

PAGE 24

Delete Section 5 "PREPARATION FOR DELIVERY" and substitute the following:

"5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be Level A, C or commercial/industrial as specified (see 6.2).

5.1.1 Level A. Each timer shall be preserved and packaged in accordance with Method IA8 of MIL-P-116.

5.1.2 Level C. The level C preservation and packaging shall conform to the requirements of MIL-STD-794 for this level. OR

Commercial/industrial preservation of timers shall be in accordance with the requirements of ASTM D 3951.

5.2 Packing. Packing shall be Level A, B or C or Commercial/industrial, as specified (see 6.2).

5.2.1 Level A. The timers preserved and packaged as specified in 5.1.1 shall be packed in a container conforming to PPP-B-636, weather resistant. The closure shall be in accordance with appendix of the container specified.

5.2.2 Level B. The timers preserved and packaged as specified in 5.1.1 shall be packed in a container conforming to PPP-B-636, weather resistant. The closure shall be in accordance with appendix of the container specified.

5.2.3 Level C. Timers preserved and packaged as specified in 5.1.1 shall be packed in a manner to ensure carrier acceptance and safe delivery at

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T12:41Z
Check the source to verify that this is the current version before use.

destination. Container shall be in accordance with either the uniform Freight Classification Rules or Regulations of the other carrier applicable to mode of transportation. OR

Commercial/industrial packing of timer shall be in accordance with the requirements of ASTM D 3951.

5.3 Marking. In addition to any other marking required by the order or contract, interior and exterior containers shall be marked in accordance with MIL-STD-129.

6.2.1 delete subparagraph c and substitute the following:

* "c. Levels of packaging and packing or commercial/industrial packaging required and reinspection data marking (see Section 5)."

PAGE 25

6.4 delete in its entirety and substitute the following:

* "6.4 First Article - When a first article inspection is required, the item will be tested and should be a first article sample or it may be a standard production item from the contractor's current inventory. The first article should consist of four units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests and approval of the first article."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 99

Review Activity:
Air Force - 11
DLA - GS

Preparing Activity:
Air Force - 82

(Proj. 6645-F368)

Source: https://assist.dla.mil - Downloaded: 2026-10-21T12:41Z
Check the source to verify that this is the current version before use.