MILITARY SPECIFICATION

BOMB, INERT, BLU-3(D-1)/B

METAL PARTS, LESS BODY, FOR

1. SCOPE

1.1 This specification covers the metal parts, less body, for one type of bomb designated as Bomb, Inert, BLU-3(D-1)/B.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of these provisions to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-Z-325	-	Zine, Coating, Electrodeposited, Requirements for
QQ-P-416	-	Plating, Cadmium (Electrodeposited)

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-C-5541	-	Chemical Films for Aluminum and Aluminum Alloys
MIL-A-8625	-	Anodic Coating for Aluminum Alloys

FSC: 1325

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

MIL-F-18240 - Fastener, Externally Threaded, 250°C Self Locking Element for

MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

FEDERAL

FED-STD-151 - Metals, Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

PL-9248737 - Bomb, Inert, BLU-3(D-1)/B

PUBLICATIONS

ARMY

ET-9266376 - Equipment Tabulation

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by the supplies in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117-64 - Standard Method of Salt Spray (Fog) Testing

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pa. 19103)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Parts.-The fuze parts and assemblies shall comply with all requirements specified on Drawing 9248737 and with all requirements specified in applicable specifications.

3.3 Embrittlement.-All components which require relief from hydrogen embrittlement shall not break when stressed to the minimum point of permanent distortion when tested as specified in 4.4.2.

3.4 Outside diameter of metal parts assembly.-The outside diameter of metal parts assembly, with components assembled to simulate a complete bomb, shall be 2.78 inches maximum (max) when inspected as specified in 4.4.14.

3.5 Vane functioning.-The finger spring of the vane when depressed shall rest between and clear the edges of the finger spring slot, and the vanes shall function satisfactorily as evidenced by the vanes swinging away from the cup and locking (with assistance) into position without permanent distortion of the affected parts, when tested as specified in 4.4.15.

3.6 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, greast, rust, and other foreign matter. The cleaning method used shall not be in-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

jurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.7 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract, the specification, or as required by the Contracting Officer (See 6.5).

3.8 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. the Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified within this specification.
b. Number of units of product inspected.
c. Results obtained, by defect code, for all inspections performed.
d. Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. (See 6.1) The first article sample shall consist of the following:

a. One hundred ten (110) metal parts assemblies consisting of stabilizer assembly, nester, catch spring, safety strap and spring tab.

b. Twenty-five (25) each component part.

c. Twenty-five (25) fuze assemblies inert.

All parts and completed assemblies submitted shall have been produced by the contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings, except that the tab, spring, 8862072, will be subjected by the Government to all dimensional requirements of the applicable drawing. In addition, any or all of the following examinations and tests will be performed.

4.2.2.1 Salt spray.-Four (4) of each of the following piece parts: 8862051, 8862055, 8862056, 8862062, 8862069, 8862070, 8880396 and 9247285 shall be subjected to this test in accordance with the applicable drawings and specifications: QQ-Z-325, QQ-P-416, MIL-C-5541 and MIL-A-8625. The test shall be performed as specified in 4.4.1.

4.2.2.2 Embrittlement (See 3.3).-Twenty (20) of each of the following piece parts shall be subjected to this test: 8862070, 8862062, 8862059 and 8880396. The test shall be performed as specified in 4.4.2.

4.2.2.3 Vane hardness (See Dwg 8862070).-Five (5) vanes shall be subjected to this test. The test shall be performed as specified in 4.4.3.

4.2.2.4 Plating thickness of vane (See Dwg. 8862070).-Four (4) vanes shall be subjected to this test. The test shall be performed as specified in 4.4.4.

4.2.2.5 Direction of grain of spring tab (See Dwg 8862072).-Five (5) spring tabs shall be subjected to this test. The test shall be performed as specified in 4.4.5.

4.2.2.6 Outside diameter of metal parts assembly (See 3.4).-The one hundred ten (110) metal parts assemblies consisting of stabilizer assembly, nester, catch spring, safety strap and spring tab shall be subjected to this test. The test shall be performed as specified in 4.4.7.

4.2.2.7 Vane functioning (See 3.5).-After completion of the test specified in 4.2.2.6, the assemblies shall be subjected to this test. The test shall be performed as specified in 4.4.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each lot of fuze assemblies shall contain:

Vanes of one lot interfix number from one manufacturer.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects,

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defects and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

In addition, at the option of the procuring activity, defect characteristics of the same classification which have been separated into two (2) groups to specifically allow the optional method of inspection in accordance with 4.3.3.1 and 4.3.3.2 may be combined into one (1) group when the option of 4.3.3.1 and 4.3.3.2 is not exercised. The AQL for the combined grouping will be as indicated in the applicable classification of defects paragraph. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Tab, spring (See Dwg 8862072 covering a detail of Dwg 9248737).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent (See 4.3.3.2)		
101.	Distance between tab, tip end	Gage	01001
102.	Radii of latching portion of tabs improper	Gage	01002
103.	Length of tip on latching portion of tabs	Gage	01003
104.	Protrusion of tabs on latching portion of tab	Gage	01004
105.	Length of tab	Gage	01005
106.	Crack	Visual	01006
Minor	AQL 1.50 Percent		
201.	Thickness of tab, minimum (min)	Gage	01007

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

202.	Radius of tab missing (6 places)	Visual	01008
203.	Evidence of poor workmanship (See 3.6)	Visual	01009

4.3.2.2 Strap, safety (See Dwg. 8862071 covering a detail of Dwg. 9248737).

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent (See 4.3.3.2)		
101.	Length from tab slot to tab slot	Gage	02001
102.	Length from end to tab slot	Gage	02002
103.	Length from side to tab slot	Gage	02003
104.	Width of thumb screw slot, min	Gage	02004
105.	Thickness	Gage	02005
106.	Distance of elongated dimple from end	Gage	02006
107.	Height of elongated dimple	Gage	02007
108.	Height of elongated dimple edge, max.	Gage	02008
109.	Radius missing under elongated dimple at detail "E"	Visual	02009
110.	Crack	Visual	02010
111.	Straight edge improper	Visual	02011
Minor	*(See 4.3.3.2)		
201.	Width	Gage	02012
202.	Length of tab slot	Gage	02013
203.	Width of tab slot	Gage	02014
204.	Length of thumb screw slot, min	Gage	02015
205.	Height of dimples	Gage	02016
Minor	*AQL 0.65 Percent		
206.	Evidence of poor workmanship (See 3.6)	Visual	02017

*Combined AQL for Minor defects 201-206 (See Para. 4.3.2) is 2.50 percent.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.2.3 Nester (See Dwg 8862065 covering a detail of Dwg. 9248737).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent (See 4.3.3.1)		
101.	Distance across outside tabs, maximum (max)	Gage	03001
102.	Wall thickness at base, min (when applicable)	Gage	03002
103.	Diameter at top of outer flange	Gage	03003
104.	Height of outer flange	Gage	03004
105.	Tab spacing improper	Gage	03005
106.	Incomplete mould fill	Visual	03006
Minor	AQL 1.50 Percent		
201.	Radii between tabs (6 places)	Gage	03007
202.	Diameter of hole	Gage	03008
203.	Evidence of poor workmanship (See 3.6)	Visual	03009

4.3.2.4 Spring, catch (See Dwg 8862066 covering a detail of Dwg 7248737).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.65 Percent (See 4.3.3.2)		
101.	Distance across tabs	Gage	04001
102.	Diameter of center hole	Gage	04002
103.	Height of small projection, min	Gage	04003
104.	Height of large projection, min	Gage	04004
inor	*(See 4.3.3.2)		
201.	Thickness	Gage	04005
Minor	*AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	04006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

*Combined AQL for Minor defects 201-202 (See Para. 4.3.2) is 1.00 Percent.

4.3.2.5 Vane (See Dwg 8862070 covering a detail of Dwg 8862067).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 1.50 Percent (See 4.3.3.2)		
101.	Total length across slots	Gage	05001
102.	Location of catch surface at hinge end	Gage	05002
103.	Distance, hole to vane tip	Gage	05003
104.	Radius at inside surface to vane tip	Gage	05004
105.	Distance from hole to vane stop	Gage	05005
106.	Distance from hole to inside surface of profile	Gage	05006
107.	Alignment of slot with sides	Gage	05007
108.	Distance from hole to inside free end profile	Gage	05008
109.	Distance from hole to outside surface of first bend	Gage	05009
110.	Radius at free end profile	Gage	05010
111.	Height of bend at free end profile	Gage	05011
112.	Width of finger spring slot, max	Gage	05012
113.	Width of finger spring, min	Gage	05013
114.	Length from base to end of finger spring	Gage	05014
115.	Triple radius contour of finger spring improper	Gage	05015
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	05016

4.3.2.6 Support, vane (See Dwg 8862069 covering a detail of Dwg 8862067).-

Categories	Defects	Method of Inspection	Defect Code

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.65 Percent (See Para 4.3.3.2)		
101.	Location of alignment hole	Gage	06001
102.	Diameter of location hole, min	Gage	06002
103.	Diameter of vane holes, max	Gage	06003
104.	Location of vane holes	Gage	06004
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	06005

4.3.2.7 Stabilizer assembly (See Dwg 8862067).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Rivet end not flattened	Visual	07001
102.	Height of each finger spring above vane surface	Gage	07002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	07003

4.3.2.8 Cup (See Dwg 8862051-3 covering a detail of Dwg 9248738).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.50 Percent (See Para 4.3.2.2)		
101.	Inside diameter	Gage	08001
102.	Location of safety strap slot	Gage	08002
103.	Length of safety strap slot (large dimension)	Gage	08003
104.	Distance from end of cup to safety strap slot	Gage	08004
105.	Location of crimp slots	Gage	08005
106.	Distance from end of cup to crimp slots	Gage	08006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

107.	Location of spring tab slots	Gage	08007
108.	Length of spring tabs slots (large dimension)	Gage	08008
109.	Width of spring tab slots (small dimension)	Gage	08009
110.	Distance from end of cup to spring tab slots	Gage	08010
111.	Total height, max	Gage	08011
112.	Height of large boss, max.	Gage	08012
113.	Large diameter of arming spring cavity	Gage	08013
114.	Small diameter of arming spring cavity	Gage	08014
Minor	*(See Para. 4.3.2.2)		
201.	Thickness	Gage	08015
Minor	*AQL 1.00 Percent		
202.	Color code improper	Visual	08016
203.	Evidence of poor workmanship (See 3.6)	Visual	08017

*Combined AQL for Minor defects 201-203 (See Para 4.3.2) is 1.50 Percent.

4.3.2.9 Spring, arming (See Dwg 8862062 covering a detail of Dwg 9248738).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Load at required height	Gage	09001
Minor	AQL 1.00 Percent		
201.	Outside diameter, max	Gage	09002
202.	Evidence of poor workmanship (See 3.6)	Visual	09003

4.3.2.10 Base (See Dwg 8862055 covering a detail of Dwg 9248739)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	*AQL 1.00 Percent		
101.	Diameter of retaining ring groove	Gage	10001
102.	Concentricity of retaining ring groove with largest outside diameter	Gage	10002
103.	Contour of retaining ring groove improper	Gage	10003
104.	Distance from shoulder to side of retaining ring groove	Gage	10004
105.	Width of retaining ring groove	Gage	10005
106.	Location of safety pin hole and length of hole to corner of slide cavity	Gage	10006
107.	Thickness of flange	Gage	10007
Major	*(See 4.3.3.1)		
108.	Location of slot	Gage	10008
109.	Outside diameter	Gage	10009
110.	Diameter of base cover cavity, max	Gage	10010
111.	Concentricity of outside diameter with diameter of base cover cavity	Gage	10011
112.	Distance from counterbore to slide cavity	Gage	10012

*Combined AQL for Major defects 101-112 (See Para 4.3.2) is 1.50 Percent.

Minor	AQL 1.50 Percent		
201.	Diameter of body	Gage	10013
202.	Total length	Gage	10014
203.	Finish improper	Visual	10015
204.	Evidence of poor workmanship (See 3.6)	Visual	10016

4.3.2.11 Cover, base (See Dwg 8862056 covering a detail of Dwg 9248739).-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent (See 4.3.3.1)		
101.	Outside diameter, min.	Gage	11001
102.	Total length	Gage	11002
103.	Concentricity of spring cavity with outside diameter	Gage	11003
Minor	AQL 1.50 Percent		
201.	Chamfer missing	Visual	11004
202.	Evidence of poor workmanship (See 3.6)	Visual	11005

4.3.2.12 Spring safety (See Dwg 8880396 covering a detail of Dwg 8862054).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Loads at required heights	Gage	12001
102.	Solid height, max	Gage	12002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	12003

4.3.2.13 Pin, safety (See Dwg 8880398 covering a detail of Dwg 8862054).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Total length	Gage	13001
102.	Length from flat end to first shoulder	Gage	13002
103.	Outside diameter	Gage	13003
104.	Diameter "O" ring groove	Gage	13004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

105.	Spherical radius missing	Visual	13005
106.	Finish improper in "0" ring groove and outside diameter	Visual	13006
Minor	AQL 1.50 Percent		
201.	Chamfer or radius missing	Visual	13007
202.	Radii improper	Visual	13008
203.	Evidence of poor workmanship (See 3.6)	Visual	13009

4.3.2.14 Base assembly, prior to assembling base cover (See Dwg 9248739 covering a detail of Dwg 9248738).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Safety pin protrudes into slider cavity when unrestrained	Visual	14001
102.	Safety pin staked improperly (See Para 4.3.3.5)	Visual	14002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	14003

4.3.2.15 Ring, retaining (See Dwg 9247285 covering a detail of Dwg 9248738).-

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Thickness	Gage	15001
102.	Width	Gage	15002
103.	Outside diameter	Gage	15003
104.	Contour improper	Gage	15004
105.	Width of slot	Gage	15005
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	15006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.2.16 Fuze assembly inert (See Dwg 9248737)

Categories	Defects	Method of Inspection	Defect Code
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Gap between crimp and delay assembly, max	Gage	16001
102.	Cup fails to move freely up and return freely without evidence of binding	Visual-Manual	16002
103.	Safety pin fails to move freely inward and return freely without evidence of binding	Visual-Manual	16003
104.	Retaining ring missing or improperly assembled	Visual	16004
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.6)	Visual	16005

4.3.3 Production test sampling

4.3.3.1 Dimensional control of cast parts.-In place of the normal sampling associated with the Classification of Defects and with the approval of the Contracting Officer, a sample of at least three (3) parts (as cast) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of 5000 parts. Individual cavity identification must be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test specified above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.3.2 Dimensional control of stamped parts.-In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.3.3.3 Salt spray, Major Defect, Defect Code 17001.-Four (4) of each piece part as specified in Para 4.2.2.1 shall be selected from each lot and subjected to this test in accordance with the applicable drawing and specifications QQ-Z-325, QQ-P-416, MIL-A-8625 and MIL-C-5541 as applicable. If one or more piece parts fail to comply with the applicable requirement, the lot shall be rejected. This test shall be performed as specified in 4.4.1.

4.3.3.4 Embrittlement (See 3.3) Major Defect, Defect Code 18001.-Twenty-five (25) of each of the applicable parts shall be selected from each lot and subjected to this test. If one (1) or more parts from a lot fail to comply with the applicable requirement, that specific part lot shall be rejected. The test shall be performed as specified in 4.4.2.

4.3.3.5 Pull test of safety pin of base assembly, (See Dwg 9248739) Major Defect, Defect Code 19001.-Twenty-five (25) base assemblies shall be randomly selected from those assemblies which have successfully met the requirement specified in Para 4.3.2.14, Major 102, and then subjected to this test. If one (1) or more base assemblies fail to comply with the applicable drawing requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.3.6 Vane hardness (See Dwg 8862070).-This test shall be performed as specified in 4.4.4.

4.3.3.6.1 Sampling

4.3.3.6.1.1 Batch type heat treatment, Major Defect, Defect Code 20001.-Five (5) vanes from each heat treatment charge or batch shall be selected for this test. If one (1) or more vanes fail to comply with the applicable drawing requirement, the lot shall be rejected.

4.3.3.6.1.2 Continuous heat treatment, Major Defect, Defect Code 20002.-Five (5) vanes per eight (8) hour's production or fraction thereof from one mill heat of steel shall be selected for this test. If one (1) or more vanes fail to comply with the applicable drawing requirement, the lot shall be rejected.

4.3.3.7 Plating thickness of vane (See Dwg 8862070) Major Defect, Defect Code 21001.-Four (4) piece parts shall be selected from each lot and subjected to this test. If one (1) or more vanes fail to comply with the applicable drawing requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.5.

4.3.3.8 Direction of grain of spring tab (See Dwg 8862072) Major Defect, Defect Code 22001.-Five (5) spring tabs shall be selected from each lot and subjected to this test. If one (1) or more spring tabs fail to comply with the applicable drawing requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.6.

4.3.3.9 Outside diameter of metal parts assembly (See 3.7) Major defect, Defect Code 23001.-One hundred fifty (150) of each metal parts assembly consisting of stabilizer assembly, nester, catch spring, safety strap, and spring tab shall be selected from each lot and subjected to this test. If two (2) or more assemblies fail to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.7.

4.3.3.10 Vane functioning (See 3.8) Major Defect, Defect Code 24001.-One hundred fifty (150) of each major parts assembly as specified in 4.3.3.9 shall be subjected to this test. If two (2) or more assemblies fail to comply with the applicable requirement, the lot shall be rejected. The test shall be performed as specified in 4.4.8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.3.4 Inspection equipment.-Equipment tabulation (ET) number 9266376 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3. Supply and maintanance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed.

4.3.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.4 Test methods and procedures

4.4.1 Salt spray.-The applicable parts shall be subjected to the salt spray test in accordance with ASTM standard method B 117-64. The number of hours shall be as specified on the applicable drawing. Parts so tested shall be discarded.

4.4.2 Embrittlement of springs.-The applicable springs shall be stressed to the minimum point of permanent distortion in the direction of intended use, by any method approved by the procuring activity. Parts so tested shall be discarded.

4.4.3 Pull test of safety pin of base assembly.-The base assembly shall be assembled to an approved fixture (See 4.3.4) and the load specified on the applicable drawing applied. Assemblies so tested, if acceptable, may be returned to the lot.

4.4.4 Vane hardness.-Reading shall be as specified on the applicable drawings except that Rockwell 15N scale readings (or equivalent Rockwell 15N scale readings) 1.0 point above or 1.0 below the applicable requirement, are acceptable. However, readings both above and below, in the same lot, are not acceptable. Vanes so tested may be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

4.4.5 Plating thickness of vane.-The vane shall be measured for plating thickness at three (3) spots approximately one inch apart on the outside surface as per applicable drawing requirement and QQ-P-416, Method 4.4.1.1. Vanes so tested shall be scrapped.

4.4.6 Direction of grain of spring tab.-The test shall be conducted by any method satisfactory to the Contracting Officer. Part so tested shall be scrapped.

4.4.7 Outside diameter of metal parts assembly.-The body assembly and fuze assembly are to be simulated as part of the fixture and all other components as specified in 4.3.3.9 shall be assembled to the simulated parts of the fixture to make a complete bomb assembly. The outside diameter shall be dimensionally checked using the gage specified on the Equipment List. The spring tab and safety strap so tested shall be scrapped. The stabilizer assembly, nester and catch spring so tested may be returned to the lot.

4.4.8 Vane functioning.-The metal parts assembly, as specified in 4.4.7 shall be assembled to a fixture as shown on the inspection equipment list and the vanes shall be released. The spring tab and safety strap so tested shall be scrapped. The stabilizer assembly, nester and catch spring so tested may be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C.-The stabilizer assembly shall be packaged with the vanes flat and in such a manner as to prevent the finger springs of the vanes from entanglement. Spacers shall be placed between successive layers of the stabilizer assembly. The stabilizer assemblies and all other parts and assemblies shall be preserved and packaged in accordance with MIL-STD-1169.

5.2 Packing

5.2.1 Level C.-The Bomb, Inert, BLU-3(D-1)/B, metal parts, less body, preserved and packaged as specified in 5.1.1, shall be packed for shipment in accordance with MIL-STD-1169.

5.3 Marking.-Marking of the carton shall comply with MIL-STD-1169.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

5.4 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (See 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Equipment lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basis classifications: Mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army Design, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, with the approval of the Government, design alternate inspection equipment to facilitate his operations. Such selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor design.-All submitted designs shall contain a reference to the applicable 5-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S. All

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.

other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of test data.-In addition to the normal distribution of records, when the Bomb, Inert, BLU-3(D-1)/B, Metal Parts, less Body, is procured by the U.S. Army Munitions Command, one (1) copy of all fuze assembly functioning data shall be forwarded to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

6.5 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-S.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1325-A-385

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:26Z
Check the source to verify that this is the current version before use.