MIL-D-60573(MU)
19 August 1966
SUPERSEDING
FA-PD-MI-2431, Rev. 0
3 July 1961
AMENDMENT 1
15 August 1962

MILITARY SPECIFICATION

DUMMY CARTRIDGE, 7.62MM, M172, INERT LOADED

1. SCOPE

1.1 This specification covers an inert-loaded dummy cartridge used for testing metallic link belts and the mechanism of 7.62MM small arms.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Standards for Small Arms Ammunition through Caliber .50
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition

DRAWINGS

Munitions Command

C10522688	- Dummy Cartridge, 7.62mm, M172, Inert Loaded
F10522703	- Packing and Marking, Dummy Cartridge, 7.62mm, M172, Inert Loaded
IEL-10522688	- Inspection Equipment List for Dummy Cartridge, 7.62mm, M172, Inert Loaded

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

AMCR 715-505 Volume 3 - Ammunition Ballistic Acceptance Test Methods, Volume 3, Test Procedures for 7.62mm Cartridges

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge shall comply with Drawing C10522688 referenced specifications and the following:

3.2 First article sample.- Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.3 Bullet extraction.- The force required to extract the bullet from the cartridge case shall be not less than 175 lbs.

3.4 Residual stress.- The cartridge case shall not split when subjected to a one percent mercurous nitrate solution for 15 minutes.

3.5 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specification and the following:

3.5.1 Metal defects.- The cartridge shall be free of splits.

3.5.2 Foreign matter.- The cartridge shall be free of corrosion, dirt and oil.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 300 cartridges. The samples shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and Test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Lot identification.- Each lot of ammunition shall be identified as to type, caliber and model, as well as with a lot number and the manufacturer's identification as assigned by the procuring activity. Each lot shall be further identified by a Federal Stock Number assigned by the procuring activity.

4.3.2 Examination.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality level (AQL) for the major class shall be 1.00 percent and the AQL for the minor class shall be 2.50 percent. All non-conforming cartridges shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of defects.- The classification of defects shall be as specified in Table I.

TABLE I

No.	Defect and Method of Inspection	Major	Minor
	Visual 1/		
	Cartridge		
1	Discolored, dirty, oily		X
2	Corroded or stained, if etched	X	
2A	Identification missing or incorrect	X	
	Case		
4	Round head	X	
5	Dent		X
6	Split case	X	
7	Perforated case	X	
10	Beveled underside of head	X	
11	Case mouth not crimped in cannelure	X	
12	Scaly metal		X
13	No chamfer on head (rim)	X	
14	Fold		X
15	Wrinkle		X
16	Buckle		X
17	Bulge		X
19	Defective head		X
20	Defective mouth		X
	Bullet		
24	Split bullet jacket		X
25	Loose bullet	X	
26	Missing cannelure	X	
27	Scaly metal (bullet)		X
	Gaging		
32	Total length	X	
33	Cartridge profile failure (requiring more than 20 pounds dead weight to insert in profile and alignment gage)	X	
34	Diameter of extractor groove, max.	X	
35	Diameter of extractor groove, min.		X
36	Diameter of head	X	
37	Thickness of head	X	
38	Length to shoulder datum	X	
	Weighing		
39	Weight, min.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

1/ Refer to MIL-STD-636 for visual standards for defects 1 through 27. In the event of conflict between Table I of this specification and MIL-STD-636 as to defect classification, the classification specified in Table I shall apply.

4.3.2.2 Inert charge.- The contents of each cartridge case obtained from the bullet extraction test shall be emptied and examined. The presence of propellant, in lieu of inert mixture, in any cartridge case shall be cause for rejection of the lot.

4.3.3 Tests.- The following tests shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Bullet extraction.- A sample of fifty cartridges shall be tested for bullet extraction. Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

4.3.3.2 Residual stress (Mercurous nitrate).- A sample of twenty cartridges shall be subjected to the mercurous nitrate test. Failure of two or more cartridges to comply with the applicable requirement shall be cause for rejection of the lot. If one cartridge fails in the first test, a second sample consisting of double the number of cartridges in the first sample may be tested. If any failing cartridges are found in the second sample, the lot shall be rejected.

4.3.4 Packaging, packing and marking inspection.- During or immediately prior to the packaging operation, 100% examination of the cartridges shall be performed to ascertain that no primer is present in the primer pocket. The presence of a primer shall be classed as a critical defect and all cartridges containing a primer shall be rejected. Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644 as applicable to the drawing.

4.3.5 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL 10522688.

4.4 Test methods and procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

4.4.1 Bullet extraction.- The test shall be conducted in accordance with AMCR 715-505, Volume 3. The rate of travel of the test head shall be not less than three nor more than six inches per minute.

4.4.2 Residual stress (Mercurous nitrate).- The test shall be conducted in accordance with AMCR 715-505, Volume 3.

5. PREPARATION FOR DELIVERY

5.1 Packing - Level A.- (Worldwide shipment) - The cartridges shall be packed in accordance with Drawing F10522703.

5.2 Marking and labeling.- Packing boxes shall be marked and labeled in accordance with the applicable drawing cited in 5.1, except that the marking and labeling shall refer to "Dummy Cartridge, 7.62MM, M172, inert loaded".

6. NOTES

6.1 Ordering data.- Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of ammunition presented to the Government.

6.1.4 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1305-A448

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*.
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:45Z
Check the source to verify that this is the current version before use.