MIL-J-83278A(USAF)
AMENDMENT 2
2 April 1980
SUPERSEDING
MIL-J-83278A(USAF)
AMENDMENT 1
23 May 1972

MILITARY SPECIFICATION

JACK, HYDRAULIC, TRIPOD MMU-129/E,
60 TON CAPACITY, 72- TO 144-INCH RANGE

This amendment forms a part of Military Specification
MIL-J-83278A(USAF), dated 2 September 1971.

PAGE 1

2.1: Delete and substitute:

"2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

PPP-B-601	Boxes, Wood, Cleated-Plywood

Military

MIL-P-116	Preservation-packaging, Methods of
MIL-H-5606	Hydraulic Fluid, Petroleum Base, Aircraft, Missile and Ordnance
MIL-C-6021	Casting, Classification and Inspection of
MIL-H-6083	Hydraulic Fluid, Petroleum Base, for Preservation and Operation
MIL-H-6875	Heat Treatment of Steels (Aircraft Practice), Process for
MIL-M-8090	Mobility, Towed Aerospace Ground Equipment, General Requirements for
MIL-C-13924	Coating, Oxide, Black, for Ferrous Metals
* MIL-P-25732	Packing, Preformed, Petroleum Hydraulic Fluid Resistant, 275°F
MIL-B-26195	Box, Wood-Cleated, Skidded, Load-bearing Base
MIL-H-81019	Hydraulic Fluid, Petroleum Base, Ultra-low Temperature
* MIL-P-83461	Packings, Preformed, Petroleum Hydraulic Fluid Resistant, Improved Performance at 275°F(135°C)

STANDARDS

Military

DOD-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-143	Standards and Specifications, Order of Procedures for the Selection of
MIL-STD-808	Finishes, Protective, and Codes, for Finishing Schemes for Ground and Ground Support Equipment

FSC 1730

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:44Z
Check the source to verify that this is the current version before use.

MIL-STD-810	Environmental Test Methods
MIL-STD-831	Test Reports, Preparation of
MIL-STD-889	Dissimilar Metals
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, With Appropriate Test Methods
MIL-STD-1472	Human Engineering Design Criteria for Military Systems, Equipment and Facilities

DRAWINGS

Air Force

43A13905	Connector Assembly - Hydraulic Hose, Female
56B6129	Socket - Ball Type Jack Pad

(Copies of specfications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)"

PAGE 7

3.7.1.1, line 3 (second sentence): Delete: "capped".

* 3.7.1.3: Delete and substitute:

"3.7.1.3 Ram packings and seals shall be of the O-ring type conforming to MIL-P-25732 or MIL-P-83461, with V-type teflon backup rings. Equivalent materials shall require approval of the procuring activity."

PAGES 8 & 9

* 3.7.2.1, line 7 (fifth sentence): Delete and substitute

"The packing shall be of the O-ring type conforming to MIL-P-25732 or MIL-P-83461(USAF)."

PAGE 9

Add:

"3.7.2.5 Pressure gage. A pressure gage shall be furnished to provide visual inspection of the cylinder fluid pressure under all load conditions. The gage dial shall have dual calibration markings and increments to permit direct reading of fluid pressure in pounds per square inch (psi) and static load in tons. The fluid pressure scale shall be calibrated in 500-psi increments up to 4,000 psi with incremental divisions. The load scale shall be calibrated in 10-ton increments up to 60 tons with incremental divisions."

PAGE 10

3.7.4.1, line 5: Add new sentence:

"The caster swivel shaft shall maintain a vertical position under all retraction/extension conditions."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:44Z
Check the source to verify that this is the current version before use.

* 3.12: Delete and substitute:

"3.12 Finishes and protective coatings. Cleaning, painting, plating, anodic films, and chemical treatment shall be in accordance with MIL-STD-808 and AF Drawing 7545352. Color shall be 24052 of FED-STD-595."

* NOTE: The margins of this amendment are marked with an asterisk to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Air Force - 11

Review activity:
Air Force - 99

Preparing activity:
Air Force - 11

Project No. 1730-F249

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:44Z
Check the source to verify that this is the current version before use.