DDD–C–486a
22 AUGUST 1951
SUPERSEDING
Fed. Spec. DDD–C–486
5 AUGUST 1937

FEDERAL SPECIFICATION

CLOTHS; WASH, TERRY CLOTH

This specification was approved on the above date by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. CLASSIFICATION

1.1 Type and class.—Wash cloths covered by this specification shall be of but one type and class.

1.2 Grade. — The wash cloths shall be furnished in the grade known commercially as firsts.

2. APPLICABLE SPECIFICATIONS

2.1 The following Federal Specifications, of the issues in effect on date of invitation for bids, form a part of this specification:

CCC–T–191—Textiles; General Specifications, Test Methods.
DDD–S–751—Stitches; Seams; and Stitching.

(Copies of Federal specifications and the Federal Specifications Index may be obtained upon application, accompanied by money order, coupon, or cash, to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Prices may be obtained from the Superintendent of Documents.)

2.2 Specifications and other publications applicable only to individual departments are listed in section 7.

3. REQUIREMENTS

3.1 Material.—Wash cloths shall be made of thoroughly cleaned cotton, free from waste.

3.2 Weave.—The fabric shall consist of warp and filling ground yarns and warp pile yarns, woven with a terry weave, except that there shall be a plain woven even border, not more than ½ inch wide, either on both sides and both ends or on both ends only. The cloths shall be single loop (pile yarns woven singly), and the border shall be not more than 1 inch from the ends of the cloth when woven on the ends only.

3.3 Dimensions.—The finished wash cloths shall be 12 by 12 inches, with a tolerance in either direction of plus or minus ½ inch.

3.4 Edges.—All raw edges shall be finished with not less than 13 stitches per inch, using stitching type EFd–1 as described in Federal Specification DDD–S–751.

3.5 Thread.—Sewing shall be done with either 2– or 3–cord white cotton thread with a breaking strength of not less than 2.35 pounds. (See 4.3.1.)

3.6 Physical requirements. — The wash cloths shall conform to the requirements in table I.

Source: https://assist.dla.mil/ Downloaded: 2026-10-26T12:35Z
Check the source to verify that this is the current version before use.

TABLE I.—*Physical requirements*

Weight		Yarns per inch, minimum			Ply			Breaking strength (grab method), minimum	
					Warp				
Per dozen	Tolerance	Warp and filling	Warp[1]	Filling[1]	Ground	Pile	Filling	Warp	Filling
Ounces 16	*Ounce* ± ½	100	65	32	2 or 1	2 or 1	1	*Pounds* 40	*Pounds* 35

[1] These minimums may not be used together but one or the other or both must be increased to meet the minimums specified for the sum of the number of yarns in the warp and filling.

3.7 Finish.—Unless otherwise specified, the wash cloth shall be bleached white and shall be free from sizing or other nonfibrous materials.

3.8 Identification.—If a woven design, or woven, embroidered, or stamped lettering is required, it shall be as specified (see 6.1). Any colors involved shall show good fastness to laundering and laundering agents containing active chlorine.

3.9 Workmanship. — The finished wash cloths shall be free from defects which affect the appearance or which may impair the serviceability.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Sampling.—Not less than 9 cloths shall be taken at random by the purchaser from each 3,000 cloths or fraction thereof, except that when the shipment is over 10,000 cloths, 3 cloths shall be taken from each one-tenth of the shipment.

4.2 Inspection.—Inspection shall be made at the point of delivery or at the factory, at the discretion of the purchasing agent.

4.3 Tests. — Tests shall be conducted in accordance with the applicable methods described in Federal Specifications CCC–T–191 and as hereinafter specified.

4.3.1 *Thread strength.* — Strength tests shall be made by the single-strand method on a pendulum (inclined-balance) type machine having smooth jaws of the flat grip or drum type. The drum shall be not less than ½ inch in diameter. The jaw at which the load is applied shall move at a uniform rate of 12 ± 2 inches per minute. The distance between the centers of the drums or between the flat grips at the beginning of the test shall be not less than 10 inches. If for any reason attributable to faulty operation, the strength of a specimen falls markedly below the average for the set, the result shall be disregarded and another specimen shall be broken. At least 10 specimens shall be broken and the results averaged.

5. PREPARATION FOR DELIVERY

5.1 Packaging.—Unless otherwise specified, commercial packages will be acceptable.

5.2 Packing.—The wash cloths shall be prepared for shipment to permit acceptance by carrier for transportation at the lowest applicable rate and to afford maximum protection from normal hazards of transportation.

5.3 Marking.—Unless otherwise specified, shipping containers shall be marked with the name of the commodity, as defined by the contract or order under which the shipment is made, the quantity contained therein, the name of the contractor, the number of the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:35Z
Check the source to verify that this is the current version before use.

contract or order, the name of the consignee, and the gross weight.

6. NOTES

6.1 Ordering data. — Purchasers should specify any particular design or marking required (see 3.8) and should exercise any desired options offered herein (see 3.7, 4.2, 5.1, 5.3, 7.2.3, and 7.2.6.1).

6.1.1 In the purchase of name-woven cloths, it is customary to accept "seconds" up to 10 percent of the shipment at a discount, which should be specified in the invitation for bids.

6.1.2 It is suggested that 10 percent in excess of or 5 percent less than, the stipulated number be accepted at contract price. This allows the manufacturer to dispose of cloths woven in excess of order.

Patent notice.—When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the nolder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

7. DEPARTMENTAL REQUIREMENTS

7.1 The following specifications and other publications, of the issues in effect on date of invitation for bids, and special requirements, form a part of this specification for purchases made under this specification by the respective departments.

7.2 Army, Navy, and Air Force.

7.2.1 *Applicable specifications.*

Federal Specifications:

CCC–T–191—Textiles; General Specifications, Test Methods.

Military Specifications:

JAN–P–106—Packaging and Packing for Overseas Shipment — Boxes; Wood, Nailed.

JAN–P–125—Packaging and Packing for Overseas Shipment—Barrier-Materials, Waterproof, Flexible.

JAN–P–140—Packaging and Packing for Overseas Shipment — Adhesives, Water-Resistant, Case-Liner.

MIL–B–3149—Baling of Clothing and Equipage.

MIL–M–3157—Marking of Domestic Shipments by Contractors for Supplies and Equipment Consigned to the Medical Departments of the Armed Services.

U. S. Army Specification:

100–2—Standard Specification for Marking Shipments by Contractors.

Navy Department Specifications:

General Specifications for Inspection of Material.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer. Both the title and identifying symbol or number should be stipulated when requesting copies.)

7.2.2 *Inspection procedures (Navy only).*— For Naval purchases the general inspection procedures shall be in accordance with Navy Department General Specifications for Inspection of Material.

7.2.3 *Color.*—When specified in the invitation for bids, the cloth shall be fully bleached or evenly dyed with vat dyes, an approved shade of olive drab No. 3, and shall show good fastness to weather, laundering, and bleaching. When olive-drab No. 3 cloths are specified, the sewing shall be done with olive-drab thread conforming to shade Q of the U. S. Army Standard Color Card.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:35Z
Check the source to verify that this is the current version before use.

7.2.4 *Tests.*

7.2.4.1 *Fastness to weather.*—Test for fastness to weather shall be conducted as prescribed in Federal Specification CCC–T–191, except that specimens shall be exposed for 30 days.

7.2.4.2 *Fastness to bleaching.*—Test for fastness to bleaching shall be conducted in accordance with the fastness to chlorine bleaching test prescribed in CCC–T–191.

7.2.5 *Packaging.* — Ten cloths shall be packaged in a bundle. Each bundle shall be tied with five-ply cotton twine.

7.2.6 *Packing.*—One hundred bundles, each containing 10 wash cloths, shall be packed in a bale for either domestic or overseas shipment in accordance with the requirements of Specification MIL–B–3149. Waterproof barrier shall not be required in bales for domestic shipment.

7.2.6.1 *Alternate packing.*—When specified in the invitation for bids, the following alternate packing shall be used. One hundred bundles, each containing 10 wash cloths, shall be packed in a nailed wood box conforming to the requirements of Specification JAN–P–106, type 2 load. Closure and strapping shall comply with the appendix thereto. Each box shall be lined with a sealed waterproof barrier (bag) fabricated from material conforming to requirements of Specification JAN–P–125. Barrier shall be sealed with waterproof adhesive conforming to the requirements of Specification JAN–P–140.

7.2.7 *Marking.*

7.2.7.1 Bales for domestic shipment (not containing waterproof barrier-material) shall be marked in accordance with the requirements of Specification MIL–B–3149, except that the service color marking shall not be applied. In addition, a domestic shipment code "DOMPK" shall immediately follow the stock number or nomenclature as illustrated in the following example:

Stock No.
DOMPK
Nomenclature
Quantity
Size
Weight
Cube

7.2.7.2 *Army (Quartermaster Corps only).*—Bales for overseas shipment (containing waterproof barrier-material) shall be marked in accordance with the requirements of MIL–B–3149, with the service color marking applied for the Army in Quartermaster green. No other identification will be necessary.

7.2.7.3 *Army (Quartermaster Corps only).*—Boxes shall be marked in accordance with the requirements of Specification MIL–B–3149.

7.2.7.4 *Medical Department.* — Bales or boxes consigned to the Medical Department of the Armed Services shall be marked in accordance with Specification MIL–M–3157.

NAVY INTEREST: Md

This specification is a part of Section IV, Part 5, of the Federal Standard Stock Catalog.

For sale by the Superintendent of Documents, Washington 25, D. C. Price 5 cents.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:35Z
Check the source to verify that this is the current version before use.