AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

TOWELS AND TOWELING, COTTON FOR GLASSWARE

This amendment was developed by the Federal Supply Service, General Services Administration, Washington, D. C., 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification DDD-T-00501D(GSA-FSS), dated May 26, 1967.

PAGE 1

Paragraph 2.1, under "Federal Specifications" delete "CCC-T-191 - Textile Test Methods" and add the following:

UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
PPP-B-636	-	Box, Fiberboard.
PPP-P-1134	-	Packaging and Packing of Cotton and Cotton-Synthetic Fiber Blend Fabrics.
PPP-T-76	-	Tape, Pressure-Sensitive Adhesive Paper (For Carton Sealing).

Under "Federal Standards" add:

"Fed. Test Method Std. No. 191 - Textile Test Methods."

PAGE 2

Paragraph 3.1.2, delete and substitute:

3.1.2 Thread. The cotton thread for hemming shall conform to IA2 of V-T-276. The thread used with stitch type 301 shall be ticket No. 50, 3 ply. The thread used with stitch type 401 shall be ticket No. 50, 3 ply for the needle and ticket No. 70, 2 ply for the looper.

Paragraph 3.5, delete and substitute the following paragraphs:

3.5 Hems and selvages. The finished towel shall be hemmed at each end. The sides of the towel shall have two fast selvages, or one fast selvage and one hemmed side or two hemmed sides. There shall be no raw edges showing on the finished towel.

3.5.1 End hems. The hem at each end of the towel shall be 1/4 to 3/8 inch wide. Stitching shall be 1/16 to 1/8 inch from the turned edges, 10 to 12 stitches per inch using stitch type 301 or 401 and seam type EFb-1 of Fed. Std. No. 751. The corners of the hems shall be backstitched at least 1/2 inch.

3.5.2 Side hems. When side hems are used, they shall be 1/4 to 3/8 inch wide. Stitching shall be 1/16 to 1/8 inch from the turned edges, 10 to 12 stitches per inch using stitch type 301 or 401 and seam type EFb-1 of Fed. Std. No. 751.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:35Z
Check the source to verify that this is the current version before use.

PAGE 4

Table II, under "Workmanship" delete "Less than 9 or more than 12 stitches per inch" and substitute "Less than 10 or more than 12 stitches per inch."

Table II, add the following defect under "Workmanship:" "Stitching less than 1/16 inch or more than 1/8 inch from turned edge Minor (X)".

Paragraph 4.3, line 1, delete "CCC-T-191" and substitute: "Fed. Test Method Std. No. 191."

PAGE 7

Paragraph 5.1.1.2, line 2, delete "PPP-P-51, Class 3" and substitute "PPP-P-1134."

Paragraph 5.1.2.2, delete "text" and substitute "No packaging required."

Paragraph 5.2.1.2, line 2, delete "PPP-P-51" and substitute "PPP-P-1134."

Paragraph 5.2.2.2, line 2, delete "PPP-P-51" and substitute "PPP-P-1134."

GSA DC 70-11685

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:35Z
Check the source to verify that this is the current version before use.