INCH-POUND

MS51866A
AMENDMENT 1
9 MARCH 1998

MILITARY STANDARD

NUT, SELF-LOCKING, SPLINE -GENERAL PURPOSE, 250° F

This amendment forms a part of MS51866A, dated 15 January 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

In Title Block, Change TITLE To: "NUT, SELF-LOCKING, SPLINE, NON-METALLIC INSERT, 250° ."

Delete: In Procurement Specification Block, "MIL-N-45913" Substitute: "MIL-DTL-25027"

Delete: In Figure Note "Configuration of Locking Feature (All-Metal or Non-Metallic Insert) Optional" Substitute: "Shape Of Top Optional"

Delete: Note 1. MATERIAL in entirety.

Substitute:
"MATERIAL: Steel, Grades 12L14 (UNS G12144) Per SAE J403, 1215 (UNS G12150) Per SAE J403, 1137 (UNS G11370) Per AMS5024, 11L37 (UNS G11374) Per AMS 5020.
Steel nuts shall meet mechanical property requirements in procurement specification for shear-type nuts.
Corrosion Resistant Steel (CRES), Type 303 (UNS S30300) Per AMS 5640.

Insert: Nylon Per ASTM D4066, Group 1, Class 1 or 2."

Delete Note 2. PROTECTIVE COATING in entirety.

Substitute "PROTECTIVE COATING: Steel Nuts, Cadmium Plate Per QQ-P-416, Type II, Class 2. CRES, Passivate Per ASTM A967."

Add Note 9. Nuts shall meet axial tensile strength requirements listed in procurement specification for shear-type nuts.

In Table, Change Thread Designations as follows:

"8-32 UNC-3B"	To	".1640-32UNJC-3B"
"10-32 UNF-3B"	To	".1900-32UNJF-3B"
"1/4-28 UNF-3B"	To	".2500-28UNJF-3B"
"5/16-24 UNF-3B"	To	".3125-24UNJF-3B"
"3/8-24 UNF-3B"	To	".3750-24UNJF-3B"
"7/16-20 UNF-3B"	To	".4375-20UNJF-3B"
"1/2-20 UNF-3B"	To	".5000-20UNJF-3B"

Custodians:
Army - AV
Navy - AS
Air Force - 99

Preparing Activity:
DLA-IS

(Project 5310-2345)

AMSC N/A FSC 5310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:11Z
Check the source to verify that this is the current version before use.