
MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-121/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the crystal unit described herein shall consist of this specification and the latest issue of MIL-C-3098.

Pertinent characteristics: 2 to 10 MHz; fundamental; controlled; antiresonance.



INCHES	MM	INCHES	MM
.002	.05	.050	1.27
.005	.13	.175	4.45
.008	.20	.238	6.05
.010	.25	.352	8.94
.015	.38	.486	12.34
.025	.64	.757	19.23
.035	.89	.775	19.69

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. The type designation, frequency, and code designation characters shall be not less than .038 (.97 mm) in height and not less than .027 (.69 mm) in width.
4. The pin undercut may be omitted.

Figure 1. Crystal unit - CR-120/U.

(D) denotes changes

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.

TABLE I. Requirements.

Requirement	Specified value or condition
Holder	HC-27/U (MIL-H-10056/14)
Dimensions, marking, and configuration	See figure 1
Frequency range	2 to 10 MHz, inclusive
Capacitance, shunt	6 pF, maximum
Frequency tolerance	±5 ppm at 85°C ±0.5°C
Antiresonance, load capacitance	50.0 ±0.5 pF
Mode of oscillation	Fundamental
Temperature range:	
Operating	85°C ±5°C
Operable	-55°C to +90°C, inclusive
Test set	TS-330/TSM, modified with RFL AGC adapter, model HB-16940 for low drive application
Drive level, rated	200 µW
Crystal quality (Q) 1/	300,000 minimum
Temperature coefficient of parallel resonant frequency	≤ 0.2 ppm per degree C at 85°C
Shock:	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±15 percent
Thermal shock:	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±15 percent
Vibration, high frequency: 2/	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±15 percent
Aging:	
Frequency change permitted	±0.4 ppm per week for the last 2 weeks of a 4-week aging test.

1/ $Q = \dfrac{1}{4\pi\,(\Delta f)(C_T)(R)}$

Where: Δf = difference, in Hz, between the series and antiresonant frequency at C_L (load capacitance) of 50 pF.

C_T = Capacitance: C_0 (shunt capacitance of the crystal unit) plus C_L (load capacitance) of 50 pF.

R = Motional-arm resistance of the crystal unit.

2/ Method 204 of MIL-STD-202, test condition A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.

(D) QUALITY ASSURANCE PROVISIONS:

Qualification inspection: Not applicable for this specification.

Quality conformance inspection: Group A tests of MIL-C-3098 shall be applicable.

NOTE:

NATO guidance type NXT 36.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI, AR, SM
Navy - SH
Air Force - 11, 99
DLA - ES

User activities:
Navy - AS, CG, MC, OS
Air Force - 17, 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5955-0617-5)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.