INCH-POUND
MIL-PRF-3098/100F
1 November 2017
SUPERSEDING
MIL-PRF-3098/100E
6 March 2013

PERFORMANCE SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR123/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-3098.

Pertinent characteristics: 50 MHz to 125 MHz; fifth mechanical overtone; controlled; series resonance.




FIGURE 1. Crystal unit - CR123/U.

AMSC N/A
FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.

Ltr	Inches		mm	
	Min	Max	Min	Max
A	---	.402	---	10.21
B	---	.183	---	4.65
C	---	.435	---	11.05
D	.184	.200	4.67	5.08
E	---	.530	---	13.46
F	.50	---	12.7	---
G	---	.150	---	3.81
H	.015	.019	0.38	0.48

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Marking to be in accordance with MIL-PRF-3098.

FIGURE 1. Type CR123/U, crystal unit - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions, marking, and configuration: See figure 1.

Frequency range: 50 MHz to 125 MHz, inclusive.

Capacitance, shunt: 4.5 pF, maximum.

Frequency tolerances:

Operating temperature range: ±10 ppm.

Reference temperature: ±10 ppm.

Room temperature: ±80 ppm.

Frequency stability: ±2.5 ppm.

Mode of oscillation: Fifth mechanical overtone.

Rated drive level: 1.0 mW, maximum.

Resonance: Series.

Reference temperature: +85°C ±1°C.

Temperature ranges:

Operating (controlled): +80°C to +90°C, inclusive.

Operable: -55°C to +80°C and +90°C to +100°C.

Equivalent resistance: 60 ohms, maximum.

Unwanted modes: Minimum unwanted mode effective resistance of 120 ohms or an unwanted to main mode resistance ratio of 3:1, whichever is greater.

Shock (specified pulse):

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Vibration: MIL-STD-202-204, test condition A; 0.06 inch double amplitude or 5 gravity units, whichever is less.

Frequency change permitted: ±5 ppm.

Equivalent resistance change permitted: ±10 percent.

Thermal shock: ±10 ppm.

Aging:

Frequency change permitted: ±5 ppm.

Reference documents. In addition to MIL-PRF-3098, this document references the following:

MIL-STD-202-204

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.

The margins of this specification sheet are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Review activities:
Air Force - 84, 99

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5955-2017-010)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:49Z
Check the source to verify that this is the current version before use.