
MILITARY SPECIFICATION SHEET

CRYSTAL UNIT, QUARTZ, CR-124/U

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the crystal unit described herein shall consist of this specification and the latest issue of MIL-C-3098.

Pertinent characteristics: 2.9 to 3.8 MHz; fundamental; noncontrolled; antiresonance.



INCHES	MM
.002	.05
.008	.20
.017	.43
.150	3.81
.183	4.65
.192	4.88
.402	10.21
.435	11.05
.50	12.7
.530	13.46

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.
3. The type designator, frequency, and manufacturer's code shall be not less than .038 (.97 mm) in height and not less than .027 (.69 mm) in width.

FIGURE 1. Crystal unit - CR-124/U.

Ⓐ denotes changes

FSC 5955

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:50Z
Check the source to verify that this is the current version before use.

Ⓐ TABLE I. Requirements.

Requirement	Specified value or condition
Holder	HC-18/U or HC-43/U (MIL-H-10056/9)
Dimensions, marking, and configuration	See figure 1.
Frequency range	2.9 to 3.8 MHz, inclusive
Capacitance, shunt	7 pF, maximum
Frequency tolerance (operating temperature range)	±50 ppm
Mode of oscillation	Fundamental
Government reference standard test set	TS-683/TSM
Rated drive level	1.0 ±0.2 mW
Calibration values:	
Resistance	150 ohms
Crystal current	2.7 mA
Antiresonance, load capacitance	32.0 ±0.5 pF
Operating temperature range (noncontrolled)	-55°C to +100°C, inclusive
Operable temperature range	-65°C to -55°C and +100°C to +105°C, inclusive
Equivalent resistance	450 ohms, maximum
Shock:	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±15 percent
Vibration: 1/	
Frequency change permitted	±5 ppm
Equivalent resistance change permitted	±15 percent
Thermal shock	±50 ppm
Aging:	
Frequency change permitted	±5 ppm

1/ Method 204 of MIL-STD-202, test condition A, 0.10 inch double amplitude or 5 gravity units (55 to 500 cycles per second), whichever is less.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 85
DLA - ES

User activities:
Air Force - 17, 19

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5955-0623-24)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T16:50Z
Check the source to verify that this is the current version before use.